TABLE 5

	Fittings		
Pipe	Schedule	Sizes	Maximum Working Pressure
160 psi (SDR 26) (1102.4 kPa)	40	1/2" thru 8" incl. (12.7 mm - 203 mm)	160 psi - 1102.4 kPa
	80	1/2" thru 8" incl. (12.7 mm - 203 mm)	160 psi - 1102.4 kPa
200 psi (SDR 21) (1378 kPa)	40	1/2" thru 4" incl. (12.7 mm - 102 mm)	200 psi - 1378 kPa
	80	1/2" thru 8" incl. (12.7 mm - 203 mm)	200 psi - 1378 kPa
250 psi (SDR 17) (1722.5 kPa)	40	1/2" thru 3" incl. (12.7 mm - 76 mm)	250 psi - 1722.5 kPa
	80	1/2" thru 8" incl. (12.7 mm - 203 mm)	250 psi - 1722.5 kPa
315 psi (SDR 13.5) (2170.4 kPa)	40	1/2" thru 1-1/2" incl. (12.7 mm - 38 mm)	315 psi - 2170.4 kPa
	80	1/2" thru 4" incl. (12.7 mm - 102 mm)	315 psi - 2170.4 kPa
Schedule 40	40 80	1/2" thru 1-1/2" incl. (12.7 mm - 38 mm)	320 psi - 2204.8 kPa
	40 80	2" thru 4" incl. (51 mm - 102 mm)	220 psi - 1515.8 kPa
	40	5" thru 8" incl. (127 mm - 203 mm)	160 psi - 1102.4 kPa
Schedule 80	40	1/2" thru 1-1/2" incl. (12.7 mm - 38 mm)	320 psi - 2204.8 kPa
	40	2" thru 4" incl. (51mm - 102 mm)	220 psi - 1515.8 kPa
	40	5" thru 8" incl. (127 mm - 203 mm)	160 psi - 1102.4 kPa
	80	1/2" thru 4" incl. (12.7 mm - 102 mm)	320 psi - 2204.8 kPa
	80	5" thru 8" incl. (127 mm - 203 mm)	250 psi - 1722.5 kPa