

- The kitchen	40 square feet	5 feet
- The bathroom	30 square feet	5 feet
- The lavatory	15 square feet	3 feet

In addition to this, it is acceptable in some of the service rooms such as the maid's room and the janitor's room that the floor area can be (70) square feet and the limit inferior for the dimension is (7) feet.

Article (9) : Passages:

The limit inferior for the net width of the public passages in buildings should be as the following:

- a. Residential and office buildings:
 - (6) feet for the plots whose area is more than (2500) square feet.
 - (5) feet for the plots whose area is less than (2500) square feet.
- b. Residential buildings for workers:
 - (6) feet if the rooms are from two sides.
 - (4.5) feet if the rooms are from one side.
- c. Commercial passages:
 - (10) feet
- d. The passages between classes in an educational buildings (schools, colleges and universities)
 - (10) feet if the passages are opened to the classes from two sides.
 - (8) feet if the passages are opened to the classes from one side.
- e. The buildings of public usages(it is not mentioned in the previous sections):
 - It is according to the nature of the usage with a limit inferior (3) feet.
- f. The limit inferior for the net width of the inner passages between rooms in the apartments and offices should not be less than (3) feet.
- g. It is stated to decrease the width of some passages in the buildings that have a small spaces and where the form of the ground and its dimensions do not allow having passages with the required width according to the above sections.
- h. It stated to put stall in the commercial passages, in this case, there should be passages with width (5) feet on the two sides of the stall providing that these stalls are not connected or interconnected with each other for more than (20) feet and the distance among them is not less than (10) feet and the width of the stall is not more than (6) feet.
- i. The limit inferior for the net height of the passage must not be less than:
 - (8) feet for apartments, offices and worker's buildings.
 - In the special buildings, the limit inferior for the height of the passages should be according to the nature of use where its limit inferior should not be less than (8) feet.

Article (10): Open galleries:

In the buildings that are overlooking the street and in which it is decided to build open galleries in it, it should be provided with beams in front of the frontage of those buildings with observing the following conditions: