FprEN 12464-1:2011 (E)

Table 5.53 — Transportation areas - Railway installations

| Ref. no. | Type of area, task or activity | Ē _m | UGR _L | U ₀ | R _a | Specific requirements |
|----------|--|----------------|------------------|----------------|----------------|--|
| 5.53.1 | Fully enclosed platforms, small number of passengers | 100 | - | 0,40 | 40 | Special attention to the edge of the platform. |
| | | | | | | Avoid glare for vehicle drivers. |
| | | | | | | 3. Illuminance at floor level. |
| 5.53.2 | Fully enclosed platforms, large number of passengers | 200 | - | 0,50 | 60 | Special attention to the edge of the platform. |
| | | | | | | Avoid glare for vehicle drivers. |
| | | | | | | 3. Illuminance at floor level. |
| 5.53.3 | Passenger subways (underpasses), small number of passengers | 50 | 28 | 0,50 | 40 | Illuminance at floor level |
| 5.53.4 | Passenger subways (underpasses), large number of passengers | 100 | 28 | 0,50 | 40 | Illuminance at floor level. |
| 5.53.5 | Ticket hall and concourse | 200 | 28 | 0,50 | 40 | |
| 5.53.6 | Ticket and luggage offices and counters | 300 | 19 | 0,50 | 80 | |
| 5.53.7 | Waiting rooms | 200 | 22 | 0,40 | 80 | |
| 5.53.8 | Entrance halls, station halls | 200 | | 0,40 | 80 | |
| 5.53.9 | Switch and plant rooms | 200 | 28 | 0,40 | 60 | Safety colours must be recognisable. |
| 5.53.10 | Access tunnels | 50 | - | 0,40 | 20 | Illuminance at floor level. |
| 5.53.11 | Maintenance and servicing sheds | 300 | 22 | 0,50 | 60 | |

6 Verification procedures

6.1 General

Specified design criteria which are listed in this European Standard shall be verified by the following procedures.