The term $0.2W$ that previously appeared in these combinations has been removed and has been replaced by a requirement to check lateral stability. One approach for meeting this requirement, which is based on recommendations of the Structural Stability Research Council (Galambos 1998),is to apply lateral notional forces, $N_i = 0.002\ \Sigma P_i$, at level i, in which ΣP_i = gravity force from Eq. 2.5-1 or 2.5-2 acting at level i, in combination with the loads stipulated in Eq. 2.5-1 or 2.5-2. Note that Eq. 1.4-1 stipulates that when checking general structural integrity, the lateral forces acting on an intact structure shall equal 0.01 w_x, where w_x is the dead load at level x.

REFERENCES

Breen, J. E., and Siess, C. P. (1979). "Progressive collapse—Symposium summary." *ACI J.,* 76(9), 997–1004.

Carper, K., and Smilowitz, R. (eds.). (2006). "Mitigating the potential for progressive disproportionate collapse." *J. Perf. of Constr. Fac.,* 20(4).

Chalk, P. L., and Corotis, R. B. (1980). "Probability models for design live loads." *J. Struct. Div.,* 106(10), 2017–2033.

Department of Defense (DOD). (2009). *Design of buildings to resist progressive collapse,* Department of Defense, Washington, D.C., Unified Facilities Criteria (UFC) 4-023-03, July.

Ellingwood, B. (1981). "Wind and snow load statistics for probabilistic design." *J. Struct. Div.,* 107(7), 1345–1350.

Ellingwood, B., and Corotis, R. B. (1991). "Load combinations for buildings exposed to fires." *Engineering Journal, ASIC,* 28(1), 37–44.

Ellingwood, B. R., and Dusenberry, D. O. (2005). "Building design for abnormal loads and progressive collapse." *Computer-Aided Civil and Infrastruct. Engrg*. 20(5), 194–205.

Ellingwood, B., and Leyendecker, E. V. (1978). "Approaches for design against progressive collapse." *J. Struct. Div.,* 104(3), 413–423.

Ellingwood, B. R., and Li, Y. (2009). "Counteracting structural loads: Treatment in *ASCE Standard 7-05*." *J. Struct. Engrg. (ASCE),* 135(1), 94–97.

Ellingwood, B., MacGregor, J. G., Galambos, T. V., and Cornell, C. A. (1982). "Probability-based load criteria: Load factors and load combinations." *J. Struct. Div.*, 108(5), 978–997.

Eurocode 1. (2006). *Actions on structures, Part 1–7: General actions–Accidental actions*, EN 1991-1-7.

Federal Emergency Management Agency (FEMA). (2004). *NEHRP recommended provisions for the development of seismic regulations for new buildings and other structures,* Federal Emergency Management Agency, Washington, D.C., FEMA Report 450.

Galambos, T. V., ed. (1998). *SSRC guide to stability design criteria for metal structures,* 5th ed., John Wiley, New York.

Galambos, T. V., Ellingwood, B., MacGregor, J. G., and Cornell, C .A. (1982). "Probability-based load criteria: Assessment of current design practice." *J. Struct. Div.*, 108(5), 959–977.

General Services Administration (GSA). (2003). *Progressive collapse analysis and design guidelines for new federal office buildings and major modernization projects,* General Services Administration, Washington, D.C.

Marjanishvili, S., and Agnew, E. (2006). "Comparison of various procedures for progressive collapse analysis." *J. Perf. of Constr. Fac.,* 20(4), 365–374.

Mehta, K. C., et al. (1998). *An investigation of load factors for flood and combined wind and flood,* Report prepared for Federal Emergency Management Agency, Washington, D.C.

Nair, R. S. (2006). "Preventing disproportionate collapse." *J. Perf. of Constr. Fac.,* 20(4), 309–314.

National Institute of Standards and Technology (NIST). (2007). *Best practices for reducing the potential for progressive collapse in buildings,* National Institute of Standards and Technology, Gaithersburg, Md., NISTIR 7396.

Pate-Cornell, E. (1994). "Quantitative safety goals for risk management of industrial facilities." *Struct. Safety,* 13(3), 145–157.

Taylor, D. A. (1975). "Progressive collapse." *Can. J. Civ. Engrg.,* 2(4), 517–529.

Turkstra, C. J., and Madsen, H. O. (1980). "Load combinations in codified structural design." *J. Struct. Div.*, 106(12), 2527–2543.