

- seismic design requirements, 483
- snow loads, 433
- wind loads, 262, 264, 309, 321, 332, 349f, 354f, 356f, 555, 564–566, 572
- partial loading
 - live loads, 408
 - snow loads, 31–32, 38f, 431
- partitions, 408
 - defined, 60
 - seismic design requirements, 118–119
- passenger vehicle garages, 410–411
- p*-delta effect, 1, 60
- Peabody, A.B., 455, 458
- peak ground acceleration, 209
- Peck, R.B., 397
- Peir, J.C., 407
- performance-based engineering applications, 390
- Periard, G., 461
- periodic special inspection, 60
- Perry, D.C., 526
- Peter, B.G.W., 427
- Peterka, J.A., 460, 509, 510, 570, 571, 575
- pile
 - anchorage requirements, 99–100
 - batter piles, 99
 - defined, 60
 - detailing requirements for, 131
 - pile group effects, 100
 - pile soil interaction, 100
 - splices of pile segments, 100
- pile cap, 60
- piping systems, 124, 486–488
- pitched free roofs, 288f, 552
- pitched roof, 411
- plan irregularities, 493
- Pohlman, J.C., 455
- pole-type structures, 98–99
- ponding instability
 - rain loads, 43, 447–448, 450f–451f, 452t
 - snow loads, 33, 434
- population risk, 382
- Powell, M.D., 511, 515
- Power, B.A., 457
- power actuated fasteners, 115
- precast structural walls, 129, 130
- Pressure Model, 575
- pressure piping systems, 124, 488
- pressure vessels, 125
- “principal action–companion action” format, 390
- probability-based limit states design, 390
- promenades, 408
- quality assurance provisions, 359–362
 - contractor responsibility, 360
 - details, 359–360
 - reporting/compliance procedures, 362
 - scope, 359
 - special inspection and testing, 360–361
 - structural observations, 362
 - testing, 361–362
- raceways, 123, 486
- Rack Manufacturers Institute (RMI), 236
- Rainer, J.H., 581
- rain loads
 - controlled drainage, 43, 448
 - design rain loads, 43, 447
 - ponding instability, 43, 447–448, 450f–451f, 452t
 - roof drainage, 43, 447
- rain-on-snow surcharge load, 33, 434, 435, 436
- Rawlins, C.B., 456
- Rayleigh-Ritz method, 494
- recognized literature, 243
- registered design professional, 60
- reinforcing steel, 360
- Reinhold, T.A., 526, 575
- relative displacements, 98, 112, 114–116, 119, 484
- reliability index selection, 391
- reporting and compliance procedures, 362
- required strength, 61
- resistance factor, 1
- response history procedure, 170, 173
- response modification coefficients (*R*), 134
- response spectrum procedure
 - isolated structures, 169–170, 173
 - structures with damping systems, 184–187
- Reynolds numbers, 357, 461
- Richmond, M.C., 455, 456
- ridge, 243
- Rigato, A., 576
- rime, 47
- risk-adjusted maximum considered earthquake ground motion response accelerations, 60
- risk categories, 380–382, 382f
- risk category, 1, 2t, 5, 5t
- Risk Management Plan, 383
- Robbins, C.C., 455
- Robertson, A.P., 563
- robustness, 393
- rock, shear wave velocity for, 203–204
- rocking stiffness, 199, 501
- Ronan Point disaster, 378
- roof drainage, 43
- roof live load, 13, 15–16, 408