



Table 404.01 (1): Maximum VOC Content Limit Values for Paints and Coatings

Product Sub-Category	Type**	VOC (g/l)*
Interior meth wells and seilings (Class 42E @ COS)	WB	30
Interior matt walls and ceilings (Gloss <25 @ 60°)	SB	30
	WB	100
Interior glossy walls and ceilings (Gloss >25 @ 60°)	SB	100
First and the Control of the control	WB	40
Exterior walls of mineral substrate	SB	430
Interior/Exterior trim and cladding paints for wood and metal	WB	130
	SB	300
Interior/Exterior trim varnishes and wood stains, including	WB	130
opaque wood stains	SB	400
	WB	130
Interior/Exterior minimal build wood stains	SB	700
	WB	30
Primers	SB	350
Dr. H	WB	30
Binding primers	SB	750
	WB	140
One-pack performance coatings	SB	500
Two-pack reactive performance coatings for specific end	WB	140
use such as floors	SB	500
Multi-colored coatings	WB	100
	SB	100
	WB	200
Decorative effect coatings	SB	200

^{*} Ready to use

COMPLIANCE DOCUMENTATION

Table 404.01(2): Documents Required

Project Stages	Submittal Documents
Design Permit Application	1. DM BLDG Al Sa'fat declaration.
Construction Completion Application	 DCL certificate. Purchase order/delivery notes as a proof of purchase.
After Completion	Not applicable

REFERENCES AND ADDITIONAL INFORMATION

Dubai Municipality. (2015). Standard DMS 20:2015—Specification for Paints and Varnishes Dubai Central Laboratory. (2018). Specific Rules for FA Certification of Low Emitting Materials as per Al Sa'fat Dubai Green Building System.

^{**} WB- Water Based SB-Solvent Based