6.5.4.	Variable Frequency Drives	67
6.5.5.	Motor Control Centre	
6.5.6.	Protection Device	
6.5.7.	Power Factor Correction Capacitors	
6.5.8.	Earthing	
6.5.9. 6.5.10.	Lightning Protection	
6.5.11.	Uninterruptible Power Supply	
6.5.12.	Cables	
6.5.13.	Mobile Generator Junction Box / Stand-by Generator with ATS	70
	trumentation	
6.6.1.	Level Measurement Sensors	
6.6.2.	Methods of Flow Measurement	
6.6.3. 6.6.4.	Compatibility to SCADAControl Systems	
6.6.5.	Pump Control Philosophy	73 73
6.6.6.	Fieldbuses	
6.6.7.	SCADA System	
6.7. Str	uctural Design	
7.	PUMPING MAIN DESIGN	77
	oduction	
7.1. Intr 7.2. Pip	e Material Selection	
7.2. Fip	draulic Design of Pumping Mains	76 78
7.3.1.	Design Considerations	78
7.3.2.	Friction Head Losses	79
7.3.3.	Localised Head Loses	
	uctural Design	
7.4.1. 7.4.2.	Internal Forces	
7.4.2. 7.4.3.	Temperature Range Unbalanced Thrust	
_	Ves	
7.5.1.	Valve Selection	
7.5.2.	Valve Losses	
7.5.3.	Flushing Flow	
7.5.4.	Maximum Draining Flow	
7.5.5. 7.5.6.	Draining TimeActuators	
7.5.0. 7.5.7.	Equipment Isolation Valves	84
7.5.8.	Check and Flap Valves	
7.5.9.	Air Release and Vacuum Valves	
7.5.10.	Washout Valves	
	ve Chambers	
7.6.1. 7.6.2.	Flow Meter Chamber	
7.6.2. 7.6.3.	Air Valve ChamberWashout chamber	
8.	DESIGN SUBMISSION REQUIREMENTS	
	neral	
	quired Standards	
	omission Requirementssign Review Stages and Requirements	
8.4.1.	General Notes	
8.4.2.	Preliminary Design	
8.4.3.	Detailed Design	91
	nnection to Existing Approval	
	mpliance form	
	eck listdraulic Modelling Shape File Data Requirements	
•	9 ,	
9.	REFERENCES	101
10.	APPENDIX	102