

- Wadhera, D., 510
- wall
  - segments, 489
- wall drift, 365, 580–581
- Wallis, J.R., 460
- wall pier, 129–130, 489
- walls, 61
  - anchorage, 96–97
  - detailed plain concrete shear, 490
  - intermediate precast structural, 489–490
  - wind loads, 335f
- wall system, bearing, 62
- Walmsley, J.L., 519
- Walton, T.L. Jr., 418
- Wang, Q.J., 460
- wave loads, 22–25, 417–418
- Weitman, N., 433, 435
- welded steel, 155
- Wen, Y.K., 513
- West, M., 579, 580
- West, R.J., 455
- wheel loads, 16
- White, H.B., 456, 461
- Willis, W.E., 427
- wind
  - directionality, 246
  - on ice-covered structures, 49, 461–462
- wind-borne debris regions, 244, 508
- wind hazard map, 246, 247f, 248f
- wind loads
  - calculating, 522
  - wind tunnel procedure, 357–358
- wind loads (components and cladding), 315–355, 569–572
  - air-permeable cladding, 315–316, 569
  - all heights, 344f
  - buildings less than 160 ft, 321, 322t–324t, 345f–347f, 572
  - buildings over 60 ft, 320, 334, 335f–343f, 348f, 572
  - exposure C, 325t–330t
  - general requirements, 315–316
  - low-rise buildings, 318–319, 318t, 319t, 572
  - open buildings, 331, 572
  - parapets, 321, 332, 349f, 354f, 572
  - roof overhangs, 321, 333, 350f, 355f, 572
  - scope, 315
  - velocity pressure, 316, 317t
  - wall and roof pressures, 322t–324t, 346f–348f
- wind loads (general requirements)
  - ASCE cross reference of sections, 531t–535t
  - basic wind speed, 246, 508–512, 538t–539t
  - Davenport classification of effective terrain roughness, 541t
  - definitions, 241–244, 506–508
  - design wind speeds, 540t
  - enclosure classification, 255, 257, 524–525
  - exposure, 246, 251, 514–518, 516f, 517f
  - general, 245–246, 505–506
  - gust effects, 254–255, 256f, 519–524, 542t–543t
  - internal pressure coefficient, 257–258, 525–526
  - procedures, 241
  - special wind regions, 512
  - symbols and notation, 244–245, 508
  - topographic effects, 251, 252f–253f, 254, 518–519
  - wind directionality, 246, 250f, 513–514
  - wind hazard map, 246, 247f, 248f, 249f
- wind loads on buildings—MWFRS (directional procedure)
  - ambient air density values, 551t
  - building geometry requirements, 292f
  - design wind load cases, 291f, 552–553
  - enclosed/partially enclosed/open buildings, 259–262, 547–553, 550t
  - enclosed simple diaphragm buildings, 263–265, 269t–270t, 293f–295f, 553–555
  - general requirements, 259, 260t, 263
  - parapets, 555
  - roofs, 271t–282t, 283f–292f, 554, 555
  - roughness change, 547–549
  - scope, 259
  - velocity pressure, 259–260, 261t, 547
  - walls, 266t–268t, 554
- wind loads on buildings—MWFRS (envelope procedure), 297–306, 557–561
  - basic load cases, 300f
  - enclosed/partially enclosed low-rise buildings, 297, 557–560, 558f, 559f
  - enclosed simple diaphragm low-rise buildings, 302, 560–561
  - general requirements, 297
  - main wind-force resisting system, 298, 302, 303f–305f, 306
  - scope, 297
  - torsional load cases, 301f
  - velocity pressure, 297–298, 299t, 557
- wind loads on other structures and building appurtenances, 307–314
  - general requirements, 307
  - minimum design wind loading, 309, 566
  - open signs/lattice frameworks, 313f
  - parapets, 309
  - roof overhangs, 309