| Oxidizers, liquid and solid Table 414.2.5(1),<br>Table 414.5.1, 415.8.4,<br>Table 415.11.1.1.1 | HIGH-PILED COMBUSTIBLE STORAGE 413<br>907.2.15, 910.2.2<br>HIGH-PRESSURE DECORATIVE EXTERIOR- |
|--|---|
| Pyrophoric materials Table 307.1(1), 307.4,  | GRADE COMPACT LAMINATES 1408  |
| Table 414.5.1, 415.7.1,  | HIGH-RISE BUILDINGS 403   |
| 415.8.4, Table 415.11.1.1.1  | Alarms and detection 403.4.1, 403.4.2, 907.2.13   |
| Sensitizers Table 415.11.1.1.1   | Application   |
| Solids, highly toxic and toxic   | Construction  |
| Table 414.2.5(1), 415.10.4,  | Elevators   |
| Table 415.11.1.1.1, 908.3  | Emergency power   |
| Unstable materials 307.3, Table 414.2.5(1),<br>Table 414.5.1, 415.5.4,                         | Emergency systems403.4  |
| Table 414.5.1, 415.5.4,  | Fire command station  |
| Water-reactive materials Table 414.5.1,  | Fire department communication 403.4.3, 403.4.4  |
| 415.8.3, 415.8.4, 415.8.5,   | Fire service elevators  |
| 415.11, Table 415.11.1.1.1   | Occupant evacuation elevators 403.6.2, 3008   |
| Sprinkler protection 415.2, 415.11.6.4,  | Smoke removal   |
| 415.11.9, 415.11.10.1,   | Smokeproof enclosure  |
| 415.11.11, 705.8.1, 903.2.5  | Sprayed fire-resistant materials (SFRM) 403.2.4   |
| Standby, emergency power2702.2   | Sprinkler protection  |
| Storage 413, 414.1, 414.2.5,   |   |
| 414.5, 414.6, 415.6,   | Stairways   |
| Table 415.6.2, 415.7.1,  | Standby power   |
| 415.9.1, 426.1   | Structural integrity  |
| Unlimited area   | Super high-rise (over 420 feet) 403.2.1, 403.2.3<br>403.2.4, 403.3.1, 403.5.2                 |
| HEAD JOINT, MASONRY  | Voice alarm   |
| <b>HEADROOM</b>  | Zones   |
| 1010.1.1.1, 1011.3, 1012.5.2, 1207.2   | HISTORIC BUILDINGS  |
| HEALTH CARE  | Flood provisions  |
| (see INSTITUTIONAL I-1 AND INSTITUTIONAL I-2)  | HORIZONTAL ASSEMBLY   |
| Ambulatory care facilities 202, 422  | Continuity  |
| Clinics, outpatient  | 711.2.3, 713.11, 713.12   |
| Hospitals  | Fire-resistance rating 603.1(1), 603.1(22)  |
| HEALTH-HAZARD MATERIALS 307.2,   | 603.1(23), 703, 704.4.2   |
| Table 414.2.5(1), 415.2,   | 707.3.10, 711.2.4   |
| 415.11.1.1.1, Table 415.11.6.1   | Glazing, rated  |
| <b>HEAT VENTS</b> 910  | Group I-1   |
| HEATING (see MECHANICAL) 101.4.2   | Group R   |
| Aircraft hangars 412.3.4   | Incidental  |
| Fire pump rooms  | Insulation  |
| Fireplace  | Joints  |
| Masonry heaters  | Nonfire-resistance rating   |
| Parking garages406.2.9   | Opening protection 712.1.13.1, 714.5, 716, 717.6  |
| Repair garages   | Shaft enclosure   |
| <b>HEIGHT, BUILDING</b> 503, 504, 505, 508, 510  | Special provisions  |
| Limitations  | Atrium  |
| Mixed construction types 510   | Covered and open mall buildings 402.4.2.3   |
| Modifications  | 402.8.7   |
| Roof structures  | Fire pumps  |
| HELIPORT   | Flammable finishes  |
| Definition   | Group H-2 415.9.1.1, 415.9.1.2  |
| Live loads   | Groups H-3 and H-4 415.10.2   |
|  | Group H-5   |