- Figure 10. Example of planter that correctly exceed the imaginary detection cone
- Figure 11. Interaction spaces in front desk and beside a bench
- Figure 12. KEEP CLEAR area
- Figure 13. Section of guardrails with and without glass
- Figure 14. Transversal section of a ramp
- **Figure 15.** Maximum rise and length for ramps with details of handrails required and different alternatives for handrails ends
- Figure 16. Example of a ramp with an intermediate handrail
- Figure 17. Dimension of corridors in landings
- Figure 18. Door location near ramps
- Figure 19. Open risers are not permitted
- Figure 20. Step nosing is not advisable and is limited up to 25 mm
- Figure 21. Section of a stair
- Figure 22. Stair with landings
- Figure 23. Spaces under stairs shall be protected
- Figure 24. Dimensions of handrails
- Figure 25. Examples of accessible handrail profile
- Figure 26. Elevator recommended dimensions
- Figure 27. Example of buttons path
- Figure 28. Example of a keypad
- Figure 29. Lift platform dimensions
- Figure 30. Door handle
- **Figure 31.** Minimum manoeuvring space in front of one push side swinging doors
- **Figure 32.** Minimum manoeuvring spaces in front of both-side push swinging doors and sliding doors
- Figure 33. Minimum manoeuvring space for two aligned doors in a series
- Figure 34. Minimum manoeuvring space for two angled doors in a series
- Figure 35. Window at 1200 mm with fixed glass at 900 mm from the floor
- Figure 36. Glass marks
- Figure 37. Cabin latch example