

- f. Abiding by the locations of cars exits or entrances according to the requirements of the concerned administration and according to the planning conditions, if there is something which locates these places on the map of planning.
- g. Entrances and exist for cars should not be put on sidewalk or on the parts that are for parking lots or public benefit unless it is unfeasible to enter from the streets or for any technical reasons on which the concerned administration approved.
- h. It is allowed to exceed the limit superior for the ceiling level of the cellar which is settled by the regulations of this list in the case of dedicating the cellar floors and the ground floor as parking lots providing that the height of the ground floor must not exceed the settled height in this list.
- i. The plans for road works which are enclosed with the construction license application should include the following plans as a limit inferior:
 - i. Setting out plan: which shows streets, roads, sidewalk and the neighborhood which surrounds the plot as well as the levels of tracks, existing streets, the levels of the plot and the neighborhood, areal references, the entrances and the exits of cars, traffic direction in the streets which surround the plot and any traffic signs or crossroads or turning points or obstacle that affects the entrances and the exits of cars as well as street lambs.
 - ii. The plans of parking lots for all floors
 - iii. The conditions, the specifications and the instructions of traffic, the signs and the necessary controlling devices.
 - iv. Any other details which are required by the concerned administration.
 - v. The calculations of parking lots.
 - vi. The studies of traffic effect. (when it is required)
- j. If it is not feasible to use ramps to get to the different floors of parking lots, It is possible to use electric elevators for cars after getting in advance an approval from the concerned administration and using the ground floor and the cellar completely for parking lots.
- k. Natural lighting and ventilation should be provided and if this is not feasible, electric lighting with active mechanical ventilation system should be provided according to the standard specifications approved by the competent administration, should be provided.
- l. The necessary fittings to drain rain water at the end of the ramps of entrances and exits. Ground drainages and suitable slopes should be made in the grounds of parking lots floors.
- m. If there is a contradiction after issuing the construction license between the entrances and the exits of the neighborhood or the traffic or the surrounding streets, the competent administration has the right to ask to modify the entrances and the exits in a way that goes with the existing state and the municipality does not take any responsibility for this modification.
- n. The ground of the parking lots should be covered with a suitable concrete layer which can be easily cleaned.