

Table C3-1 (Continued)

Component					Load (psf)
Density of unit (125 pcf)					
No grout	26	28	36	44	50
48 in. o.c.		33	44	54	62
40 in. o.c. grout		34	45	56	65
32 in. o.c. spacing		36	47	58	68
24 in. o.c.		39	51	63	75
16 in. o.c.		44	59	73	87
Full grout		59	81	102	123
Density of unit (135 pcf)					
No grout	29	30	39	47	54
48 in. o.c.		36	47	57	66
40 in. o.c. grout		37	48	59	69
32 in. o.c. spacing		38	50	62	72
24 in. o.c.		41	54	67	78
16 in. o.c.		46	61	76	90
Full grout		62	83	105	127
Solid concrete masonry unit wythes (incl. concrete brick):					
Wythe thickness (in mm)	4	6	8	10	12
Density of unit (105 pcf)	32	51	69	87	105
Density of unit (125 pcf)	38	60	81	102	124
Density of unit (135 pcf)	41	64	87	110	133
CEILINGS					
Acoustical fiber board					0.05
Gypsum board (per mm thickness)					0.008
Mechanical duct allowance					0.19
Plaster on tile or concrete					0.24
Plaster on wood lath					0.38
Suspended steel channel system					0.10
Suspended metal lath and cement plaster					0.72
Suspended metal lath and gypsum plaster					0.48
Wood furring suspension system					0.12
COVERINGS, ROOF, AND WALL					
Asbestos-cement shingles					0.19
Asphalt shingles					0.10
Cement tile					0.77
Clay tile (for mortar add 0.48 kN/m ²)					
Book tile, 51 mm					0.57
Book tile, 76 mm					0.96
Ludowici					0.48
Roman					0.57
Spanish					0.91
Composition:					
Three-ply ready roofing					0.05
Four-ply felt and gravel					0.26
Five-ply felt and gravel					0.29
Copper or tin					0.05
Corrugated asbestos-cement roofing					0.19
Deck, metal, 20 gage					0.12
Deck, metal, 18 gage					0.14
Decking, 51-mm wood (Douglas fir)					0.24
Decking, 76-mm wood (Douglas fir)					0.38
Fiberboard, 13 mm					0.04

Continued