

1. All materials shall be legibly tagged by the manufacturer so that the material can be identified against the corresponding test certificate.
2. Delivery, storage and handling shall at all times be performed in a manner to avoid product damage.
3. Only nylon slings shall be allowed for lifting products.
4. Products shall be stored off the ground on timber blocks of sufficient size and spacing to provide adequate support.
5. Products shall be stored at site in a temperature, humidity etc. environment as recommended by the manufacturer.
6. Products that are stored outside at site shall be stored under cover to prevent ultra violet deterioration and as recommended by the manufacturer.
7. Protect from damage or soiling by adjacent construction operations and provide suitable separation between individual items to prevent them coming into contact with each other.
8. All coating materials shall be kept in the manufacturer's original containers with labels and seals intact. Each container shall clearly display the name of the coating manufacturer, colour, type of coating, batch number and shelf life.
9. The Contractor shall visually inspect all products upon delivery to site and report any damage to the Engineer.
  - a. Any products damaged during delivery, storage and handling shall be marked by the Contractor and set aside.
  - b. Proposals for repair of any damaged products shall be submitted in writing to the Engineer for approval.
  - c. Any damaged products deemed unsuitable for repair by the Engineer shall be removed from site and replaced.

### **2.1.7 Warranty**

- A. The manufacturer and the Contractor shall jointly guarantee the completed protective coating system to be free from defects in materials and workmanship for a period of 10 years from the date of completion of the Works.
- B. The Contractor shall furnish the Engineer with the manufacturer's guarantee and warranty certificates for all materials and components used.