TABLE 722.5.1(4)—continued
WEIGHT-TO-HEATED-PERIMETER RATIOS (*W/D*) FOR TYPICAL WIDE FLANGE BEAM AND GIRDER SHAPES

| STRUCTURAL SHAPE | CONTOUR PROFILE | BOX PROFILE | TYPICAL WIDE FLANG | CONTOUR PROFILE | BOX PROFILE |
|------------------|-----------------|-------------|--------------------|-----------------|-------------|
| W33 x 241 | 2.13 | 2.86 | W21 x 62 | 0.952 | 1.23 |
| x 221 | 1.97 | 2.64 | x 57 | 0.952 | 1.17 |
| x 201 | 1.79 | 2.42 | x 50 | 0.838 | 1.04 |
| x 152 | 1.53 | 1.94 | x 44 | 0.746 | 0.92 |
| x 141 | 1.43 | 1.80 | | l . | |
| x 130 | 1.32 | 1.67 | W18 x 119 | 1.72 | 2.42 |
| x 118 | 1.21 | 1.53 | x 106 | 1.55 | 2.18 |
| | | 1 | x 97 | 1.42 | 2.01 |
| W30 x 211 | 2.01 | 2.74 | x 86 | 1.27 | 1.80 |
| x 191 | 1.85 | 2.50 | x 76 | 1.13 | 1.60 |
| x 173 | 1.66 | 2.28 | x 71 | 1.22 | 1.59 |
| x 132 | 1.47 | 1.85 | x 65 | 1.13 | 1.47 |
| x 124 | 1.39 | 1.75 | x 60 | 1.04 | 1.36 |
| x 116 | 1.30 | 1.65 | x 55 | 0.963 | 1.26 |
| x 108 | 1.21 | 1.54 | x 50 | 0.88 | 1.15 |
| x 99 | 1.12 | 1.42 | x 46 | 0.878 | 1.09 |
| | | | x 40 | 0.768 | 0.96 |
| W27 x 178 | 1.87 | 2.55 | x 35 | 0.672 | 0.85 |
| x 161 | 1.70 | 2.33 | | | |
| x 146 | 1.55 | 2.12 | W16 x 100 | 1.59 | 2.25 |
| x 114 | 1.39 | 1.76 | x 89 | 1.43 | 2.03 |
| x 102 | 1.24 | 1.59 | x 77 | 1.25 | 1.78 |
| x 94 | 1.15 | 1.47 | x 67 | 1.09 | 1.56 |
| x 84 | 1.03 | 1.33 | x 57 | 1.09 | 1.43 |
| | | | x 50 | 0.962 | 1.26 |
| | | | x 45 | 0.870 | 1.15 |
| W24 x 162 | 1.88 | 2.57 | x 40 | 0.780 | 1.03 |
| x 146 | 1.70 | 2.34 | x 36 | 0.702 | 0.93 |
| x 131 | 1.54 | 2.12 | x 31 | 0.661 | 0.83 |
| x 117 | 1.38 | 1.91 | x 26 | 0.558 | 0.70 |
| x 104 | 1.24 | 1.71 | | | |
| x 94 | 1.28 | 1.63 | W14 x 132 | 1.89 | 3.00 |
| x 84 | 1.15 | 1.47 | x 120 | 1.71 | 2.75 |
| x 76 | 1.05 | 1.34 | x 109 | 1.57 | 2.52 |
| | | | | | |
| W14 x 99 | 1.43 | 2.31 | W10 x 30 | 0.806 | 1.12 |
| x 90 | 1.31 | 2.11 | x 26 | 0.708 | 0.98 |
| x 82 | 1.45 | 2.12 | x 22 | 0.606 | 0.84 |
| x 74 | 1.32 | 1.93 | x 19 | 0.607 | 0.78 |
| x 68 | 1.22 | 1.78 | x 17 | 0.543 | 0.70 |
| x 61 | 1.10 | 1.61 | x 15 | 0.484 | 0.63 |
| x 53 | 1.06 | 1.48 | x 12 | 0.392 | 0.51 |
| x 48 | 0.970 | 1.35 | | | |

(continued)