

3. The Engineer will define the repair areas.
4. The Contractor shall obtain the written approval of the Engineer prior to start any sequence of the works.
5. During all the works, the exposed termination of waterproofing to the underground concrete shall be properly protected from rains and water infiltrations to the satisfaction of the Engineer.
6. The support should be clean, sound, dry, dustless and degreased and as required by the waterproofing manufacturer's specifications.
7. All works related to the waterproofing system such as removing the electrical accessories and raising it, etc. shall be done by the Contractor.
8. Jointing works shall be carried out with approved materials and in accordance with good practice and manufacturer's specifications.
9. The connection between the old and new waterproofing works shall be properly done in accordance with the manufacturer's recommendations.
10. All the termination details Aluminium flashing, sealant, etc. shall be done properly in accordance with the manufacturer's recommendations.
11. The waterproofing works shall be performed by applicators approved by the water proofing system manufacturer and in accordance with the manufacturer's method and details.
12. The Contractor shall include in his prices all the works described under this section, as well as additional works judged necessary by the Engineer for the good achievement of the works, including the supply of materials, the samples, the applications, the preparation works, the treatment of defective and damaged areas, the repair or replacement of items or areas damaged by the Contractor during the performance of the works, etc.

#### **13.4.4 Construction of Pavement**

##### **A. Extent of the Works**

1. These works concern the construction of new pavement around the reservoirs or pumping stations as defined by the Engineer. These works shall allow obtaining paved access to the desired locations.
2. The type of required works shall be defined by the Engineer.

##### **B. Description of the Works:**

1. As a guideline, these works are constituted of: