

Figure 38. Door hanger

Figure 39. Urinary dimensions and bars

Figure 40. Dimensions for sinks

Figure 41. Symmetrical toilets may substitute interaction space on both sides

Figure 42. Required toilet door accessories

Figure 43. Transfer area on both sides of the toilet

Figure 44. Minimal dimensions for toilets with only one interaction area when permitted

Figure 45. Fixed bars positions

Figure 46. Bars dimensions in showers

Figure 47. Example of full family restroom

Figure 48. Example of individual feeding room - plan

Figure 49. Example of individual feeding room - front view

Figure 50. Example of dual lactation room - plan

Figure 51. Example of dual lactation room - front view

Figure 52. Free area and sink and accessories dimensions in ablution rooms

Figure 53. Table dimensions

Figure. 54. Chair dimensions

Figure 55. Bench with lateral interaction area

Figure 56. Drinking fountain dimensions

Figure 57. Example of a trash bin

Figure 58. Lateral interaction space in ATM

Figure 59. Street at the same level where pedestrians have preference and vehicles speed, if allowed is limited to 10Km/h

Figure 60. Standard section of a Sikka

Figure 61. Standard section of a shared street

Figure 62. Section of a sidewalk with recessed façade

Figure 63. Section of a sidewalk with a pergola

Figure 64. Section of a sidewalk with a cycle path

Figure 65. Standard section of a one-way street with cycling paths in one direction

Figure 66. Standard section of a two-way street with cycling paths in both directions