



- NOTES:**
- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS INDICATED OTHERWISE.
  - IF THERE IS DISCREPANCY BETWEEN THE REQUIREMENTS IN THE SPECIFICATIONS AND THOSE SHOWN ON THIS DRAWING, THE SPECIFICATIONS SHALL BE FOLLOWED.
  - ALL MATERIALS, FABRICATION AND CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS AND VERIFIED BY THE ENGINEER.
  - WHERE SWALE SIDE SLOPES EXCEED 1 IN 4, PROVIDE GROUTED STONE RIPRAP WITH AN AVERAGE SLOPE DEPTH OF 300mm OR SIMILAR SCOUR PROTECTION SUBJECT TO THE APPROVAL OF THE ENGINEER.
  - PLACE GEOTEXTILE FILTER FABRIC UNDER ALL SCOUR PROTECTION AS PER SPECIFICATIONS.

REFERENCE DRAWINGS AND DOCUMENTS			
No.	REVISIONS	APP'D	DATE
CLIENT			
TITLE			
STANDARD DRAWINGS MAIN ROADS			
DRAWING TITLE			
SURFACE DRAINAGE DETAIL OF SWALE DRAIN IN A CATCH BASIN			
DRAWN	-	SCALE	N.T.S
CHECKED	-	DATE	-
APPROVED	-	SIZE	A1
PROJECT No.	-	DWG. No.	N-246