

INDEX

- story drift ratio, 61
- story shear, 61
- strength, 61
- strength design, 1–2
 - combining factored loads using, 7–8
 - with overstrength factor, 87
- structural dumping, 521–522
- Structural Engineers Associations, 427
- structural geometry, 494–495
- structural height, 61
- structural integrity, general, 4–5
- structural irregularities, 81–85, 83t, 84t, 85t
- structural modeling, 89
- structural observations, 61, 362
- structural reliability theory, 390
- structural robustness, 393
- structural separation, 97–98
- structural steel, 127, 360
- structural wall, 62, 96–97
- structure, 61
- Stubbs, N., 526
- Stuttgart, University of, 490
- subdiaphragm, 61
- supports, 61, 476
- Surry, D., 526
- suspended ceilings, 116

- Tabler, R., 432
- tanks and vessels
 - anchorage, 151t, 152
 - boilers and pressure vessels, 158–159
 - elevated, for liquids/granular materials, 156
 - ground-supported storage (granular materials), 156
 - ground-supported supported storage (liquids), 152–155, 154t, 497–498
 - horizontal, saddle supported for liquid/vapor storage, 160
 - liquid and gas spheres, 159–160
 - maximum material strength, 159t
 - petrochemical/industrial liquid storage, 155
 - piping attachment flexibility, 150, 151t
 - refrigerated gas liquid storage, 160, 498
 - seismic design basis, 149–150
 - strength/ductility, 150
 - water storage/water treatment, 155
- Tattelman, P., 455
- Taylor, D., 430, 434
- Taylor, D.A., 394, 427, 432
- Taylor, T.J., 571
- telecommunication towers, 149
- Templin, J.T., 571
- temporary facilities, 2

- Terzaghi, K., 397
- testing agency, 61
- thermal factor, 428
- Thorkildson, R.M., 455
- tie strut, 59
- Tobiasson, W., 426, 428, 434
- topographic effects, wind, 251–254
- torsional irregularities, 495
- torsional moments, 291, 523, 545
- torsional wind load cases, buildings exempt from, 367–368, 369f–370f, 593
- total design displacement, 165
- total maximum displacement, 165
- toxic substances, 2, 5–6, 382–384
- Traczuk, G., 564
- transverse reinforcement requirements, 490
- troughed free roofs, 289f, 552
- trussed towers, 314f
- Turkstra, C.J., 387
- Twisdale, L.A., 524

- ultimate deformation, 58
- undrained shear strength average, 204–205
- Uniform Building Code* (UBC), 467
- United States Army Cold Regions Research and Engineering Laboratory (CRREL), 427
- United States Geological Survey (USGS), 503
- U.S. Army Corps of Engineers, 418, 419, 422, 427
- U.S. Department of Agriculture Soil Conservation, 427
- utility lines, 123

- vehicle barrier system, 13, 14, 409
- vehicle garages, 410–411
- velocity-dependent damping device, 179
- velocity pressure, 259–260, 261t, 557
 - components and cladding, 316, 317f
 - wind loads on other structures/building appurtenances, 307–308, 310t
- velocity pressure exposure coefficient, 547
- veneers, 61
- vertical deflections, 365, 579–580
- vertical irregularities, 81, 84t, 493
- vertical pilings and columns, breaking waves and, 23
- vertical seismic load effect, 86
- vertical walls, breaking waves and, 23
- vessels. *See* tanks and vessels
- vibrations, 365, 581
- Vickery, P.J., 508, 510, 511, 513, 515, 526
- viscous damping, 191–192
- V zone, 21, 416, 418