Chapter 29 - Plumbing Systems

SECTION 2901 GENERAL

2901.1 Scope. The *Abu Dhabi Uniform Plumbing Code* shall govern the erection, installation, *alteration*, repairs, relocation, replacement, *addition* to, use or maintenance of plumbing equipment and systems. Plumbing systems and equipment shall be constructed, installed and maintained in accordance with the *Abu Dhabi UniformPlumbing Code*. Private sewage disposal systems shall conform to the *Abu Dhabi International Private Sewage Disposal Code*. [P]

2902. Legionella management. In order to prevent the growth of Legionairres' Disease Bacteria in warm water systems used design, installation and maintenance of these systems shall be in accordance with Abu Dhabi EHS Code of Practice 12.0- Prevention and Control of Legionairres Disease and ASHRAE Guidelines 12-2000 Minimizing the risk of Legionellosis Associated with Building Water Systems.

2903 Water Conserving Fixtures, Fittings and Appliances

MAXIMUM FLOW RATES AND CONSUMPTION FOR PLUMBING FIXTURES AND FIXTURE FITTINGS

PLUMBING FIXTURE OR FIXTURE	MAXIMUM FLOW RATE OR QUANTITY ^b	
FITTING	gpm	L/m
Lavatory, private	1.5 gpm at 60 psi	6 L/minute at
		413.7 kilopascals
Lavatory, public	0.25 gallon per	1 liter per
(metering)	metering cycle	metering cycle
Lavatory, public	0.5 gpm at 60 psi	1.9 liters at 413.7
(other than metering)		kilopascals
Shower head ^a	2.5 gpm at 80 psi	9.5 liters at 551.6
	-	kilopascals
Sink faucet (incl. bidet	2.21.5 gpm at 60	6 L/minute at
and ablution faucets)	psi	413.7 kilopascals
Urinal	1.0 pint per	0.5 liters per
	flushing cycle	flushing cycle
Water closet ^c	1.6 gallons per	6 liters per
	flushing cycle	flushing cycle

For SI: 1 gallon = 3.785 L, 1 gallon per minute = 3.785 L/m,

- a. A hand-held shower spray is a shower head.
- b. Consumption tolerances shall be determined from referenced standards.
- c. Water closets to be dual flush with a maximum 1.6 gallons (6 liters) per flush.

All appliances are to be *approved* for energy and water efficiency.

2904. Water conservation in landscaping . Design of outdoor landscaping to be guided by Urban Planning Council (UPC) Public Realm Design Manual. Where Recycled Water connection is available for irrigation, owner shall make provisions to utilize the system with approval of the relevant authority.

¹ pound per square inch = 6.895 kPa.