

- C. The Contractor shall remove debris and abandoned items from area and from concealed spaces.
- D. The Contractor shall prepare surface and remove surface finishes to provide for proper installation of new work and finishes.
- E. The Contractor shall close openings in exterior surfaces to protect existing work from weather and extremes of temperature and humidity.

10.3.3 Installation

- A. The Contractor shall coordinate work of alterations and renovations to expedite completion.
- B. The Contractor shall remove, cut, and patch Work in a manner to minimise damage and to provide a means of restoring Products and finishes to specified condition.
- C. The Contractor shall refinish visible existing surfaces to remain in renovated locations, to specified condition for each material, with a neat transition to adjacent finishes.
- D. In addition to specified replacement the Contractor shall restore existing systems to full operational condition.
- E. The Contractor shall re-cover and refinish Work that exposes mechanical and electrical work exposed accidentally during the work.
- F. The Contractor shall install Products as specified in individual sections.

10.3.4 Transitions

- A. Where new Work abuts or aligns with existing items, the Contractor shall perform a smooth and even transition. He shall patch Work to match existing adjacent Work.
- B. When finished surfaces are cut so that a smooth transition with new Work is not possible, the Contractor shall terminate existing surface along a straight line at a natural line of division and make recommendations to the Engineer.

10.3.5 Adjustments

- A. Where removal of partitions or walls results in adjacent spaces becoming one, the Contractor shall rework floors, walls, and ceilings to a smooth plane without breaks, steps, or bulkheads.