

- F. Road narrows ahead signs shall be placed midway between the road works ahead signs and the beginning of the taper of traffic cones.
- G. On roads with speed limits of 80km/h or more, all advance signs should have plates giving the distance to the works in meters.
- H. A line of traffic cones shall be placed at a taper and guide traffic past the works in accordance with DMAT "Traffic control devices manual" .
- I. The maximum spacing distance of cones in longitudinal lengths of coning shall be 9m, but no less than 2 cones shall be used in any length between tapers.
- J. Keep right or left signs shall be placed at the beginning and end of the lead in taper of cones.
- K. Road danger lamps shall be added at night, in poor daytime visibility and in bad weather and shall not be higher than 1.2m above the road.

18.1.14 Personal Protective Equipment

- A. The Contractor shall provide all their site staff and workers with a minimum of a safety helmet, safety boots, protective glasses, earplugs, respiratory protection, suitable gloves and high visibility clothing for their personal use. The Contractor shall replace these where any wear or tear renders them ineffective. The Contractor shall ensure that both their own and sub-contractors staff and workforce fully comply with this requirement.
- B. The Contractor shall class all construction sites as "Hard hat areas" and enforce the same to visitors.
- C. All PPE chosen must carry a CE mark or other mark to an international standard.

18.1.15 Manual Handling

- A. The Contractor shall assess his work methods and identify where manual handling is required and provide necessary control measures. The maximum weight for one person to lift shall be 25 kg.

18.1.16 Mechanical Plant and Equipment

- A. The Contractor shall assess his work methods and identify all mechanical plant and equipment required and provide necessary control measures.