

- D. The Contractor shall verify that utility services are available, of the correct characteristics, and in the correct locations.

14.3.2 Quality Assurance

- A. The Contractor shall monitor quality control over suppliers, manufacturers, Products, services, site conditions, and workmanship, to produce Work of specified quality.
- B. The Contractor shall comply with manufacturers' instructions, including each step in sequence.
- C. Should manufacturers' instructions conflict with Contract Documents, the Contractor shall request clarification from Engineer before proceeding.
- D. The Contractor shall comply with specified standards as minimum quality for the Work except where more stringent tolerances, codes, or specified requirements indicate higher standards or more precise workmanship.
- E. The Contractor shall perform Work by persons qualified to produce required and specified quality.
- F. The Contractor shall verify that field measurements are as indicated on shop drawings or as instructed by the manufacturer.
- G. The Contractor shall secure Products in place with positive anchorage devices designed and sized to withstand stresses, vibration, physical distortion, or disfigurement.

14.3.3 Tolerances

- A. The Contractor shall monitor fabrication and installation tolerance control of Products to produce acceptable Work. He shall not permit tolerances to accumulate.
- B. The Contractor shall comply with manufacturers' tolerances. Should manufacturers' tolerances conflict with Contract Documents, he shall request clarification from Engineer before proceeding.
- C. The Contractor shall adjust Products to appropriate dimensions; position before securing Products in place.