

4. The room should have one emergency exit which leads directly to outside the building or to a balcony. Security devices should be provided for the different groups of the people of peculiar needs in the hotel.
  5. One of the elevators should have the specifications which correspond to the standards related to the people of peculiar needs concerning the dimensions, the measurements, the location and the height of the control panel, the opening time and the inner rails.
  6. Parking lots should be provided as the following: one parking lot is for every (75) parking lots out of the total number of parking lots with a limit superior (5) parking lots. It should be as close as possible to elevators or to the main entrance of the hotel with supplying them with the necessary directorial signs whose measurements should be according to the standards related to the people of peculiar needs.
  7. The space for loading and unloading at the main entrance of the hotel should be according to the standards related to the people of peculiar needs.
  8. Ramps with slope rates that are not more than (1) to (12) centimeters at sidewalks, outer stairs and the points of different levels inside and outside the buildings. The necessary warning instructions should be supplied.
  9. Direct lanes without obstacles from parking lots and even elevators or the main entrance of the hotel and the passages should have sufficient width for the movement of the people of peculiar needs according to the approved standards and where it is possible to go in or out from all doors and to get to all the inner and the outer elements without any obstacles that may restrict his movement.
- d. The passages and the ramps that are related to the people of peculiar needs should have the following conditions:
1. The ramps that are related to the sidewalk should be within the same sidewalk.
  2. If there are two successive ramps, there should be a flat space between them with measurements according to the standards approved by the competent administration.
  3. All ramps, passages and stairs should be equipped with the necessary warning signs (roughing, colors) at the points of the beginning and the end and when reaching to the roads of cars.
  4. The rate of the ramp should not be more than (1) to (12).
  5. It is not allowed to put any parking lots in front of ramps.
  6. The ramps should be on the same direction as the direction of the pedestrians' movement on the sidewalk.
  7. The upper surface of the ramp should be flat and has no holes that restrict movement.