

INDEX

- diaphragm, 243, 507
 - defined, 59
 - flexibility, 80–81, 81f
- diaphragm boundary, 59
- diaphragm chord, 59
- diaphragm deflection, 97
- diaphragm strut, 59
- direct design, 379
- directional procedure, 243
- displacement, 165
- displacement-dependent damping device, 179
- displacement restraint system, 165
- domed roofs, 285f, 344f, 432
- Donelan, M.A., 511, 515
- Downey, C., 434
- drag strut, 59
- drainage, 43. *See also* ponding instability
- dual system
 - defined, 59
 - seismic design requirements, 78
- ductwork, 123–124
- Dumitrescu-Brulotte, M., 571
- Dunn, G.E., 526
- durability, 365, 582
- Durst, C.S., 510, 513
- Dusenberry, D.O., 394, 395
- dynamic analysis procedures, 172–175, 495

- earthquake load, 468. *See also* seismic design
- earth-retaining structures, 148
- Eaton, K.J., 571
- eave height, 243
- eave icings, 428, 430–431
- effective damping, 165, 190–192, 200
- effective ductility demand, 192
- effective seismic weight, 88–89
- effective stiffness, 165
- effective wind area, 243, 507–508
- electrical components, 484, 485–488
 - quality assurance, 361
 - seismic design requirements for, 120t–121t, 122
- electrical equipment, testing, 362
- elevators, 125, 410
- Ellingwood, B., 387, 388, 389, 394, 395, 513, 579, 580, 581
- Ellingwood, B.R., 379, 407
- Elliott, M., 427
- enclosure, 59
- enclosure classification, 255, 257
- envelope procedure, 243. *See also* wind loads on buildings—MWFRS (envelope procedure)
- equipment support, 59

- equivalent lateral force, 480
- equivalent lateral force procedure, 89–93
 - horizontal distribution of forces, 91
 - isolated structures, 169
 - overturning, 92
 - p -delta effects, 93
 - period determination, 90
 - seismic base shear, 89
 - soil-structure interaction, 199–201, 201f
 - story drift determination, 92, 93f
 - structures with damping systems, 187–190
 - vertical distribution of seismic forces, 91
- equivalent static method, 494
- equivalent uniformly distributed loads, 410
- erosion effects, 21, 416
- escalators, 125
- escarpment, 243
- essential facilities, 1
- existing building provisions, 363–364
- expansion and contraction, 365, 582
- explosive substances, 5–6, 382–383
- exposure, 246, 251, 256f
- exposure factor, 427–428
- extraordinary events, load combinations for, 9, 393–395
- extreme impact loads, 419

- factored load, 1
- Factory Mutual Engineering Corp., 447
- Federal Aviation Administration, 409
- Federal Emergency Management Agency (FEMA), 387, 415
- federal government construction, 471
- Federal Insurance and Mitigation Administration (FIMA), 415
- field standard penetration resistance average, 204
- Filliben, J.J., 576
- Finney, E., 432
- Fintel, M., 379
- fire protection sprinkler piping systems, 124, 488
- fire pump equipment, 484
- Fisher, J., 579, 580
- fixed ladder, 13, 14, 409
- fixed service equipment weight, 11
- flat roof
 - reduction in live loads, 411
 - snow loads, 29, 31, 427–430, 435, 436
 - wind loads, 322, 345f
- flexible connections, 59
- flood hazard area, 21, 416
- flood hazard map, 21, 416
- flood insurance rate map (FIRM), 21