

2.2.5 Accessories

- A. Adhesive: FS MMM-A-130 contact adhesive. Type recommended by BS 1204 laminate manufacturer to suit application.
- B. Aluminium Edge Trim: Extruded convex or flat shape; smooth surface finish; self locking serrated tongue; of width to match component thickness; clear anodised finish.
- C. Wire Glass: Clear, polished both sides; square mesh of woven stainless steel wire of 12 mm grid size; 6 mm thick.
- D. Fasteners: Size and type to suit application.
- E. Bolts, Nuts, Washers, Lags, Pins, and Screws: Of size and type to suit application.
- F. Concealed Joint Fasteners: Threaded steel.
- G. Grommets: Plastic, Metal or Rubber material for cut-outs.

2.2.6 Ironmongery

- A. The provision of ironmongery and door furniture is covered by the relevant Schedules on the Drawings.
- B. Generally hinges to all timber and aluminium frame doors are to be stainless steel washered butt hinges.
- C. Mortice and dead locks are to be 5 lever Mortice locks with silver chrome plated exposed parts and striking plates.
- D. All locks shall comply with the requirements of Abu Dhabi Public Gardens Directorate and shall be sub-mastered as shown on the Drawings.
- E. The Contractor shall provide the following:
 - 1. 2 No. keys for each individual lock.
 - 2. Sub master keys for any new sub master group generated as shown on the Drawings (number of keys to be determined by the Engineer).
 - 3. A schedule giving the individual lock numbers door numbers and sub master groupings.
- F. Lever handles, knob sets, pull handles, escutcheons roses and plates are to be finished in anodized aluminium natural silver finish.