

- c. The number of floors and withdrawals should be according to the map which is supplement with the system of classifying and economizing land usages in the emirate.
- d. The inner withdrawal between buildings should not be less than (20) feet and the limit inferior for the area of the inner yard is (20×20) feet.
- e. The limit inferior for the building ratio should be sufficient for the residence of (50%) of the number of the workers according to the documents of land assigning as the first phase of building.
- f. It is not stated to open the doors of the rooms directly to the street or the track and the main entrance should be from inside the plot as the first phase of building.
- g. It is stated for the passages of the first floor to emerge with a rate (4.5) feet inside the withdrawal between the buildings and the outer withdrawals. These passages are not stated to be closed at the projection.
- h. When using metal ceiling or another kind other than reinforced concrete, it should be covered with suspended ceiling from the inside and with thermal insulating materials according to the approved specification by the competent administration.
- i. It is allowed to build rooms with independent services (not gathered) for the supervisors where one room is for every (40) workers.
- j. There should be one kitchen or more for preparing food as well as dinning rooms that go with the number of workers providing that the room should contain ($\frac{1}{4}$) of the total number of workers at one time as a limit inferior. The design and the furniture of the kitchen and the dinning room should be according to the sanitary conditions that are in accordance with the regulations of public health and the vocational safety that are prevalent in the emirate.
- k. There should be a room for trash or an uncovered assemblage for the trash bins inside the boarders of the plot and this is according to the conditions of trash rooms that are mentioned in this list. This assemblage can be put in the frontal withdrawal from the street side.

Article (32): Mosques:

When designing mosques, service elements should be provided according to the kind of the mosque, its location and the number of the prayers:

Kind	Lavatories Limit inferior	Sinks Limit inferior	Ablution place Limit inferior	Residence services	Parking lot Limit inferior	Stopping stands
Residential areas (villas): a) Prayer times mosque: Capacity for 150 prayers	3	3	5	1 apartment for the imam+ 1 room for the worker	8	2