2017 EDITION

	 Maintenance access/replacement convenience for switchgear components 	Breaker[] CTs[]4 KWH Meter[] Gland plate[]
	10.Provision for termination of Cu./ XLPE/AWA(S.C.)	Non-Ferrous glands plate []
V.	IDENTIFICATION	
	 Rating of Incoming supply & Outgoing circuit breakers:- (vis-a-vis the rating specified - Refer approved Single Line Diagram No.:) 	Thermal [] Discrimination [] Fault []
	Type of circuit breakers :- Incoming Outgoing	ACB[] MCCB[] F/S[] MCCB[] F/S[] C/L MCCB[]
	2. Colour codes for internal, main circuits wiring:- Phase Neutral Earth	Red / Yellow / Blue [] Black [] Green and Yellow []
	3. Terminal ferrules for control/auxiliary circuits	KWH Meter [] Indicating Instruments [] Other[]
	4. Permanent labels, engraved, 'trafolite' or similar	Board Designation [] Controls [] Circuit Designation [] Indications [] Warning Notice/s []
VI	EARTHING	Compliance with Regulation Section - 5 []
	1. Rating/size of Earth bus-bar & terminals	Adequate, consistent with the min. fault rating specified under IV.4 and IV.5 [] Adequate No. & size to terminate Main & Circuits ECCs []
	2. Earthing of conductive parts	Enclosure[] Hinged Door[] Cable Glands[]

111