APPENDIX 8 SPECIFICATIONS OF DBs

(Refer section 4 of Regulations)

DB No.:

I.	REFERENCE STANDARDS	BS EN 61439, BS EN 60947, IEC 61439
II.	RATING OF INCOMING SUPPLY BREAKER/ISOLATOR+ (+On-load)	40A[] 60A[] 100A[] 125A[][] BREAKER[] ISOLATOR[]
III.	CONSTRUCTION	
	1. Mounting	Wall[] Pedestal[] Surface[] Recessed[]
	Degree of protection of the enclosure for installation	Indoor-IP41/42[] Outdoor-IP54/55[]
	3. Painting/Finish (Internal/External)	Stove enamelled [] Epoxy [] Polyester [] Galvanized[][]
	4. Front Cover (+Neoprene)	Hinged[] Bolted[] Panel lock[] Gasketted+[]
	5. Cable Tray/Conduit entry	Top[] Bottom[] Top&Bottom[]
	6. Assembly	Factory Assembled [][]
IV.	INTERNAL LAYOUT/ARRANGEMENT & FAULT RATING	
	1. Segregation of live parts :-	Barrier [] Shroud[] Firmly secured [] *Separately mounted &
	Incoming supply terminals/lugs	Removable by tool []
	Bus bar, tap-off connections & terminals (*Separate and independent of each other)	Barrier [] Firmly secured [] *Separately mounted & Removable by tool []

2017 EDITION