APPENDIX 7 SPECIFICATIONS OF MDBs/SMDBs

(Refer section 4 of Regulations)

MDB/SMDB No.:

I.	REFERENCE STANDARDS	BS EN 61439/ IEC 61439
II.	RATING OF INCOMING SUPPLY BREAKER/ISOLATOR+ (+On-load)	200A[] 300[] 400A[] 800A[] 1600A[] 2500A[] BREAKER[] ISOLATOR[]
III. CONSTRUCTION		
	1. Mounting	Wall[] Floor[] Pedestal[]
	Degree of protection of the enclosur for installation	Indoor-IP41/42[] Outdoor-IP54/55[]
	3. Painting/Finish (Internal/External)	Stove enamelled [] Epoxy [] Polyester [] Galvanized []
	4. Front Cover (+Neoprene)	Hinged[] Bolted[] Panel lock[] Gasketted+[]
	5. KWH Meter reading provision	Glass Window [] Gasketted []
	6. Cable Tray	Top[] Bottom[] Top&Bottom[]
	7. Ventilation	Louvers []
	8. Sealing/pad locking provision	Compliance with Regulation 3.3.10 []
IV	INTERNAL LAYOUT/ARRANGEMENT & FAULT RATING	
	1. Segregation of live parts :- Incoming supply terminals/lugs	Barrier [] Shroud [] Firmly secured [] *Separately mounted & Removable by tool []
	Bus bar, tap-off connections & terminals (*Separate and independent of each other)	Firmly secured [] *Separately mounted & Removable by tool []