

NUC976 Reference Circuit

Size	Document Number	Rev
Custom	System Block	1.0
Date:	Wednesday, April 06, 2016	Sheet 1 of 10

PIN	FUNCTION
PA0	LCD_DATA0/PwrOnSet_0
PA1	LCD_DATA1/PwrOnSet_1
PA2	LCD_DATA2/PwrOnSet_2
PA3	LCD_DATA3/PwrOnSet_3
PA4	LCD_DATA4/PwrOnSet_4
PA5	LCD_DATA5/PwrOnSet_5
PA6	LCD_DATA6
PA7	LCD_DATA7
PA8	LCD_DATA8
PA9	LCD_DATA9
PA10	LCD_DATA10
PA11	LCD_DATA11
PA12	LCD_DATA12
PA13	LCD_DATA13
PA14	LCD_DATA14
PA15	LCD_DATA15

PIN	FUNCTION
ADC4	TP_YM
ADC5	TP_YP
ADC6	TP_XM
ADC7	TP_XP

PIN	FUNCTION
PB2	TBD
PB3	TBD
PB6	SPIO_SS0
PB7	SPIO_CLK
PB8	SPIO_DO (DATA0)
PB9	SPIO_DI (DATA1)
PB10	SPIO_DATA2
PB11	SPIO_DATA3
PB12	UART10_TXD
PB13	UART10_RXD
PB14	UART10_RTS
PB15	UART10_CTS









PIN	FUNCTION
PD0	SD0_CMD
PD1	SD0_CLK
PD2	SD0_DATA0
PD3	SD0_DATA1
PD4	SD0_DATA2
PD5	SD0_DATA3
PD6	SD0_NCD
PD7	LCD_LCS
PIN	FUNCTION
PE0	UART0_TXD
PE1	UART0_RXD

PIN	FUNCTION
PF0	RMII0_MDC
PF1	RMII0_MDIO
PF2	RMII0_TXD0
PF3	RMII0_TXD1
PF4	RMII0_TXEN
PF5	RMII0_REFCLK
PF6	RMII0_RXD0
PF7	RMII0_RXD1
PF8	RMII0_CRSDV
PF9	RMII0_RXERR
PF10	USB_PWREN

PIN	FUNCTION
PG0	I2C0_SCL
PG1	I2C0_SDA
PG6	LCD_CLK
PG7	LCD_HSYNC
PG8	LCD_VSYNC
PG9	LCD_DEN
PG10	LCD_BLEN
PG11	UART6_TXD
PG12	UART6_RXD
PG13	UART6_RTS
PG14	UART6_CTS


PIN	FUNCTION
PH0	USB0_VBUSVLD
PH1	USB_OVC

PIN	FUNCTION
PI3	VCAP_CLKO
PI4	VCAP_PCLK
PI5	VCAP_HSYNC
PI6	VCAP_VSYNC
PI7	VCAP_PWDN
PI8	VCAP_DATA0
PI9	VCAP_DATA1
PI10	VCAP_DATA2
PI11	VCAP_DATA3
PI12	VCAP_DATA4
PI13	VCAP_DATA5
PI14	VCAP_DATA6
PI15	VCAP_DATA7
PIN	FUNCTION
PJ0	JTAG_TCK
PJ1	JTAG_TMS
PJ2	JTAG_TDI
PJ3	JTAG_TDO
PJ4	JTAG_NTRST




NUC976 Reference Circuit

Size	Document Number	Rev
A	Power	1.0
Date:	Wednesday, April 06, 2016	Sheet 3 of 10



Power On Setting





S2	S1	Bootting from
ON	ON	USB.
ON	OFF	eMMC Flash.
OFF	ON	NAND Flash.
OFF	OFF	SPI Flash.

S3	System Clock from
ON	12MHz crystal.
OFF	UPLL output.


S4	Watch Dog Setting
ON	OFF after power on.
OFF	ON after power on.

S5	Setting PJ[4:0]
ON	As GPIO pin.
OFF	As JTAG interface.

S6	UART Debug Message
ON	Output turn ON.
OFF	Output turn OFF.




ICE I/F



NUC976 Reference Circuit

Size	Document Number	Rev
A	Configure, ICE, Reset	1.0
Date:	Wednesday, April 06, 2016	Sheet 5 of 10


PB6	SPICS
PB7	SPICLK
PB8	SPIDo/D0
PB9	SPIDi/D1
PB10	SPIWp/D2
PB11	SPIHiD/D3



PB[11:6]  PB[11:6]

PD[6:0]  PD[6:0]













PD0	SDCmd
PD1	SDCLK
PD2	SDD0
PD3	SDD1
PD4	SDD2
PD5	SDD3
PD6	SDCd






NUC976 Reference Circuit


Size	Document Number	Rev
A	Memory	1.0
Date:	Wednesday, April 06, 2016	Sheet 6 of 10


5" 800X480 LCD RGB565 (E50A2V1)





PI5	HSYNC
PI6	VSYNC
PI7	PWDN
PI8	D0
PI9	D1
PI10	D2
PI11	D3
PI12	D4
PI13	D5
PI14	D6
PI15	D7











PE[1:0]  PE[1:0]

PG[14:11]  PG[14:11]



PB[15:12]  PB[15:12]



NUC976 Reference Circuit

Size	Document Number	Rev
A	UART	1.0
Date:	Wednesday, April 06, 2016	Sheet 9 of 10

USB0_DM USB0_DM
 USB0_DP USB0_DP
 USB0_ID USB0_ID
 USB1_DM USB1_DM
 USB1_DP USB1_DP
 PF10 PF10
 PH[1:0] PH[1:0]
 VBUS VBUS



NUC976 Reference Circuit

Size	Document Number	Rev
A	USB	1.0
Date:	Wednesday, April 06, 2016	Sheet 10 of 10