

**DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Product code : 000000000001907506

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

PO box : 65091

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 4

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H361f Suspected of damaging fertility.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

II Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	: Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Amorphous fumed silica	112945-52-5	$\geq 7 - \leq 8$
Octamethylcyclotetrasiloxane	556-67-2	$\geq 0.27 - \leq 0.3$

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	: In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.

**DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

- Most important symptoms and effects, both acute and delayed : Suspected of damaging fertility.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.

**DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up :

- Non-sparking tools should be used.
- Soak up with inert absorbent material.
- Suppress (knock down) gases/vapors/mists with a water spray jet.
- For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
- Clean up remaining materials from spill with suitable absorbent.
- Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
- Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling :

- Avoid inhalation of vapor or mist.
- Do not swallow.
- Avoid contact with eyes.
- Avoid prolonged or repeated contact with skin.
- Handle in accordance with good industrial hygiene and safety practice.
- Keep container tightly closed.
- Keep away from heat and sources of ignition.
- Take precautionary measures against static discharges.
- Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage :

- Keep in properly labeled containers.
- Keep tightly closed.
- Keep in a cool, well-ventilated place.
- Store in accordance with the particular national regulations.
- Keep away from heat and sources of ignition.

Materials to avoid :

- Do not store with the following product types:
- Strong oxidizing agents
- Explosives
- Gases

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version 5.0 Revision Date: 03/14/2017 SDS Number: 995119-00006 Date of last issue: 10/28/2016
Date of first issue: 02/17/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Amorphous fumed silica	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Amorphous fumed silica

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand

**DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR**

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

protection. Wash hands before breaks and at the end of workday.

- | | | |
|--------------------------|---|---|
| Eye protection | : | Wear the following personal protective equipment:
Safety glasses |
| Skin and body protection | : | Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Hygiene measures | : | Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|---|---|-----------------------------|
| Appearance | : | viscous liquid |
| Color | : | colorless |
| Odor | : | Acetic acid |
| Odor Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | No data available |
| Initial boiling point and boiling range | : | > 100 °C |
| Flash point | : | 87 °C
Method: closed cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | Not applicable |
| Flammability (liquids) | : | Not applicable |

**DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR**

Version 5.0	Revision Date: 03/14/2017	SDS Number: 995119-00006	Date of last issue: 10/28/2016 Date of first issue: 02/17/2015
----------------	------------------------------	-----------------------------	---

Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.03
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	45,000 mPa.s
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapors may form explosive mixture with air. Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:**Amorphous fumed silica:**

Acute oral toxicity	: LD50 (Rat): > 20,000 mg/kg Assessment: The substance or mixture has no acute oral toxicity Remarks: Information taken from reference works and the literature.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials Information taken from reference works and the literature.

Octamethylcyclotetrasiloxane:

Acute oral toxicity	: LD50 (Rat): > 4,800 mg/kg Assessment: The substance or mixture has no acute oral toxicity Remarks: On basis of test data.
Acute inhalation toxicity	: LC50 (Rat): 2975 ppm Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity Remarks: On basis of test data.
Acute dermal toxicity	: LD50 (Rabbit): > 2.5 ml/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: On basis of test data.

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Amorphous fumed silica:**

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials
Information taken from reference works and the literature.

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No skin irritation
Remarks: On basis of test data.

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:**Amorphous fumed silica:**

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials
Information taken from reference works and the literature.

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No eye irritation
Remarks: On basis of test data.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**Octamethylcyclotetrasiloxane:**

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test
Species: Guinea pig
Result: negative
Remarks: On basis of test data.

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Octamethylcyclotetrasiloxane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: On basis of test data.
	: Test Type: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative Remarks: On basis of test data.
	: Test Type: Chromosome aberration test in vitro Result: negative Remarks: On basis of test data.
	: Test Type: In vitro sister chromatid exchange assay in mam- malian cells Result: negative Remarks: On basis of test data.
	: Test Type: DNA damage and repair, unscheduled DNA syn- thesis in mammalian cells (in vitro) Result: negative Remarks: On basis of test data.
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (vapor) Result: negative Remarks: On basis of test data.
	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Rat Application Route: Ingestion Result: negative Remarks: On basis of test data.
Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version 5.0	Revision Date: 03/14/2017	SDS Number: 995119-00006	Date of last issue: 10/28/2016 Date of first issue: 02/17/2015
----------------	------------------------------	-----------------------------	---

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Ingredients:**Octamethylcyclotetrasiloxane:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat, male and female Application Route: inhalation (vapor) Symptoms: Effects on fertility. Remarks: On basis of test data.
Effects on fetal development	:	Test Type: Prenatal development toxicity study (teratogenicity) Species: Rabbit Application Route: inhalation (vapor) Symptoms: No effects on fetal development. Remarks: On basis of test data.
Reproductive toxicity - Assessment	:	Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Octamethylcyclotetrasiloxane:**

Routes of exposure: Ingestion Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.
Routes of exposure: inhalation (vapor) Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.
Routes of exposure: Skin contact Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity**Ingredients:****Octamethylcyclotetrasiloxane:**

Species: Rat Application Route: Ingestion
--

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor)

Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact

Remarks: On basis of test data.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information**Ingredients:****Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Octamethylcyclotetrasiloxane:**

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l
Exposure time: 336 h
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l
Exposure time: 72 h
Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

icity) Remarks: On basis of test data.
No toxicity at the limit of solubility.

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Remarks: On basis of test data.
No toxicity at the limit of solubility.

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability**Ingredients:****Octamethylcyclotetrasiloxane:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.7 %
Exposure time: 28 d
Method: OECD Test Guideline 310

Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7
Method: OECD Test Guideline 111

Bioaccumulative potential**Ingredients:****Octamethylcyclotetrasiloxane:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 12,400

Partition coefficient: n-octanol/water : log Pow: 6.48 (25.1 °C)

Mobility in soil

No data available

Other adverse effects**Ingredients:****Octamethylcyclotetrasiloxane:**

Results of PBT and vPvB assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACH Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015



expected to deposit from the air to water, to land, or to living organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations**UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : NA 1993

Proper shipping name : Combustible liquid, n.o.s.
(Octamethylcyclotetrasiloxane)

Class : CBL

Packing group : III

Labels : None

ERG Code : 128

Marine pollutant : no

Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetic acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Chronic Health Hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated	70131-67-8
Amorphous fumed silica	112945-52-5
Acetic acid	64-19-7
Acetic anhydride	108-24-7

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California Permissible Exposure Limits for Chemical Contaminants

Amorphous fumed silica	112945-52-5
------------------------	-------------

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR


Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

AICS	:	All ingredients listed or exempt.
IECSC	:	All ingredients listed or exempt.
ENCS/ISHL	:	All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	:	All ingredients listed, exempt or notified.
PICCS	:	All ingredients listed or exempt.
DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	:	All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	*	0
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-3 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

DOW CORNING(R) 734 FLOWABLE SEALANT
CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/28/2016
5.0	03/14/2017	995119-00006	Date of first issue: 02/17/2015

German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8