Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 1 of 15

1. Product and Company Identification

Product Name : MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Product Code : 852851-3CBFL-QT

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company

33 Haynes Circle Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

DANGER

Highly Flammable Liquid & Vapor, Category 2

Acute Toxicity, Category 4

Skin Irritation, Category 2

Eye Irritation, Category 2B

Chronic, Respiratory Sensitizer, Category 1, Skin Sensitizer, Category 1b







Potential Health Effects

Eye:

Causes eye irritation.

Skin:

Causes skin irritation.

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 2 of 15

Ingestion:

If swallowed, call a poison control center or physician if you feel unwell. Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probably, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at leveles greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
HEXAMETHYLENE DIISOCYANATE HOMOPOLYMER (SUPPLIER) 0.5 mg/m3 - TWA	28182-81-2	50.583
(SUPPLIER) 1.00 mg/m3 - STEL TERTIARY BUTYL ACETATE ACGIH: 200 PPM TWA	540-88-5	27
OSHA: 200 PPM TWA		
METHYL ETHYL KETONE ACGIH: 200 PPM TWA	78-93-3	10
OSHA: 200 PPM TWA METHYL NORMAL AMYL KETONE	110-43-0	9
OSHA PEL 100 PPM - TWA	110 10 0	J
OSHA VPEL 100 PPM -TWA ACGIH TLV 50 PPM - TWA		
ACGIH TLV 233 MG/M3 - TWA ACETONE	67-64-1	3
ACGIH TLV: 500 PPM TWA	· · · · · · ·	-

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 3 of 15

ACGIH TLV: 750 PPM STEL OSHA PEL: 1000 PPM TWA OSHA VPEL: 750 PPM TWA OSHA VPEL: 1000 PPM STEL

HEXAMETHYLENE-1,6-DIISOCYANATE 822-06-0 .36

ACGIH TLV: 0.005 PPM - TWA

(SUPPLIER): 0.02 PPM - CEILING

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:

If swallowed: Immediately call a poison center/physician.

Do NOT induce vomiting.

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:

INFORMATION NOT AVAILABLE.

5. Fire Fighting Measures

Flammable Properties:

Flash Point: -4 F Method: TCC

Explosive Limits:

Lower explosive limit: 1.1 Upper explosive limit: 12.8

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 4 of 15

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of

internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash

back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to

safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

ı

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material,

(e.g. sand earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local/state/federal regulations.

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 5 of 15

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour)

should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory

protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical

generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an

acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program

should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic

Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 133 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 6 of 15

Specific Gravity: .975

Coating VOC: 2.35 lb/gl

Material VOC: 1.54 lb/gl

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

```
Eye Irritation/Damage:
```

Component 28182-81-2:

Mild eye irritation, Category 2b

Component 67-64-1:

Mild eye irritation, Category 2b

Component 110-43-0:

Mild eye irritation, Category 2b

Component 540-88-5:

Based on available data, the classification criteria are not met.

Component 822-06-0:

Mild eye irritation, Category 2b

Skin Irritation/Damage:

Component 28182-81-2:

LD50: >2000 mg/kg, rat. Category 5

Mild skin irritation, possible skin sensitizer.

Randolph Products Company

```
MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT
Date Printed: 5/15/2015
Page 7 of 15
Component 67-64-1:
LD50: 7426 mg/kg, rat. Category 5
Mildy irritating to skin.
Component 110-43-0:
LD50: >2000 mg/kg, rat. Category 5
Component 540-88-5:
LD50: >2000 mg/kg, rabbit. Category 5.
Component 822-06-0:
LD50: >2000 mg/kg, rat. Category 5
Mild skin irritation, possible skin sensitizer.
Acute Oral Toxicity:
Component 28182-81-2:
LD50: >5000 mg/kg, rat. Category 5
Component 67-64-1:
LD50: 5800 mg/kg, rat. Category 5
Component 110-43-0:
LD50: 1670 mg/kg, rat. Category 4
Component 540-88-5:
LD50: 4,500 mg/kg, rat. Category 5
Component 822-06-0:
LD50: >5000 mg/kg, rat. Category 5
Acute Inhalation Toxicity:
Component 28182-81-2:
LC50: 1.18, rat. Category 4
Component 67-64-1:
LC50: 16000 mg/l, rat. Category 4
Component 110-43-0:
LD50: >16.7 mg/kg, rat. Category 4
Component 540-88-5:
LC50: 12.52 mg/l, rat. Category 2
Component 822-06-0:
LC50: 1.18, rat. Category 4
Respiratory/Skin Sensitization:
```

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 8 of 15

Component 28182-81-2:

Caused skin sensitization in animal studies. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN

SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY

BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

Component 67-64-1:

No evidence of respiratory or skin sensitization.

Component 110-43-0:

No evidence of respiratory or skin sensitization.

Component 540-88-5:

No evidence of respiratory or skin sensitization.

Component 822-06-0:

Caused skin sensitization in animal studies. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN

SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY

BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

Carcinogenicity:

Component 28182-81-2:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 67-64-1:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 110-43-0:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 540-88-5:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 822-06-0:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity:

Component 28182-81-2:

No evidence of human reproductive toxicity.

Randolph Products Company

```
MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT
Date Printed: 5/15/2015
Page 9 of 15
Component 67-64-1:
No evidence of human reproductive toxicity.
Component 110-43-0:
No evidence of human reproductive toxicity.
Component 540-88-5:
No evidence of human reproductive toxicity.
Component 822-06-0:
No evidence of human reproductive toxicity.
Germ Cell Mutagenicity:
Component 28182-81-2:
No data
Component 67-64-1:
No data
Component 110-43-0:
No data
Component 540-88-5:
No data
Component 822-06-0:
No data
Aspiration Toxicity:
Component 28182-81-2:
Not classified as an Aspiration Hazard.
Component 67-64-1:
Not classified as an Aspiration Hazard.
Component 110-43-0:
Not classified as an Aspiration Hazard.
Component 540-88-5:
Not classified as an Aspiration Hazard.
```

Randolph Products Company

12. Ecological Information

```
MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT
Date Printed: 5/15/2015
Page 10 of 15
Component 822-06-0:
Not classified as an Aspiration Hazard.
STOT-single exposure
Component 28182-81-2:
No data
Component 67-64-1:
No Data
Component 110-43-0:
No data
Component 540-88-5:
Transient target organ effects (Category 3);
Respiratory tract irritation.
Component 822-06-0:
No data
STOT-repeated exposure
Component 28182-81-2:
Repeated exposure affected lungs, nasal cavities
Component 67-64-1:
No data
Component 110-43-0:
No data
Component 540-88-5:
No data
Component 822-06-0:
Repeated exposure affected lungs, nasal cavities
Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.
```

Randolph Products Company

```
MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT
Date Printed: 5/15/2015
Page 11 of 15
Environmental Toxicity:
Component 28182-81-2:
LC50: >100 mg/l (fish); EC50: >100 mg/l (daphnia); EC50: 100 mg/l (algae); EC50:
<10 mg/l (bacteria)
Component 67-64-1:
LC50: 6100 mg/l (fish); EC50: 7630 mg/l (daphnia)
Component 110-43-0:
LC50: 131 mg/l (fish); EC50: >90.1 mg/l (daphnia); EC50: 98.2 mg/l (algae);
EC50: <10 mg/l (bacteria)
Component 540-88-5:
Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria)
Component 822-06-0:
LC50: >100 mg/l (fish); EC50: >100 mg/l (daphnia); EC50: 100 mg/l (algae); EC50:
<10 mg/l (bacteria)
Persistance & degradability:
Component 28182-81-2:
Not readily biodegradable
Component 67-64-1:
Readily biodegradable
Component 110-43-0:
Readily biodegradable
Component 540-88-5:
Inherently biodegradable
Component 822-06-0:
Not readily biodegradable
Bioaccumulative potential:
Component 28182-81-2:
No Data
Component 67-64-1:
Does not bioaccumulate
Component 110-43-0:
No Data
Component 540-88-5:
Not expected to bioaccumulate
```

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 12 of 15

Component 822-06-0:
No Data

Mobility in soil:
Component 28182-81-2:
No data
Component 67-64-1:
no data

Component 110-43-0:
No data
Component 540-88-5:
No data

Component 822-06-0: No data

Other Adverse Ecological Effects: Component 540-88-5: Harmful to aquatic life.

13. Disposal Considerations

Waste Disposal Method:

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 13 of 15

Discharge, treatment or disposal is subject to national, state, or local laws.

When a decision is made to discard this

material as supplied, it meets RCRA's characteristic definition of ignitability.

The toxicity characteristic (TC) has

not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Federal Regulations may apply to empty container. State and/or local

regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the

following order of preference, based upon environmental acceptability: (1)

recycle or rework, if feasible; (2)

incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)

Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint Related Material

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR

172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 14 of 15

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where

applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 05/14/15

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the

user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to

determine if, or where, precautions - in addition to those described herein are required. Any health hazard and

safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no

liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be

used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state

and local laws and regulations.

Randolph Products Company

MIL-PRF-85285E TYPE 1 AND 2 CLASS H COMPONENT B FLT/SG-QT

Date Printed: 5/15/2015

Page 15 of 15

End of Material Safety Data Sheet