

Eubanks

AIR LINE LUBRICANT

CAT. NO. 00763

MATERIAL SAFETY DATA SHEET

SECTION I DESCRIPTION:

PRODUCT NAME: Lubricant

HAZARD CLASS:

SECTION II HAZARDOUS INGREDIENTS:

Other than the ingredients listed to the right, this product contains no other ingredients now known to be hazardous as defined in OSHA 29 CFR 1910.1000 (Sub-Part Z), OSHA 29 CFR 1910.1200, the National Fire Protection Association list of hazardous substances, and the California General Industry Safety Order 5194.

INGREDIENTS

Severely Solvent
treated oil

GAS NO.

64742-65-0

PERCENT

RANGE
70-100

HAZARD

DATA
TLV = 5MG/M3

SECTION III PHYSICAL DATA:

Boiling Point (Degrees F): + 500F

Specific Gravity (H₂O = 1): 0.86

Vapor Density (Air = 1): UNKNOWN

% Volatiles (by Volume): NEGLIGIBLE

pH: N/A

Melting Point: UNKNOWN

Vapor Pressure (MMHG): NEGLIGIBLE AT ROOM TEMP

Solubility in H₂O (% by Wt): INSOLUBLE

Evaporation Rate (Butyl Acetate = 1): NEGLIGIBLE

Appearance & Odor: LIGHT AMBER-SLIGHTLY OILY

SECTION IV FIRE AND EXPLOSION DATA:

Flash Point (COC): 390F

Fire Point (COC): -

Flammable Limits in Air (% by Volume): LOWER-UNKNOWN, UPPER-UNKNOWN

Extinguishing Media: CO₂, FOAM, DRY CHEMICAL

Special Fire Fighting Procedures: TREAT AS MINERAL OIL FIRE

Unusual Fire and Explosion Hazard: NONE

SECTION V HEALTH AND HAZARD INFORMATION:

Routes of Exposure and Effects of Overexposure:

Inhalation: TLV FOR PRODUCT NOT ESTABLISHED. REFER TO HAZARDOUS MATERIAL LIST FOR TLV'S

Skin Contact: CONTINUED CONTACT MAY CAUSE IRRITATION.

Skin Absorption: SKIN ABSORPTION IS NOT EXPECTED TO OCCUR.

Eye Contact: WILL CAUSE EYE IRRITATION.

Ingestion: ORAL LD50 FOR THIS PRODUCT HAS NOT BEEN ESTABLISHED-DO NOT INGEST.

Emergency and First Aid Procedures:

Eyes: FLUSH EYES WITH WATER FOR 15 MINUTES, CONSULT A PHYSICIAN

Skin: WASH EXPOSED AREA WITH SOAP AND WATER

Inhalation: IF IRRITATION OCCURS, REMOVE TO FRESH AIR AREA AND AVOID FURTHER INHALATION.

Ingestion: CONSULT A PHYSICIAN

SECTION VI REACTIVITY DATA:

Conditions Contributing to Instability: NONE, PRODUCT IS STABLE UNDER NORMAL CONDITIONS

Incompatibility: STRONG OXIDES

Hazardous Decomposition Products: OXIDES OF CARBON

Conditions Contributing to Hazardous Polymerization: THIS PRODUCT WILL NOT POLYMERIZE

SECTION VII SPILL OR LEAK PROCEDURES:

Steps to be taken for Product Spills and/or Disposal:

RECOVER FREE LIQUID. KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS BY DIKING OR IMPUNDING. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS. INCINERATE ABSORBED MATERIAL. DISPOSE OF FREE LIQUID THROUGH AN OIL RECLAIM SERVICE.

SECTION VIII SPECIAL PROTECTION INFORMATION:

Ventilation Requirements: IF MISTING OCCURS, PROVIDE LOCAL VENTILATION

Specific Personal Respiratory Equipment: IF EXCESSIVE MISTING OCCURS, OR IF ASSOCIATED TLV IS EXCEEDED, PROVIDE NOISH APPROVED RESPIRATORY EQUIPMENT WITH TC-21C-XXX CARTRIDGE COMBINATION.

Eyes: FACE SHIELD OR GOGGLES

Hands: IMPERVIOUS GLOVES, IF DESIRED

Other Clothing or Equipment: NONE REQUIRED

SECTION IX SPECIAL PRECAUTIONS:

AVOID CONTACT WITH EYES AND BREATHING MIST

WASH CONTAMINATED CLOTHING BEFORE USE

DO NOT TAKE INTERNALLY

KEEP DRUMS CLOSED WHEN NOT IN USE

BRING PRODUCT TO ROOM TEMPERATURE BEFORE USE

PREPARED BY: A. LUM

REPRINTED: 8/89

DATE: 10/85

Eubanks

EUBANKS ENGINEERING CO.
950 ROYAL OAKS DRIVE
MONROVIA, CALIFORNIA 91016