


Binary Heap

Last Updated: 04 Nov, 2024

DSA Interview Problems on Heap Practice Heap MCQs on Heap Heap Tutorial Binary Heap Building Heap *eπiciently to get the max or min element pased on its structure.*

A Binary Heap is either Min Heap or Max Heap. In a Min Binary Heap, the key at the root must be minimum among all keys present in Binary Heap. The same property must be recursively true for all nodes in Binary Tree. Max Binary Heap is similar to MinHeap.

Valid and Invalid examples of heaps



How is Binary Heap represented?

A Binary Heap is a **Complete Binary Tree**. A binary heap is typically represented as an array.


• The root element will be at Arr[0].

• The below table shows indices of other nodes for the ith node, i.e., Arr[i]:

Arr[(i-1)/2]	Returns the parent node
Arr[(2*i)+1]	Returns the left child node
Arr[(2*i)+2]	Returns the right child node

The traversal method use to achieve Array representation is <u>Level Order</u>

<u>Traversal</u>. Please refer to <u>Array Representation Of Binary Heap</u> for details.



Operations on Heap:

Below are some standard operations on min heap:

- **getMin()**: It returns the root element of Min Heap. The time Complexity of this operation is **O(1)**. In case of a maxheap it would be **getMax()**.
- extractMin(): Removes the minimum element from MinHeap. The time Complexity of this Operation is O(log N) as this operation needs to maintain the heap property (by calling heapify()) after removing the root.
- decreaseKey(): Decreases the value of the key. The time complexity of this operation is O(log N). If the decreased key value of a node is greater than the parent of the node, then we don't need to do anything. Otherwise, we need to traverse up to fix the violated heap property.
- insert(): Inserting a new key takes O(log N) time. We add a new key at the end of the tree. If the new key is greater than its parent, then we don't need

to do anything. Otherwise, we need to traverse up to fix the violated heap property.

delete(): Deleting a key also takes O(log N) time. We replace the key to be
deleted with the minimum infinite by calling decreaseKey(). After
decreaseKey(), the minus infinite value must reach root, so we call
extractMin() to remove the key.

Below is the implementation of basic heap operations.

C++ Python C# **JavaScript** Java O 1 # A Python program to demonstrate common binary heap operations 2 3 # Import the heap functions from python library 4 from heapq import heappush, heappop, heapify 5 6 # heappop - pop and return the smallest element from heap 7 # heappush - push the value item onto the heap, maintaining heap invarient 8 9 # heapify - transform list into heap, in place, in linear time 10 # A class for Min Heap 11 class MinHeap: 12 13 14 # Constructor to initialize a heap def __init__(self): 15 16 self.heap = [] 17 18 def parent(self, i): return (i-1)/2 19 20 # Inserts a new key 'k' 21 def insertKey(self, k): 22 heappush(self.heap, k) 23 24 # Decrease value of key at index 'i' to new val 25 # It is assumed that new val is smaller than heap[i] 26 def decreaseKey(self, i, new val): 27

```
self.heap[i] = new_val
            while(i != 0 and self.heap[self.parent(i)] >
29
   self.heap[i]):
                # Swap heap[i] with heap[parent(i)]
30
                self.heap[i] , self.heap[self.parent(i)] = (
31
                self.heap[self.parent(i)], self.heap[i])
32
33
        # Method to remove minimum element from min heap
34
        def extractMin(self):
35
            return heappop(self.heap)
36
37
        # This function deletes key at index i. It first
38
   reduces
       # value to minus infinite and then calls extractMin()
39
        def deleteKey(self, i):
40
            self.decreaseKey(i, float("-inf"))
41
            self.extractMin()
42
43
       # Get the minimum element from the heap
44
        def getMin(self):
45
46
            return self.heap[0]
47
   # Driver pgoratm to test above function
48
   heapObj = MinHeap()
49
   heapObj.insertKey(3)
50
   heapObj.insertKey(2)
51
  heapObj.deleteKey(1)
52
   heapObj.insertKey(15)
   heapObj.insertKey(5)
54
   heapObj.insertKey(4)
55
   heapObj.insertKey(45)
56
57
   print heapObj.extractMin(),
58
   print heapObj.getMin(),
59
   heapObj.decreaseKey(2, 1)
60
   print heapObj.getMin()
61
62
63 # This code is contributed by Nikhil Kumar
   Singh(nickzuck_007)
```

Output

2 4 1

Applications of Heaps:

- Heap Sort: Heap Sort uses Binary Heap to sort an array in O(nLogn) time.
- Priority Queue: Priority queues can be efficiently implemented using Binary Heap because it supports insert(), delete() and extractmax(), decreaseKey() operations in O(log N) time. Binomial Heap and Fibonacci Heap are variations of Binary Heap. These variations perform union also efficiently.
- Graph Algorithms: The priority queues are especially used in Graph Algorithms like <u>Dijkstra's Shortest Path</u> and <u>Prim's Minimum Spanning Tree</u>.
- Many problems can be efficiently solved using Heaps. See following for example. a) K'th Largest Element in an array. b) Sort an almost sorted array/c) Merge K Sorted Arrays.

Related Links:

- Coding Practice on Heap
- All Articles on Heap
- Quiz on Heap
- PriorityQueue: Binary Heap Implementation in Java Library

Join <u>GfG 160</u>, a 160-day journey of coding challenges aimed at sharpening your skills. Each day, solve a handpicked problem, dive into detailed solutions through articles and videos, and enhance your preparation for any interview—all for free! Plus, win exciting GfG goodies along the way! - <u>Explore Now</u>



Previous Article Next Article

Introduction to Heap - Data Structure and Advantages and Disadvantages of Heap Algorithm Tutorials

Similar Reads

Difference between Binary Heap, Binomial Heap and Fibonacci Heap

Binary Heap: A Binary Heap is a Binary Tree with following properties. It's a complete binary tree i.e., all levels are completely filled except possibly the last...

2 min read

Convert Min Heap to Max Heap

Given an array representation of min Heap, convert it to max Heap. Examples: Input: $arr[] = \{3, 5, 9, 6, 8, 20, 10, 12, 18, 9\} \ 3 / \ 5 9 / \ 6 \ 8 \ 20 \ 10 / \ 12 \ 18 \ 9...$

10 min read

Heap Sort for decreasing order using min heap

Given an array of elements, sort the array in decreasing order using min heap. Examples: Input: $arr[] = \{5, 3, 10, 1\}$ Output: $arr[] = \{10, 5, 3, 1\}$ Input: $arr[] = \{1...$

13 min read

When building a Heap, is the structure of Heap unique?

What is Heap? A heap is a tree based data structure where the tree is a complete binary tree that maintains the property that either the children of a node are les...

4 min read

Difference between Min Heap and Max Heap

A Heap is a special Tree-based data structure in which the tree is a complete binary tree. Since a heap is a complete binary tree, a heap with N nodes has log ...

3 min read

What's the relationship between "a" heap and "the" heap?

A Heap: "A Heap" refers to the heap data structure where we can store data in a specific order. Heap is a Tree-based data structure where the tree is a complete...

15+ min read

Complexity analysis of various operations of Binary Min Heap

A Min Heap is a Complete Binary Tree in which the children nodes have a higher value (lesser priority) than the parent nodes, i.e., any path from the root to the le...

3 min read

Print all the leaf nodes of Binary Heap

Given an array of N elements which denotes the array representation of binary heap, the task is to find the leaf nodes of this binary heap. Examples: Input: arr[] ...

7 min read

Find min and max values among all maximum leaf nodes from all possible...

Given a positive integer N, the task is to find the largest and smallest elements, from the maximum leaf nodes of every possible binary max-heap formed by...

7 min read

Check if Binary Heap is completely filled

Given an integer N which denotes the number of elements in a binary heap. Check if the binary Heap is completely filled or not. Examples: Input: 7Output:...

4 min read

Article Tags: DSA Heap

Practice Tags: Heap



Corporate & Communications Address:-A-143, 9th Floor, Sovereign Corporate Tower, Sector- 136, Noida, Uttar Pradesh (201305) | Registered Address:- K 061, Tower K, Gulshan Vivante Apartment, Sector 137, Noida, Gautam Buddh Nagar, Uttar Pradesh, 201305





Company

About Us
Legal
In Media
Contact Us
Advertise with us

GFG Corporate Solution
Placement Training Program
GeeksforGeeks Community

DSA

Data Structures
Algorithms
DSA for Beginners
Basic DSA Problems
DSA Roadmap

Top 100 DSA Interview Problems DSA Roadmap by Sandeep Jain All Cheat Sheets

Web Technologies

HTML

JavaScript

TypeScript

ReactJS

NextJS

Bootstrap

Web Design

Computer Science

Operating Systems

Computer Network

Database Management System

Software Engineering

Digital Logic Design

Engineering Maths

Software Development

Software Testing

System Design

High Level Design

Low Level Design

UML Diagrams

Interview Guide

Design Patterns

Languages

Python

Java

C++

PHP GoLang

SQL

R Language

Android Tutorial

Tutorials Archive

Data Science & ML

Data Science With Python

Data Science For Beginner

Machine Learning

ML Maths

Data Visualisation

Pandas

NumPy

NLP

Deep Learning

Python Tutorial

Python Programming Examples

Python Projects

Python Tkinter

Web Scraping

OpenCV Tutorial

Python Interview Question

Django

DevOps

Git

Linux

AWS

Docker

Kubernetes

Azure

GCP

DevOps Roadmap

Inteview Preparation

Competitive Programming

Top DS or Algo for CP

Company-Wise Recruitment Process

Company-Wise Preparation

Aptitude Preparation

OOAD Puzzles

System Design Bootcamp
Interview Questions

School Subjects

GeeksforGeeks Videos

Mathematics DSA
Physics Python
Chemistry Java
Biology C++

Social Science Web Development
English Grammar Data Science
Commerce CS Subjects

World GK

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved