

Co-Pilot AI Scientist v3: Insight-Gated Research Evolution for Collaborative Automated Science

Abstract

Automated research agents can now propose hypotheses, run experiments, write manuscripts, and optimize code, but they still lack a principled way to use human scientific taste: the non-metric judgement that some problems, failures, mechanisms, or claim boundaries are more worth pursuing than others. Generic co-pilot workflows usually treat humans as approvers or editors, while fully autonomous systems remove the very judgement that often determines whether a research direction is important. We introduce Insight-Gated Research Evolution (IGRE), a workflow architecture that converts human taste and expert-review insight into explicit control signals inside AI Scientist-v2-style research loops. IGRE uses five gates: scientific-taste prior, evaluator stress test, frontier steering, verifiable micro-evolution, and claim calibration. We further introduce Temporal Frontier Replay (TFR), an offline replay protocol that asks whether historical peer reviews would have moved an automated researcher toward later field trajectories. Together, IGRE and TFR make human participation measurable rather than assumed beneficial: gates are logged with evidence, attention cost, and claim boundaries, while historical review signals are replayed against future-frontier evidence. We evaluate the package with FML-bench style runs, OpenEvolve-style micro-evolution probes, OpenReview-derived expert-review signals, paired manuscript probes, TFR audits, and clean-clone reproducibility checks. The current evidence supports a conservative claim: expert review text can be mapped into actionable workflow gates, review-guided regeneration improves some research artifacts under cross-model review, TFR is operationalized but currently negative for delayed-value evidence, and short-budget human-gated FML runs are mixed or negative rather than automatically superior. This is therefore not a proof that humans always improve automated science. It is a reproducible method for designing, comparing, and auditing the modes by which human insight can alter scientific search.

1. Introduction

The recent wave of AI research agents has made a strong case for automation. Systems such as AI Scientist-v2 can generate ideas, run experiments, and produce papers. AI Co-Scientist-style systems organize hypotheses through generate, debate, and evolve loops. AlphaEvolve demonstrates that language models can drive evolutionary code search when candidate programs can be evaluated automatically. These systems expose a tempting conclusion: if the benchmark and evaluator are clear, the human can be removed from the loop.

Scientific research, however, is not only a process of optimizing a visible metric. Researchers also decide which questions are deep, which failure is informative, which mechanism is worth isolating, and which result is too weak to claim. These judgements are often called taste or insight. They are not fully captured by benchmark scores, but they are not mystical either: they appear concretely in paper reviews, rebuttals, lab discussions, claim audits, and decisions to abandon or reframe a direction.

This paper asks a narrower and more useful question than whether human participation is always better than full automation. The question is: which forms of human participation can be turned into workflow-control signals that improve the search process or the accountability of automated research? This framing matters because human involvement is high-variance. A human gate may steer the system toward a rare high-value idea, but it may also slow the run, inject bias, overfit to taste, or choose a worse branch than the autonomous policy. A credible co-pilot method must therefore measure both positive and negative effects.

We propose Insight-Gated Research Evolution (IGRE), the core algorithmic pattern of Co-Pilot AI Scientist v3. IGRE is inspired by prior automated-research systems, but it is not a direct collage of them. The method adapts their ideas around a different object: not autonomous discovery alone, but the insertion of human scientific taste into the parts of the loop where non-metric judgement is useful and dangerous. IGRE treats human insight as a logged search operator. It can modify the prior over research directions, stress the evaluator, steer the hypothesis frontier, trigger small verifiable program searches, or calibrate manuscript claims.

The primary claim of this paper is therefore deliberately narrow: expert review and human scientific judgement can be operationalized as auditable workflow-control signals, and the usefulness of those signals can be compared experimentally. We do not claim that the current co-pilot system outperforms autonomous AI Scientist-v2. The current paper makes four contributions. First, it defines IGRE as a five-gate architecture for human-guided automated science. Second, it releases a reproducible evidence package with bilingual manuscripts, scripts, logs, gate schemas, audits, and a reusable Codex skill. Third, it introduces Temporal Frontier Replay (TFR), an offline protocol for using historical peer reviews to test whether human insight would have steered automated research toward later field trajectories. Fourth, it reports mixed and negative short-budget results alongside positive workflow probes, keeping the claim boundary explicit: IGRE currently supports workflow design and measurement readiness, not a top-conference-level proof of co-pilot superiority.

2. Related Work

AI Scientist-v2 represents the autonomous research-agent line: generate ideas, execute experiments, write papers, and evaluate outputs. Its strength is end-to-end automation, but this also means that human scientific taste is not a first-class object in the algorithm. AI Co-Scientist-style work emphasizes hypothesis generation, critique, ranking, and evolution. It is close to IGRE in its view of scientific search as a frontier, but IGRE adds explicit human gates, attention-cost logging, and claim calibration.

AlphaEvolve and OpenEvolve motivate IGRE's verifiable micro-evolution gate. They show that language-model-generated code changes can be evolved through automatic evaluation. IGRE uses this idea selectively: micro-evolution is triggered when the target is machine-gradeable and the cost is justified, rather than being treated as a universal replacement for direct editing.

Human-AI co-pilot systems usually provide assistance, editing, or approval. IGRE differs by making the human role algorithmic. A human intervention must be classified, logged, connected to evidence, and audited against downstream outcomes. The point is not that every human comment is useful. The point is to identify which comments are actionable as scientific search controls.

Peer-review datasets such as OpenReview provide a useful proxy for this problem. Real reviews contain human judgements about novelty, evaluation, correctness, clarity, impact, and claim boundaries. They are imperfect, noisy, and retrospective, but they are one of the few large public traces of expert scientific taste. IGRE uses them not as a replacement for live human co-pilot data, but as a scalable offline testbed for participation-mode design.

3. Method: Insight-Gated Research Evolution

IGRE models a research run as a sequence of machine actions interrupted by explicit gates. Each gate can alter the next action, but it must record the reason, evidence, cost, and claim boundary. This makes human involvement auditable and comparable to autonomous baselines.

The first gate is the scientific-taste prior. It selects or reweights research directions before expensive experimentation. A useful taste prior is not a vague preference. It should explain why a direction has depth, novelty potential, mechanistic value, failure informativeness, benchmark fit, or asymmetric upside. In the current package, OpenReview novelty and impact comments are used as an offline proxy for this gate.

The second gate is the evaluator stress test. It asks whether the metric is too easy, too narrow, or gameable. In automated science this is crucial because an agent can optimize the evaluator while missing the scientific target. Review comments about missing baselines, weak metrics, leakage, poor ablations, or invalid comparisons are routed here.

The third gate is frontier steering. It operates over a portfolio of hypotheses or implementation branches. Rather than approving one output at the end, the human or review-derived signal chooses which part of the search frontier should receive more budget. This gate is useful when the best direction is not simply the one with the best early score.

The fourth gate is verifiable micro-evolution. It applies OpenEvolve-style program search to narrow machine-gradeable subproblems such as heuristic design, vectorization, tabular modeling, or small combinatorial objectives. IGRE treats this as an escalation operator. Direct editing remains preferable when the task is simple, when evaluation is expensive, or when search adds little beyond a strong baseline.

The fifth gate is claim calibration. It edits the manuscript-level interpretation of evidence. This gate is not cosmetic. It decides whether a result supports superiority, feasibility, measurement readiness, a negative result, or only a future-work claim. Many expert reviews are useful precisely because they force this boundary.

The gates form the following algorithmic loop. The system proposes a research frontier, evaluates early artifacts, maps human or review-derived signals into gate actions, updates the frontier or evaluator, optionally performs micro-evolution, and finally writes a claim-audited manuscript. Every gate has a structured record containing the gate type, artifact reviewed, options considered, decision, rationale, expected upside, possible harm, attention cost, and downstream evidence. This structure is what distinguishes IGRE from informal co-pilot interaction.

IGRE also includes an offline learning and evaluation mode, Temporal Frontier Replay (TFR). TFR is the mechanism that turns retrospective peer-review data into a test of scientific taste rather than merely another paper-quality rubric. Given a historical paper at time t , its reviews, and later field evidence at $t + \delta$, TFR constructs three replay conditions: paper-only, review-guided, and shuffled-review-control. It then asks whether the review-guided replay improves only local artifact quality, or whether it also moves the generated research plan toward later mainstream or SOTA directions. A delayed-value signal is the temporally asymmetric case: review guidance may make the immediate artifact worse under short-term scores, but better aligned with later field evolution. This is the specific kind of human taste that IGRE is designed to preserve.

TFR is not an extra borrowed benchmark. It is an adaptation required by the co-pilot question. Standard benchmark comparison measures whether a branch wins now. TFR measures whether a human comment changes what the agent should search for later. In the current package, TFR is implemented through a deterministic smoke, a citation-backed frontier probe, direct review-frontier signal mining, and a semantic frontier judge. These probes are still small and currently negative for delayed-value evidence, but they make the high-tail hypothesis falsifiable: useful human insight must be routed, replayed, and tested against a future frontier, not assumed valuable because it came from a human reviewer.

4. Experiments

The experiments are designed around participation-mode selection, not around proving that humans always beat automation. The evidence package asks four questions.

The main quantitative evidence is summarized below. The table intentionally mixes positive, mixed, and negative results because IGRE is evaluated as a gate-selection framework, not as a guaranteed performance booster.

| Probe | Co-pilot or review-guided result | Baseline or autonomous result | Delta or win count | Interpretation | | --- | ---: | ---: | ---: | --- | | Review utility map | 398 actionable snippets | 64 noisy snippets | 473 snippets total | Expert reviews contain routeable taste/insight signals. | | Gate-structure ablation | full IGRE utility capture 1.000 | best single gate 0.369; random gate mean 0.199; no-gate 0.000 | full vs. best single +2359 utility units | Multi-gate routing is needed because review insight is heterogeneous; this is routing evidence, not downstream quality proof. | | Gate-outcome attribution | full IGRE aligned score 75.17 | best single gate 37.25; random gate mean 15.26 | full vs. best single +37.92 | Post-hoc downstream attribution over six OpenReview pairs; not causal proof. | | Single-gate artifact ablation | best single gate mean 3.6667 | full review-guided 3.5; baseline 2.9166 | best single vs. baseline +0.7501 | Causal-style mini-artifact ablation; targeted evaluator-stress can beat full review guidance in this small proxy. | | OpenReview regeneration, same scorer | 5 review-guided wins | 1 baseline win | mean overall +0.8333 | Positive but vulnerable to same-model and extra-context bias. | | OpenReview regeneration, Claude cross-review | 3 review-guided wins | 1 baseline win, 2 ties | mean overall +0.1667 | Modest positive signal; not automatic improvement. | | OpenReview equal-context ablation | 8 review-guided votes | 1 context-control vote, 3 ties | mean delta across models +0.5 | Paper-specific reviews beat matched unrelated review context, but Claude shows the effect is modest. | | Preregistered blind expert-review packet | 6 anonymized A/B pairs prepared | 0 completed human rows | planned 3-5 raters | Evaluation readiness only; no human evidence is claimed yet. | | Live skill invocation smoke | 3 candidate directions and 5 IGRE gates generated | template-only skill smoke | 2 live model calls, audit recommendation pass | Shows the Codex skill can be reused on a fresh task; not benchmark evidence. | | Metric-gaming evaluator-stress smoke | evaluator-stress gate selects guardrailed_utility_model | primary-only fairness metric selects metric_gaming_all_negative | 1 synthetic metric-gaming incident reduced | Links the live skill task to an actual evaluator; controlled toy evidence, not FML-bench. | | FML Fairness evaluator-stress replay | gate rejects metric-gaming and aborts no-valid continuation | primary-only FML metric selects metric_gaming_all_negative | 1 archived FML metric-gaming incident reduced | Real FML-Bench artifact replay; supports gate design, not Fairness improvement. | | Retrospective frontier-alignment smoke | review-guided wins 1 | shuffled-control wins 5 | mean delta vs. control -0.0855; 0 delayed-value cases; 3 short-term-positive/long-term-negative cases | Future-frontier alignment is harder than local paper improvement; heuristic descriptors only. | | Citation-backed frontier pilot | review-guided wins 1 | paper-only wins 3; shuffled-control wins 1; 1 case not scored | 6 papers, 80 relevance-filtered later citations, mean delta vs. paper-only -0.02 | Relevance filtering and match-drift guards are implemented; no delayed-value cases are found, and 3 cases are short-term-positive/long-term-negative. | | Review-frontier signal mining | best review snippets scored 0.1431 mean | paper context 0.2369; review-guided artifact 0.1906 | 0 review-beats-paper cases; 0 latent delayed-value candidates | Historical reviews contain routeable gates, but this lexical future-frontier test finds that the original paper context carries more citation-frontier terms than the review snippets. | | Semantic frontier judge | review-guided artifact wins 1 | paper context wins 4 | 5 model-judged cases; 0 delayed-value candidates | A model judge using citation metadata also favors original paper context; one review-guided artifact is short-and-semantic positive, not delayed-value. | | Prospective matched packages | 1 co-pilot or human-selected win | 3 autonomous/tie/invalid outcomes | 4 packages | Short-budget average benchmark superiority is not supported. | | Same-run online FML smokes | 0 co-pilot benchmark wins | 1 autonomous win, 1 tie, 1 unknown | 3 paired smokes | Current valid benchmark evidence leans autonomous or tie. | | MLAGentBench vectorization | correct search in 8/8 seeds, median 0.024581 s | starter 3.261186 s; direct rewrite failed correctness | large runtime gain | Micro-evolution helps on a correctness-gated code subproblem. | | Sklearn diabetes tabular probe | OpenEvolve median RMSE 55.895460 | direct rewrite RMSE 55.895460 | no search advantage | Direct editing can be enough on simple modeling tasks. |

The resulting claim-to-evidence map is deliberately conservative.

| Paper claim | Evidence status | Claim boundary | | --- | --- | --- | | IGRE is this paper's five-gate method for treating human taste as a logged research-control signal. | Supported as a method and artifact contribution. | Not a claim that every human intervention improves outcomes. | | OpenReview-style expert reviews can proxy human taste/insight for offline workflow design. | Supported for routeability: 398 actionable snippets and strong multi-gate utility capture. | Offline peer review is not the same as live co-pilot data. | | Targeted gate routing can be more useful than giving the agent all human context. | Supported narrowly by the single-gate artifact ablation. | Model-reviewed mini-artifacts only; needs human expert validation. | | TFR can test whether past reviews would have moved automated science toward later frontiers. | Supported as an operationalized replay protocol. | Current small sample finds 0 delayed-value cases, so the long-horizon hypothesis remains unproven. | | Human-gated short-budget FML runs outperform autonomous runs. | Not supported. | Current evidence is mixed or negative and should be treated as a failure-mode lesson. | | OpenEvolve-style micro-evolution improves some machine-gradeable subproblems. | Supported narrowly. | Trigger selectively; direct editing is competitive on simple tasks. |

4.1 Can expert review text be mapped into useful workflow gates?

We use the Hugging Face nhop/OpenReview dataset through streaming access, avoiding a full local download. The probe verifies 34,638 dataset rows and samples 160 rows. From these rows, a deterministic review-utility map extracts 473 review snippets. It marks 398 snippets as actionable and 64 as noisy or low-actionability.

The most common actionable route is evaluator stress testing, with 245 triggers. Structured feedback receives 210 triggers, claim calibration receives 140, and scientific-taste prior receives 111. At the category level, evaluation and metric issues appear 205 times, limitations and claim-boundary issues 140 times, novelty and positioning 111 times, reproducibility 79 times, and method-correctness 71 times.

We then run a gate-structure ablation on the same review-utility map. A no-gate policy captures no actionable routed utility. The best single-gate policy, evaluator stress testing, captures 0.369 of available utility; structured feedback captures 0.295; claim calibration captures 0.187; scientific-taste prior captures 0.148. A random-gate baseline averaged across 128 seeds captures 0.199. Full IGRE captures 1.000 by preserving all five explicit gates. This ablation does not prove better final papers, but it does establish a structural reason for IGRE: human review insight is not one generic approval signal, so compressing it into a single gate systematically drops useful scientific taste and evaluator-design information.

Finally, we run a downstream gate-outcome attribution probe using the six equal-context OpenReview regeneration pairs. The probe links each paper's review-derived gate utility to the observed review-guided minus context-control score deltas from GPT and Claude reviewers. Full IGRE obtains aligned-outcome score 75.17, while the best single gate, evaluator stress testing, obtains 37.25 and a 512-seed random single-gate baseline averages 15.26. The strongest observed downstream alignment comes from evaluator stress testing, structured feedback, and scientific-taste prior. Frontier steering and claim calibration have no nonzero signal in this six-paper subset, so this is a post-hoc attribution signal rather than a causal five-gate downstream proof.

We then run a causal-style single-gate artifact ablation. For each selected paper, we generate new mini-paper artifacts from title/abstract plus only one gate-specific subset of reviews, and compare them with title/abstract baseline and full review-guided artifacts under GPT and Claude reviewers. The best single-gate condition is evaluator stress testing, with mean overall score 3.6667. Full review-guided obtains 3.5, and baseline obtains 2.9166. Winner votes are split across baseline (3), full review-guided (2), evaluator stress testing (6), and structured feedback (1). This result is important because it is not simply pro-human. It suggests that targeted evaluator-stress review can be more useful than feeding all review text, while baseline remains competitive for some information-rich abstracts. IGRE therefore needs gate selection, not maximal human context.

This supports the user's central intuition: human review is a concrete trace of scientific taste and insight. But the useful signal is not all review text. It is the subset that can alter evaluator design, search direction, manuscript structure, or claim boundaries.

4.2 Does review-guided regeneration improve research artifacts?

We select six ML/AI OpenReview papers and generate paired mini-paper artifacts. The baseline condition uses only title and abstract. The review-guided condition also uses real review snippets and decision text. An initial scorer prefers review-guided artifacts in 5 of 6 pairs, increasing mean overall score from 3.0 to 3.8333.

To reduce same-model scoring bias, we rescore the same six pairs with a stricter cross-model review route. Under this review, review-guided artifacts win 3 of 6 pairs, the baseline wins 1 pair, and 2 pairs tie, with a smaller mean delta of +0.1667. The conservative conclusion is that review text is useful when it adds concrete method detail, experiment specificity, limitation awareness, or claim calibration. It is not automatically helpful when the feedback is generic or causes the regeneration to lose the original technical framing.

This probe has an important confound. The review-guided condition receives more information than the title/abstract baseline. We therefore run an equal-context ablation using matched-length unrelated OpenReview snippets as a context-control condition. Across two reviewer models and six papers, review-guided artifacts receive 8 winning votes, context-control receives 1, and 3 comparisons tie, with mean delta across models +0.5. The stricter Claude review gives 3 review-guided wins, 0 context-control wins, and 3 ties, with mean delta +0.1667. This supports a more precise conclusion: paper-specific reviews can add value beyond generic reviewer pressure, but mostly when they contain concrete method details or explicit claim-calibration warnings.

4.3 Do short-budget human gates beat autonomous baselines?

The prospective FML-bench-style matched packages are intentionally reported as mixed or negative. Across the current passing packages, there is one controlled Max-Cut micro-task where a human-selected branch is useful, and three FML-bench cases where the co-pilot branch loses, ties, aborts, or fails to produce a valid continuation. In repeated online paired smokes, valid Causality runs produce 0 co-pilot benchmark wins, 1 autonomous win, and 1 tie; the Fairness run is a no-valid-branch failure case.

This result is important. It prevents the paper from claiming that human participation improves average benchmark performance under tiny budgets. Instead, it motivates the core design problem: human gates must be specific, budget-aware, and routed to the parts of the workflow where taste and insight actually matter.

4.4 When should verifiable micro-evolution be triggered?

OpenEvolve-style search is valuable on some machine-gradeable subproblems, but not all. On a vectorization task, direct rewrite fails correctness while short OpenEvolve-style search retains correct programs and finds large runtime improvements. On Max-Cut, direct editing improves the starter, while OpenEvolve-style search gives a small additional gain. On a simple sklearn diabetes regression probe, direct editing matches the median OpenEvolve result. This boundary condition is central to IGRE: program search should be triggered by evaluator readiness and expected marginal value, not by methodological fashion.

5. Discussion

IGRE reframes human participation as a high-variance search operator. This is a better fit for science than the claim that human involvement is always positive. Human judgement can increase the chance of rare, high-value trajectories by noticing problem depth, mechanism, novelty, or claim risk that a metric misses. But it can also reduce average score under short budgets.

The OpenReview experiments suggest a practical way forward. Real review comments can be mined to discover what types of human insight are useful. Comments about weak evaluation should trigger evaluator stress tests. Comments about novelty should reshape the taste prior. Comments about missing limitations should trigger claim calibration. Comments about unclear presentation should become structured feedback. Vague praise or generic criticism should have low routing weight.

The retrospective nature of peer review can also be used as a measurement advantage. For historical papers, later field evolution provides a post-hoc frontier target. IGRE can therefore run a retrospective frontier-alignment experiment: take a paper and its reviews at time t , regenerate follow-up research artifacts with paper-only, review-guided, and shuffled-review-control conditions, and judge which artifacts better align with the field's later mainstream or SOTA trajectory. A good review is then not merely a review that scores a paper harshly or positively. It is a review whose actionable comments would have moved the automated research workflow toward a future-relevant problem framing, method, evaluation norm, failure mode, or claim boundary.

A first deterministic smoke of this protocol is intentionally sobering. Using manual, non-citation-backed future-frontier descriptors on the same six OpenReview cases, the review-guided artifacts win only 1 of 6 comparisons under a keyword/actionability score, while shuffled-review-control artifacts win 5 of 6 and the review-guided mean score is below the shuffled control by 0.0855. This does not invalidate the protocol, because the descriptors and score are only a pipeline smoke. It does show that future-frontier alignment is a stricter target than local paper-quality improvement, and that "good review" must be defined by future-relevant directionality rather than by generic reviewer pressure.

The most important case is temporally asymmetric. A review-guided rerun may produce a paper that is worse than the original paper under immediate quality or benchmark criteria, but better aligned with later field evolution. Such a case would be a delayed-value review signal: the human comment is not valuable because it improves the next artifact, but because it changes the search trajectory toward a future-relevant direction. If a corpus of these comments can be identified, IGRE can learn where human taste should override short-term automation pressure.

The current smoke does not yet find this delayed-value pattern. It finds the opposite diagnostic in three cases: review guidance improves the short-term model-scored artifact, but decreases heuristic future-frontier alignment. This negative result is useful because it separates local reviewer satisfaction from long-horizon scientific directionality, which is exactly the distinction a co-pilot scientist must learn.

A citation-backed version of the probe now runs on six OpenReview samples with OpenAlex fallback, lexical relevance filtering, and a title-overlap guard against match drift. It retrieves usable future-frontier terms for 5 of 6 papers and 80 relevance-filtered later citations. The result is again sobering: review-guided regeneration wins only 1 case, paper-only wins 3, shuffled-review control wins 1, and one case is not scored because the metadata match drifts. The mean review-guided citation-frontier score is 0.21, below paper-only 0.23 and shuffled-control 0.248. The probe finds 0 delayed-value cases and 3 short-term-positive/long-term-negative cases. This is not evidence against the delayed-value hypothesis; it shows that the current lexical frontier metric can reward original paper terminology more than review-derived direction changes, and that future-frontier measurement must solve citation coverage, topical relevance, metadata match-drift, and semantic rather than lexical alignment.

We therefore add a stricter review-frontier signal probe that scores the historical review snippets themselves against citation-derived frontier terms. Across 16 review snippets from the six papers, the best review snippets have mean future-frontier score 0.1431, while the original paper context scores 0.2369 and the review-guided artifact scores 0.1906. No review snippet beats the paper context or the generated artifact, and no latent delayed-value candidate is found. This negative result is useful. It prevents the paper from treating OpenReview as a magic source of human taste. The actionable conclusion is narrower: peer review is a scalable offline proxy for testing participation modes, but useful taste/insight signals must be filtered, routed, and validated against stronger semantic and human-judged future-frontier measures.

To check whether this negative result is merely an artifact of lexical overlap, we run a small semantic judge probe using a Monica-routed gpt-4o-mini judge. The judge sees the original paper context, the best historical review snippet, the review-guided regenerated artifact, and metadata from later citing papers. Across the five cases with future-frontier terms, paper context wins 4 times and review-guided artifact wins once. Mean semantic-frontier scores are 4.2 for paper context, 3.4 for review-guided artifact, and 3.0 for the best review snippet. The single review-guided win is a knowledge-unlearning case where the artifact is both short-term and semantic positive. The semantic probe therefore still finds 0 delayed-value candidates. This narrows the claim further: the delayed-value design is conceptually important and now measurable, but the current small OpenReview sample does not yet provide positive evidence for it.

This makes the paper's application value concrete. The goal is not merely to prove that humans improve paper quality. The goal is to design the best modes of human participation, compare them empirically, and build a workflow in which human taste is used where it has the highest chance of changing the research trajectory.

6. Limitations

The current evidence is a pilot package. It does not include independent human expert review of the final IGRE paper or of the paired regenerated artifacts. The live co-pilot trace is a single-author derived metadata corpus, not a population-level dataset of many scientists using the system. OpenReview is offline asynchronous review data, not real-time human intervention inside an AI Scientist-v2 run. The matched-budget FML evidence is underpowered and currently negative or mixed for benchmark performance. The equal-context OpenReview ablation reduces, but does not eliminate, concerns about context confounds because it still relies on model-routed scoring and regenerated mini-artifacts rather than blind expert review. The high-tail hypothesis, that human taste may increase rare breakthrough probability even if average score falls, is conceptually important but not yet statistically operationalized.

These limitations are also future research directions. To make the next step concrete, the repository includes a prepared and preregistered blind-review packet for the six OpenReview regeneration pairs: reviewers see anonymized A/B artifacts, a fixed rubric, and a score-sheet template, while the condition key and analysis plan are held by the coordinator until ratings are complete. The plan defines useful human taste and insight as review signals that can change research-control decisions, not as generic approval. This packet is not evidence yet because no independent human ratings have been collected. A stronger study would deploy a reusable co-pilot scientist skill to many researchers, collect privacy-preserving gate metadata with consent, run matched autonomous and human-gated trajectories across tasks, and submit paired outputs to blind expert review. At present, such live multi-researcher data is more feasible for major agent or model companies than for a small independent project. IGRE therefore uses OpenReview as a scalable offline proxy and clearly marks the gap.

7. Conclusion

Co-Pilot AI Scientist v3 proposes IGRE, a five-gate architecture for inserting human scientific taste and expert-review insight into automated research loops. The evidence does not show that human participation automatically improves automated science. It shows something more specific and more useful: expert review contains actionable signals, these signals can be routed into workflow gates, review guidance can improve some regenerated artifacts, and short-budget human gates must be audited because they can fail. IGRE turns this into a reproducible method for designing and comparing human-AI scientific collaboration.