

Architecture

Solutions pour étudiants Exercices Architecture des ordinateurs

1 | Architecture

1.1 Stack-Architecture

- a) -
- b) 7 explicit fetch and none implicit
- c) 7 explicit fetch, 4 implicit fetch, 4 implicit store

arc/stack-01

1.2 Stack-Architecture

- a) -
- b) 7 explicit fetch
- c) 7 explicit fetch (with compiler optimizations)7 explicit fetch, 1 implicit store, 1 implicit fetch (without compiler optimizations)
- d) 7 explicit fetch, 3 implicit store, 3 implicit fetch (without compiler optimizations)

arc/stack-02

2 | Single-Cycle RISC-V

2.1 Fonctionnement du processeur à cycle unique

```
PCScr = '0'
RegWrite = '1'
ImmScr[1:0] = "xx"
ALUSrc = '0'
ALUControl[2:0] = "010"
MemWrite = '0'
ResultScr = '0'
```

arc/scr-01

2.2 Prolonger le mono-cycle avec l'instruction jal



```
PCScr = '0'
RegWrite = '1'
ImmScr[1:0] = "xx"
ALUSrc = '0'
ALUControl[2:0] = "010"
MemWrite = '0'
ResultScr = '0'
```

arc/scr-02

2.3 Performance du processeur à mono-cycle

$$T_{\text{program_single_cycle}} = 75 \text{sec}$$
 (1)

arc/scr-03

3 | Multi-Cycle RISC-V

3.1 Performance du processeur à multi-cycle

$$\begin{split} \text{CPI}_{\text{load}} &= 5 \text{ cycles} \\ \text{CPI}_{\text{store}} &= 4 \text{ cycles} \\ \text{CPI}_{\text{branch}} &= 3 \text{ cycles} \\ \text{CPI}_{\text{jump}} &= 4 \text{ cycles} \\ \text{CPI}_{\text{alu}} &= 4 \text{ cycles} \\ \text{CPI}_{\text{average}} &= 4.14 \text{ cycles} \end{split}$$

arc/mcr-01

3.2 Performance du processeur à multi-cycle

$$T_{\rm program_single_cycle} = 155.25 {\rm sec} \tag{3}$$

arc/mcr-02

HEI-Vs / ZaS, AmA / 2024