

COMP2045

Programming and Problem Solving

Migrate from Python

Where were we?


- Most of us have experience of **Python** or **Processing** or some other languages (C/C++, JS, etc..)
- I assume you still have some blurry memory with the following terms:
 - Loops
 - Variables
 - Operators
 - if-else
 - Functions/Methods

Processing vs Java

- Little cousin of Java
- Concepts are somewhat related and close to Java
 - Variables
 - if-then-else
 - Functions
 - Looping
 - Arrays
- Even syntax is almost the same as Java

Python vs Java

- Quite different from Java
- Python allows you to quickly come up with little programs for testing ideas
- Java allows you to build a larger software in a more structured way

 Assume you still remember Python a bit, this notes serves as a quick cheatsheet to migrate from Python to Java.

Comment in Python

```
# This is a comment in Python  
  
'''  
This is a multiple line comment  
in Python.  
'''
```

Comment in Java

```
// This is a comment in Java  
  
/* This is a multiple lines  
   in Java. */
```

  Tips: in most IDE pressing 'CTRL' + '/' (or CMD + / in mac) is a comment toggle.

Arithmetic in Python

```
a = 1 + 2 - 5  
b = 4 / 2  
c = 3 * 9  
d = 3 ** 4 # power  
e = 42 % 5 # remainder  
f = 84 // 5 # floor division
```

Arithmetic in Java

```
a = 1 + 2 - 5;  
b = 4 / 2;  
c = 3 * 9;  
e = 42 % 5; // remainder
```



floor division and power needs to be done via the APIs


`Math.floorDiv()` and `Math.pow()`

Assignment in Python

```
a = 4
```

Assignment in Java

```
a = 4;  
a++;    // same as a = a + 1  
++b;    // same as b = b + 1  
c--;    // same as c = c - 1  
--d;    // same as d = d - 1
```

 On top of that both language support assignment operators like `+=`, `-=` etc.

If-then-Else in Python

```
if a == 1:
    print("one command")
    print("Another command")
else:
    print("else")
```

multiple statements are grouped by indentation

If-then-Else in Java

```
if (a == 1) {
    System.out.println("one command");
    System.out.println("another line");
} else
    System.out.println("else");
```

multiple statements are grouped by `{ }`

If-then-Else in Python

```
if a == 1:
    print("one command")
    print("another line")
elif b > 3:
    print("alternatively")
else:
    print("else")
```

Use the keyword `elif` to handle multiple cases.

If-then-Else in Java

```
if (a == 1) {
    System.out.println("one command");
    System.out.println("another line");
} else if (b > 3) {
    System.out.println("alternatively");
} else
    System.out.println("else");
```

`else if` are two separated words

Comparison in Python

Name	Operator	Example
Equal	<code>==</code>	<code>if 2 == 1:</code>
Not Equal	<code>!=</code>	<code>if x != 4:</code>
Greater than	<code>></code> , <code>>=</code>	<code>if 2 > 3:</code>
Less than	<code><</code> , <code><=</code>	<code>if 2 < 3:</code>

Condition must be followed by
semicolon `:`

Comparison in Java

Name	Operator	Example
Equal	<code>==</code>	<code>if (2 == 1)</code>
Not Equal	<code>!=</code>	<code>if (x != 4)</code>
Greater than	<code>></code> , <code>>=</code>	<code>if (2 > 3)</code>
Less than	<code><</code> , <code><=</code>	<code>if (2 < 3)</code>

Condition must be enclosed by
parenthesis `()`

Logical Operator in Python

Name	Operator	Example
and	<code>and</code>	<code>if fat and tall:</code>
or	<code>or</code>	<code>if fat or tall:</code>
not	<code>not</code>	<code>if not tall:</code>

Logical Operator in Java

Name	Operator	Example
and	<code>&&</code>	<code>if (fat && tall)</code>
or	<code> </code>	<code>if (fat tall)</code>
not	<code>!</code>	<code>if (!tall)</code>

Loops in Python

```
while x < 10:  
    x = x + 1  
    print(x)
```

```
for x in range(1,10):  
    do_something()
```

Loops in Java

```
while (x < 10) {  
    x = x + 1;  
    System.out.println(x);  
}
```

```
for (int x = 0; x < 10; x++)  
    do_something();
```

List in Python

```
array = []  
array.append(1)  
array.append(10)  
i = 0  
j = 1  
array.append(array[i] + array[j])
```

Array in Java

```
int[] array = new int[3];  
array[0] = 1;  
array[1] = 10;  
int i = 0; int j = 1;  
array[2] = array[i] + array[j];
```

Function in Python

```
def function(param1, param2):  
    if (param1 > param2):  
        return 1  
    else:  
        return 2
```

A function always starts with `def`.
Return values are **weak type** and nullable.

Method in Java

```
public int method(int param1,  
                  int param2) {  
    if (param1 > param2)  
        return 1;  
    else  
        return 2;  
}
```

The **return type** of a Java method must be defined. A non-void method must have a return statement on every possible path.

Simple Program in Python

```
i = 9527

while i > 1:
    for j in range(2, i + 1):
        if i % j == 0:
            print(j)
            i = i / j
            break
```

Simple Program in Java



```
int i = 9527;

while (i > 1) {
    for (int j = 2; j <= i; j++) {
        if (i % j == 0) {
            System.out.println(j);
            i = i / j;
            break;
        }
    }
}
```

1. Java must have a class

- A complete Java program must include at least one class.
- Code are placed inside **methods** of a class.

```
System.out.println("Hello"); //does not work alone
```

```
public class Main {  
    public static void main(String[] arg) {  
        System.out.println("Hello"); //code placed inside method  
    }  
}
```


2. Java starts from public static void main

- All Java executable program must include a method called `public static void main`. All code starts there.

```
public class Main {  
    public static void main(String[] arg) {  
        System.out.println("Hello"); //Programme entry point  
    }  
    public static void hi(String[] arg) {  
        System.out.println("hi"); //would not go here  
    }  
}
```

3. Java needs to be compiled before runs

- The compilation procedure is transparent to you for most of the time.
- **Compile**: the process to convert source code (.java) to byte code (.class)

4. Running Java Byte code needs a JRE/JDK

- **JRE**: Java Run-time Environment (most PC installed that)
- **JDK**: Java Development Kits. Include JRE as well.

5. Java variable needs to be declared

- All variable needs to be declared before it can be used.
- Java is a **strong type** language. Each variable has a fixed type.

- Read flipped lecture notes (Quiz is coming~)
- Watch Video
- Install Java
- Attending the lab
 - May bring your laptop if you want.