

2015-05-21

Semidefinite Programming

Semidefinite Programming

Fin Bauer and Stefan Heidekrüger

21. Mai 2015

Semidefinite Programming

Fin Bauer and Stefan Heidekrüger

21. Mai 2015

Outline

- 1 Introduction
- 2 Some Theory
 - Duality
 - Optimality
- 3 Algorithms
 - Interior Points
- 4 Applications
 - Lovasz
 - Max Cut
 - Machine Learning

2015-05-21

Semidefinite Programming

└ Outline

- 1 Introduction
- 2 Some Theory
 - Duality
 - Optimality
- 3 Algorithms
 - Interior Points
- 4 Applications
 - Lovasz
 - Max Cut
 - Machine Learning

What Is Semidefinite Programming?

$$\begin{aligned} \min_X \quad & \langle C, X \rangle := \text{Tr}(CX) = \sum_{i=1}^n \sum_{j=1}^n C_{ij} X_{ij} \\ \text{s.t.} \quad & \langle A_i, X \rangle = b_i \\ & X \succeq 0 \end{aligned}$$

C, X symmetric $X \succeq 0$ positive semidefinite(s.d.p)

2015-05-21

Semidefinite Programming

└ Introduction

└ What Is Semidefinite Programming?

$$\begin{aligned} \min_X \quad & \langle C, X \rangle := \text{Tr}(CX) = \sum_{i=1}^n \sum_{j=1}^n C_{ij} X_{ij} \\ \text{s.t.} \quad & \langle A_i, X \rangle = b_i \\ & X \succeq 0 \end{aligned}$$

C, X symmetric $X \succeq 0$ positive semidefinite(s.d.p)

An Easy Example

$$C = \begin{pmatrix} 1 & 2 \\ 2 & 9 \end{pmatrix}, A_1 = \begin{pmatrix} 1 & 0 \\ 0 & 3 \end{pmatrix}, A_2 = \begin{pmatrix} 0 & 2 \\ 2 & 3 \end{pmatrix}, b_1 = 11, b_2 = 19$$

2015-05-21

Semidefinite Programming

└ Introduction

└ An Easy Example

$$C = \begin{pmatrix} 1 & 2 \\ 2 & 9 \end{pmatrix}, A_1 = \begin{pmatrix} 1 & 0 \\ 0 & 3 \end{pmatrix}, A_2 = \begin{pmatrix} 0 & 2 \\ 2 & 3 \end{pmatrix}, b_1 = 11, b_2 = 19$$

An Easy Example

$$C = \begin{pmatrix} 1 & 2 \\ 2 & 9 \end{pmatrix}, A_1 = \begin{pmatrix} 1 & 0 \\ 0 & 3 \end{pmatrix}, A_2 = \begin{pmatrix} 0 & 2 \\ 2 & 3 \end{pmatrix}, b_1 = 11, b_2 = 19$$

$$\begin{array}{ll} \min & x_{11} + 2x_{21} + 2x_{12} + 9x_{22} \\ \text{s.t.} & x_{11} + x_{22} = 11 \\ & 2x_{21} + 2x_{12} + 3x_{22} = 19 \\ & X = \begin{pmatrix} x_{11} & x_{12} \\ x_{21} & x_{22} \end{pmatrix} \succeq 0 \end{array}$$

2015-05-21

Semidefinite Programming

└ Introduction

└ An Easy Example

$$C = \begin{pmatrix} 1 & 2 \\ 2 & 9 \end{pmatrix}, A_1 = \begin{pmatrix} 1 & 0 \\ 0 & 3 \end{pmatrix}, A_2 = \begin{pmatrix} 0 & 2 \\ 2 & 3 \end{pmatrix}, b_1 = 11, b_2 = 19$$

$$\begin{array}{ll} \min & x_{11} + 2x_{21} + 2x_{12} + 9x_{22} \\ \text{s.t.} & x_{11} + x_{22} = 11 \\ & 2x_{21} + 2x_{12} + 3x_{22} = 19 \\ & X = \begin{pmatrix} x_{11} & x_{12} \\ x_{21} & x_{22} \end{pmatrix} \succeq 0 \end{array}$$

Problem Session:

Have I Ever Seen Semidefinite Programming Before?

Linear Programming

Linear Program

$$\begin{aligned} \min_x \quad & b_0^T x + c_0 \\ \text{s.t.} \quad & b_i^T x + c_i \leq 0, \quad i \text{ in } 1, \dots, n \\ & x \geq 0 \end{aligned}$$

Hint

Diagonal Matrix

Convex Quadratically Constrained Quadratic Programming

CQCQP

$$\begin{aligned} \min \quad & x^T A_0 x + b_0^T x + c_0 \\ \text{s.t.} \quad & x^T A_i x + b_i^T x + c_i \leq 0, \quad i \text{ in } 1, \dots, n \end{aligned}$$

Hint

Given $A_i = M_i^T M_i$
then $x^T A_i x + b_i^T x + c_i \leq 0$
$$\begin{pmatrix} I & M_i x \\ x^T M_i^T & -c_i - b_i^T x \end{pmatrix} \succeq 0$$

2015-05-21

Semidefinite Programming

Introduction

Problem Session:

Have I Ever Seen Semidefinite Programming Before?

Linear Programming

Linear Program

$$\begin{aligned} \min_x \quad & b_0^T x + c_0 \\ \text{s.t.} \quad & b_i^T x + c_i \leq 0, \quad i \text{ in } 1, \dots, n \\ & x \geq 0 \end{aligned}$$

Convex Quadratically Constrained Quadratic Programming

CQCQP

$$\begin{aligned} \min \quad & x^T A_0 x + b_0^T x + c_0 \\ \text{s.t.} \quad & x^T A_i x + b_i^T x + c_i \leq 0, \quad i \text{ in } 1, \dots, n \end{aligned}$$

Hint

Diagonal Matrix

Hint

Given $A_i = M_i^T M_i$
then $x^T A_i x + b_i^T x + c_i \leq 0$
$$\begin{pmatrix} I & M_i x \\ x^T M_i^T & -c_i - b_i^T x \end{pmatrix} \succeq 0$$

Problem Session:

What is modeled here and is it a SDP?

$$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (a_i - c)^T E (a_i - c) \leq 1 \quad \forall i \\ & (b_j - c)^T E (b_j - c) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^n \end{aligned}$$

2015-05-21

Semidefinite Programming

└ Introduction

└ Problem Session: What is modeled here and is it a SDP?

$$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (a_i - c)^T E (a_i - c) \leq 1 \quad \forall i \\ & (b_j - c)^T E (b_j - c) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^n \end{aligned}$$

Problem Session: Model Max-Cut

2015-05-21

Semidefinite Programming

└ Introduction

└ Problem Session:
Model Max-Cut

Problem Session: Lovasz

2015-05-21

- Semidefinite Programming
 - └ Introduction
 - └ Problem Session:
Lovasz

What's the Dual?

2015-05-21

Semidefinite Programming

└ Some Theory

└ Duality

└ What's the Dual?

Primal Problem in Standard Form

$$\inf_X \{ \text{Tr}(CX); \text{Tr}(A_i X) = b_i \ (i = 1, \dots, m), \ X \in \mathcal{S}_n^+ \} \quad (1)$$

Dual Problem in Standard Form

$$\sup_{y, S} \{ b^T y; \sum_{i=1}^m y_i A_i + S = C, \ S \in \mathcal{S}_n^+, y \in \mathbb{R}^m \} \quad (2)$$

Primal Problem in Standard Form

$$\inf_X \{ \text{Tr}(CX); \text{Tr}(A_i X) = b_i \ (i = 1, \dots, m), \ X \in \mathcal{S}_n^+ \} \quad (1)$$

Dual Problem in Standard Form

$$\sup_{y, S} \{ b^T y; \sum_{i=1}^m y_i A_i + S = C, \ S \in \mathcal{S}_n^+, y \in \mathbb{R}^m \} \quad (2)$$

Weak and Strong Duality

2015-05-21

Semidefinite Programming

└ Some Theory

└ Duality

└ Weak and Strong Duality

Example with Duality Gap

2015-05-21

Semidefinite Programming

└ Some Theory

└ Duality

└ Example with Duality Gap

When is the Solution Optimal?

2015-05-21

Semidefinite Programming

└ Some Theory

└ Optimality

└ When is the Solution Optimal?

Optimality Conditions

$$\begin{aligned} \text{Tr}(A_i X) &= b_i, \quad X \succeq 0, \quad i = 1, \dots, m \\ \sum_{i=1}^m y_i A_i + S &= C, \quad S \succeq 0 \\ XS &= 0 \end{aligned}$$

Optimality Conditions

$$\begin{aligned} \text{Tr}(A_i X) &= b_i, \quad X \succeq 0, \quad i = 1, \dots, m \\ \sum_{i=1}^m y_i A_i + S &= C, \quad S \succeq 0 \\ XS &= 0 \end{aligned}$$

bla

2015-05-21 Semidefinite Programming
└ Algorithms
└ Interior Points
└ bla

bla

2015-05-21 Semidefinite Programming
└ Applications
└ Lovasz
└ bla

What is MAX CUT?

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ What is MAX CUT?

Group presentation time.

$$\max \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_i y_j), \quad \text{s.t. } y_i \in \{1, -1\}$$

Group presentation time.

What is MAX CUT?

IQP Model

Problem (MC) should be on the board now.

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ What is MAX CUT?

IQP Model

Problem (MC) should be on the board now.

$$\max \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_i y_j), \quad s.t. y_i \in \{1, -1\}$$

An SDP-approximation algorithm (Goermans-Williamson)

Outline

- Relax (MC) into a QP (P)
- Find approximation bound of QP
- Show: equivalent SQP (SQ) to (P)
- Strong duality holds for (SQ) (ommitted)
- Solve SQP's dual in polynomial time

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ An SDP-approximation algorithm (Goermans-Williamson)

Outline

- Relax (MC) into a QP (P)
- Find approximation bound of QP
- Show: equivalent SQP (SQ) to (P)
- Strong duality holds for (SQ) (ommitted)
- Solve SQP's dual in polynomial time

- 1995
- Approx: 0.87856
- eq. algorithm already existed, but bound wasn't known.

QP Relaxation of (MC)

2015-05-21

Semidefinite Programming
└ Applications
└ Max Cut
└ QP Relaxation of (MC)

(P)

$$W_P^* := \max \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$$
$$s.t. \ v_i \in \mathbb{S}^n \quad \forall i \in V$$

relaxation gives upper bound

(P)

$$W_P^* := \max \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$$
$$s.t. \ v_i \in \mathbb{S}^n \quad \forall i \in V$$

A randomized algorithm using (P)

1. Solve (P) to get vectors v_i
2. Sample $r \sim \text{UNIFORM}(\mathbb{S}^n)$
3. Set $S := \{i | v_i^T r \geq 0\}$

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ A randomized algorithm using (P)

1. Solve (P) to get vectors v_i
2. Sample $r \sim \text{UNIFORM}(\mathbb{S}^n)$
3. Set $S := \{i | v_i^T r \geq 0\}$

A randomized algorithm using (P)

1. Solve (P) to get vectors v_i
2. Sample $r \sim \text{UNIFORM}(\mathbb{S}^n)$
3. Set $S := \{i \mid v_i^T r \geq 0\}$

For cut W obtained this way:

$$E[W] = \sum_{i < j} w_{ij} \frac{\arccos(v_i^T v_j)}{\pi}$$

2015-05-21

Semidefinite Programming

Applications

Max Cut

A randomized algorithm using (P)

1. Solve (P) to get vectors v_i
2. Sample $r \sim \text{UNIFORM}(\mathbb{S}^n)$
3. Set $S := \{i \mid v_i^T r \geq 0\}$

For cut W obtained this way:

$$E[W] = \sum_{i < j} w_{ij} \frac{\arccos(v_i^T v_j)}{\pi}$$

A bound given by $E[W]$

Theorem

$$E[W] \geq \alpha \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$$

with

$$\alpha := \min_{0 \leq \Theta \leq \pi} \frac{2}{\pi} \frac{\Theta}{1 - \cos \Theta} > .87856 \dots$$

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ A bound given by $E[W]$

Theorem

$$E[W] \geq \alpha \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$$

with

$$\alpha := \min_{0 \leq \Theta \leq \pi} \frac{2}{\pi} \frac{\Theta}{1 - \cos \Theta} > .87856 \dots$$

A bound given by $E[W]$

Theorem

$$E[W] \geq \alpha \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$$

with

$$\alpha := \min_{0 \leq \Theta \leq \pi} \frac{2}{\pi} \frac{\Theta}{1 - \cos \Theta} > .87856 \dots$$

Corollary

$$E[W] \geq \alpha W_P^* \geq \alpha W_{MC}^*$$

2015-05-21

Semidefinite Programming

Applications

Max Cut

— A bound given by $E[W]$

Theorem
$E[W] \geq \alpha \frac{1}{2} \sum_{i < j} w_{ij} (1 - v_i^T v_j)$
with
$\alpha := \min_{0 \leq \Theta \leq \pi} \frac{2}{\pi} \frac{\Theta}{1 - \cos \Theta} > .87856 \dots$
Corollary
$E[W] \geq \alpha W_P^* \geq \alpha W_{MC}^*$

SDP formulation of (P)

(SD)

$$\begin{aligned} W_P^* := \max \quad & \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_{ij}) \\ \text{s.t.} \quad & y_{ii} = 1 \quad \forall i \in V \\ & Y \text{ sym. pos. sem. def.} \end{aligned}$$

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ SDP formulation of (P)

(SD)

$$\begin{aligned} W_P^* := \max \quad & \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_{ij}) \\ \text{s.t.} \quad & y_{ii} = 1 \quad \forall i \in V \\ & Y \text{ sym. pos. sem. def.} \end{aligned}$$

SDP formulation of (P)

(SD)

$$\begin{aligned} W_P^* := \max & \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_{ij}) \\ \text{s.t. } & y_{ii} = 1 \quad \forall i \in V \\ & Y \text{ sym. pos. sem. def.} \end{aligned}$$

How is this an SDP? Rewrite the objective!

$$\begin{aligned} &= \frac{1}{4} \sum_{i \in V} \sum_{j \in V} w_{ij} (1 - y_{ij}) \\ &= \frac{1}{2} W_{tot} - \frac{1}{4} \langle W, Y \rangle \end{aligned}$$

2015-05-21

Semidefinite Programming

└ Applications

└ Max Cut

└ SDP formulation of (P)

(SD)

$$\begin{aligned} W_P^* := \max & \frac{1}{2} \sum_{i < j} w_{ij} (1 - y_{ij}) \\ \text{s.t. } & y_{ii} = 1 \quad \forall i \in V \\ & Y \text{ sym. pos. sem. def.} \end{aligned}$$

How is this an SDP? Rewrite the objective!

$$\begin{aligned} &= \frac{1}{4} \sum_{i \in V} \sum_{j \in V} w_{ij} (1 - y_{ij}) \\ &= \frac{1}{2} W_{tot} - \frac{1}{4} \langle W, Y \rangle \end{aligned}$$

Classification - Using SDP to tell two things apart (1)

Ellipsoid

$$\mathcal{E} = \{x \in \mathbb{R}^n; (x - c)^T E (x - c) \leq 1, E \text{ is p.s.d.}\}$$

First idea for SDP

$$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (a_i - c)^T E (a_i - c) \leq 1 \quad \forall i \\ & (b_j - c)^T E (b_j - c) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^n \end{aligned}$$

2015-05-21

Semidefinite Programming

Applications

Machine Learning

Classification - Using SDP to tell two things apart (1)

Ellipsoid
$\mathcal{E} = \{x \in \mathbb{R}^n; (x - c)^T E (x - c) \leq 1, E \text{ is p.s.d.}\}$
First idea for SDP
$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (a_i - c)^T E (a_i - c) \leq 1 \quad \forall i \\ & (b_j - c)^T E (b_j - c) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^n \end{aligned}$

Classification - Using SDP to tell two things apart (2)

$$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (1, a_i)^T \bar{E} (1, a_i) \leq 1 \quad \forall i \\ & (1, b_j)^T \bar{E} (1, b_j) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^{n+1} \end{aligned}$$

2015-05-21

Semidefinite Programming

└ Applications

└ Machine Learning

└ Classification - Using SDP to tell two things apart (2)

$$\begin{aligned} \max \quad & \rho \\ \text{s.t.} \quad & (1, a_i)^T \bar{E} (1, a_i) \leq 1 \quad \forall i \\ & (1, b_j)^T \bar{E} (1, b_j) \geq \rho^2 \quad \forall j \\ & E \in \mathbb{S}_+^{n+1} \end{aligned}$$