

1 **Three-dimensional data of wirecut surface scans
2 under the confocal microscope (110 character
3 maximum, inc. spaces)**

4 **Yuhang Lin^{1,2} and Heike Hofmann^{2,3}**

5 ¹Iowa State University, Department of Statistics, Ames,

6 Center for Statistics and Applications in Forensic Evidence (CSAFE), Iowa State University, Ames,

7 ³University of Nebraska-Lincoln, Department of Statistics, Lincoln,

8 *corresponding author(s): Yuhang Lin (yhlins@iastate.edu) **it.corresponding returns nothing**

9 *corresponding author(s): Heike Hofmann (hhofmann4@unl.edu) **it.corresponding returns nothing**

10 **ABSTRACT**

Update later

Wire cut data is important in forensic investigations but lacks a systematic way of analyzing the data. We created a data set of 120 scans of aluminum wire cut in x3p format, using 5 wire cutters and 3 locations along the 4 blades, with 2 replicates for each combination. A systematic pipeline with multiple analysis plots was developed to analyze the data and draw conclusions based on numerical measures.

(maximum 170 words) This is a manuscript template for Data Descriptor submissions to *Scientific Data* (<http://www.nature.com/scientificdata>). The abstract must be no longer than 170 words, and should succinctly describe the study, the assay(s) performed, the resulting data, and the reuse potential, but should not make any claims regarding new scientific findings. No references are allowed in this section.

Please note: Abbreviations should be introduced at the first mention in the main text no abbreviations lists or tables should be included. Structure of the main text is provided below.

14 **Background & Summary**

15 motivation, context, overview of the study design, overview of files created (x3ps and derivatives)

16 XXX This section needs a lot more detail - as per instructions, we need:

17 **overview of the study design: create dataset, manual alignment**

18 **overview of files created (table?):**

- 19 • x3p files from scans: format, explanations, link to sections
- 20 • derivatives from manual processing: profiles, signals
- 21 • aligned signals
- 22 • meta csv

23 **context of previous work and literature**

24 **motivation for the creation of the dataset**

25 Wire cut data is a type of forensic tool mark data used to identify the source of a wire cutter based on the striations left
26 on the surface. There have been cases where the evidence and testimony on wire cut evidence played a crucial role in the
27 criminal investigation and conviction of a defendant. However, there is a lack of a standardized method to analyze it except for
28 visual comparison. Here, we provide a data set of 120 scans of aluminum wire cut in x3p format, and we conduct a technical
29 validation to introduce a systematic pipeline for analyzing these types of data based on numerical measures. We hope this
30 pipeline developed using this data set can be further generalized and applied to real crime scenes to help investigators draw
31 conclusions based on real wire cut data.

32 (unlimited length) An overview of the study design, the assay(s) performed, and the created data, including any background
33 information needed to put this study in the context of previous work and the literature. The section should also briefly outline

34 the broader goals that motivated the creation of this dataset and the potential reuse value. We also encourage authors to include
35 a figure that provides a schematic overview of the study and assay(s) design. The Background & Summary should not include
36 subheadings. This section and the other main body sections of the manuscript should include citations to the literature as
37 needed.

38 Methods

39 from cutting wires to how to alignment

40 full descriptions of the experimental design, data acquisition assays, and any computational processing

41 In this study, aluminum wire was used to create an optimal scenario where the most amount of information could be
42 transferred from the tool to the substrate, despite the wire in some real cases being made of lead. XXX emphasize the
43 hardness/softness of the wire - it keeps marks, but is relatively easy to bend and non-toxic The aluminum wire used was 16
44 Gauge/1.5 mm, anodized.

45 In order to cut the wire, 4-inch pieces were unspooled and cut using Kaiweets wire cutters, model KWS-105, as shown in
46 Figure 1(a), for 1 blade location, either inner, middle, or outer, which gives us 1 replicate. Each piece was then cut into half
47 to create 2-inch pieces for each side, AB and CD, with a sharpie line marking the cut ends, giving us 4 samples. Here, we are
48 showing AB sides only in Figure 1(b) (need a different tent figure), and the CD sides are similar from the other side of the cut,
49 with the back of A being C and the back of B being D. Both AB and CD sides form tent structures on the tips of the wire, and
50 we can separate each side of the tent into 2 pieces along the bending position, resulting in 8 scans. We repeated this process
51 for all 3 locations along the blade and 5 wire cutters, with 2 replicates for each tool-edge-location combination, resulting
52 in 120 scans. Each piece was labeled with the naming conventions, T(ool) 1/2/3/4/5 (Edge) A/B/C/D W(ire) - L(ocation)
53 I(nner)/M(iddle)/O(uter) - R(epetition) 1/2, with T1AW-LI-R1 being the piece cut by tool 1 on the A edge at the inner location
54 for the first repetition.

55 no, we can't use the website as a place for more detailed procedures. This paper is the detailed procedure.

56 A more detailed procedure, including standard scanning protocols for the confocal microscope in Figure 1(c) (need an
57 extra pic of the very tip), can be found in the [README of the GitHub repository heike/Wirecuts](#) (High-res pics needed
58 in the README). The scanned surfaces are saved in a resolution of $0.645\mu m \times 0.645\mu m$ per square pixel in an x3p file
59 format.

60 XXX figure 1 - generally, zoom into these images - we do not want to have a hand in the image, nor a view of the crafting
61 aluminum :) - what are the exact rules on visuals in Scientific Data ? XXX

62 fix below

63 We also conduct numerical comparisons between 2 replicates made by the same side of the same tool at the same location.
64 For example, we compare T1AW-LI-R1 to T1AW-LI-R2, T1CW-LI-R1 to T1CW-LI-R2, and so on. That is comparing each
65 row in Figure 2. The comparison is done by

- 66 1. manually extracting profiles from scans,
- 67 2. obtaining the filtered signals from scans,
- 68 3. aligning signals and computing the cross-correlation function (CCF) values.

69 Extract profiles

70 A representative function with the most information is considered as a signal for one scan, which can be used for comparison
71 later. To obtain this function, we first need a profile of the scan, which is a sequence of values along a user-drawn line on
72 the surface. The profile should capture most features of the scan, and be orthogonal to the striation marks of the scan, which
73 are formed by ups and downs of grooves. So, we draw the line across the wide region of the scan to maximize the feature
74 captured, as shown in dark blue in Figure 3(a). We can then investigate the values under this profile line. The profile function
75 is along the line is plotted in Figure 3(b).

76 Filtered signals

77 With the profile extracted, we can then obtain the signal. Two Gaussian filters are applied to these resulting profiles. In
78 particular, we first used a large low-pass filter with bandwidths of 400 microns to remove large trend, as it can overwhelm the
79 signals, and then used a small high-pass filter of 40 microns to average across noise and remove spikes, as shown in Figure
80 3(c). @clevelandLocalRegressionModels1992 ? (add reference: W. S. Cleveland, E. Grosse and W. M. Shyu (1992) Local
81 regression models. Chapter 8 of Statistical Models in S eds J.M. Chambers and T.J. Hastie, Wadsworth & Brooks/Cole.).
82 Finally, the extreme tail values are removed.





Figure 1. (a) A Kaiweets wire cutter of model KWS-105 was used to cut the wire. (b) A tent structure created by blade AB. After separating 2 tent structures by the connecting position, we obtained 2 samples - 1 sample from blade A and B. (c) A confocal microscope was used to scan the wire surfaces.

83 Align signals and compute the cross-correlation function (CCF) values

84 Signals extracted from different scans can be put together for comparison, and we maximize the overlapping region of the
 85 signals by aligning them. We know that signals from two replicates with the same tool-edge-location combination should
 86 yield similar signals as in the first and second column of Figure 4, which will give alignments of massive overlapping and high
 87 CCF values close to 1. The alignments and values we got in the rightmost column of Figure 4 fulfill our expectations.

88 (unlimited length) The Methods should include detailed text describing any steps or procedures used in producing the data,
 89 including full descriptions of the experimental design, data acquisition assays, and any computational processing (e.g. normalization,
 90 image feature extraction). See the detailed section in our submission guidelines for advice on writing a transparent
 91 and reproducible methods section. Related methods should be grouped under corresponding subheadings where possible, and
 92 methods should be described in enough detail to allow other researchers to interpret and repeat, if required, the full study.
 93 Specific data outputs should be explicitly referenced via data citation (see Data Records and Citing Data, below).

94 Authors should cite previous descriptions of the methods under use, but ideally the method descriptions should be complete
 95 enough for others to understand and reproduce the methods and processing steps without referring to associated publications.
 96 There is no limit to the length of the Methods section. Subheadings should not be numbered.

97 Authors should review the transparent methods checklist below, and ensure that their manuscript complies with any relevant
 98 points. Authors are also encouraged to search FAIRsharing.org for community reporting standards that may be relevant
 99 to their specific data-type.

100 Transparent Methods Checklist

- 101 • Materials & reagents: Identify commercial suppliers of reagents, instrumentation or kits, when the source is critical to
 102 the outcome of the experiments. Declare any restrictions on the availability of unique materials (more information here).
 103 Provide catalogue or clone numbers for all antibodies (if available). For primary antibodies, provide proof of validation

104 for the relevant species and applications.

- 105 • Exclusion criteria: If any data or samples were excluded, explain the exclusion criteria and state in the methods whether
the criteria were established before the study was conducted.
- 106
- 107 • Randomization & blinding: For any studies that involve assigning samples, animals or participants into different groups:
108 State clearly whether randomization methods were used. If randomization was not employed, this should be clearly
109 stated. State clearly whether blinding was employed during data collection. If blinding was not employed, this should
110 be clearly stated.
- 111
- 112 • Animal & human studies (full journal policies here): Experiments involving human participants must identify the
113 committee approving the experiments, and include a statement confirming that informed consent was obtained from all
114 participants. Studies employing nonhuman animals should ensure that methods descriptions comply with the ARRIVE
checklist.
- 115
- 116 • Cell lines: For each eukaryotic cell line used, state the source and whether the cell line has been authenticated or
117 otherwise tested for integrity. If any commonly misidentified cell lines were used (see ICLAC or NCBI Biosample),
118 justify their use. Report whether the cell lines were tested for mycoplasma contamination.
- 119
- Chemistry & materials science: Manuscripts describing chemical syntheses, or characterizing new chemicals or materials
should refer to the guidance at Nature Chemistry.

120 Data Records

121 The complete data set is available on the ISU DataShare repository at <https://iastate.figshare.com/>, which is public and open
122 access for every interested researcher. The data set consists of 120 scans in the x3p file format with the naming convention
123 as described before. (Explain the x3p header info?)

124 (unlimited length) The Data Records section should be used to explain each data record associated with this work, in-
125 cluding the repository where this information is stored, and to provide an overview of the data files and their formats. Each
126 external data record should be cited numerically in the text of this section, for example ?, and included in the main reference
127 list as described below. A data citation should also be placed in the subsection of the Methods containing the data-collection
128 or analytical procedure(s) used to derive the corresponding record. Providing a direct link to the dataset may also be helpful
129 to readers (<https://doi.org/10.6084/m9.figshare.853801>).

130 Tables should be used to support the data records, and should clearly indicate the samples and subjects (study inputs), their
131 provenance, and the experimental manipulations performed on each (please see 'Tables' below). They should also specify the
132 data output resulting from each data-collection or analytical step, should these form part of the archived record.

133 Technical Validation

134 a picture of alignment with ccf from different sources to show if different source, our evaluation returns small ccf, which
135 matches what we thought.

136 For the data collection process, two team members did the cutting and labeling together, then one person did the scanning
137 and named according to the naming convention above. The scanning was done in a specific order to ensure consistency across
138 all scans. The data was saved in a consistent format to ensure they could be easily accessed and analyzed. A third person then
139 checked the data to ensure that the data was consistent in naming and accurate.

140 again - the website is not the right place for the validation - instead, move parts from the website here.

141 For the validation of the scans and their processing we investigate the correlation scores of pair-wise aligned signals. For
142 signals from scans of wires cut with a different tool, we would expect a low correlation score. Large scores between signals
143 are indicative of being made by the same tool. Show boxplots and roc curve.

144 For validation of all other tools and locations of scan replicates, see the detailed report.

145 (unlimited length) This section presents any experiments or analyses that are needed to support the technical quality of
146 the dataset. This section may be supported by figures and tables, as needed. This is a required section; authors must present
147 information justifying the reliability of their data.

- 148 • Measurement of data quality?

- 149 – Numeric measurements / tests: ?

- 150 – Visualizations: ?
- 151 – Check with existing data: ?
- 152 – Questionable / slur procedures:
- 153 * **AidDatas Geospatial Global Chinese Development Finance Dataset:** Second, all data collected is reviewed by at least two individuals. Although this is not a double-blind review procedure, the use of satellite imagery to verify project locations results in far less uncertainty when compared to previous approaches to geocoding where locations were selected entirely based on text descriptions.
 - 154
 - 155
 - 156
 - 157 * **A large open access dataset of brain metastasis 3D segmentations on MRI with clinical and imaging information:** A medical student (D.R.) double checked and adjusted the revised NIfTI segmentation masks and manually counted the number of lesions with contrast-enhancement, necrosis, and peritumoral edema for each patient.
 - 158
 - 159
 - 160
 - 161 * **Time series of freshwater macroinvertebrate abundances and site characteristics of European streams and rivers:** Technical validation of the TREAM dataset was achieved through exclusion of time series data that did not match our inclusion criteria and data standardisation steps (outlined in Methods above). Any noted issues that did not adhere to the outlined standardisation within the datasets from the 41 independent projects included in this dataset were checked with data providers and corrected or removed when standardisation was not achievable (e.g., when collection methods changed over the course of the time series).
 - 162
 - 163
 - 164
 - 165
 - 166
 - 167 * **3D surgical instrument collection for computer vision and extended reality:** The main issue...Since we store our models in a standard format (STL), they are compatible with a large variety of visualisation and processing software.
 - 168
 - 169
 - 170 * **Three-dimensional reconstruction of high latitude bamboo coral via X-ray microfocus Computed Tomography :** Regular quality assurance inspections are carried out on the μ -CT scanner to verify its metrological and geometrical (alignments) accuracy for conducting the scans. The geometry of source to object and source to detector distances are verified whenever there is any significant physical interaction with the source such as re-alignment, change of filament, or source anode change. This calibration process involves scanning a specially designed phantom known as an hourglass36, which consists of three pairs of high-sphericity spheres. The sphere sizes are as follows: two spheres with a diameter of 3.000 mm, two spheres with a diameter of 6.000 mm, and two spheres with a diameter of 9.525 mm, and each sphere is kept in contact with its size-counterpart. By using this phantom, it becomes possible to accurately determine a known distance, specifically the centre-to-centre distance of the spheres, in a threshold-independent manner. If the measured distance deviates beyond the acceptable limits of metrological accuracy, the systems calibration parameters are adjusted to ensure agreement between the measured distance and the actual distance.
 - 171
 - 172
 - 173
 - 174
 - 175
 - 176
 - 177
 - 178
 - 179
 - 180
 - 181

182 Usage Notes

183 The R package `x3ptools` (available from CRAN) supports working with files in `x3p` format.

184 Sample scripts in R for processing scans from `x3p` format to their signal are available from ... [github](#).

185 Further analysis can be conducted with the GitHub R package `wire` and the GitHub R shiny app `wireShiny` ([citation?](#)). We already conduct between-replicate comparisons in the technical validation section, and we can also conduct across-replicate comparisons to establish error rates threshold and produce other analysis plots.

186 Suppose we put the CCF values in a tilemap with different tool, location and edge combinations. In that case, we expect only the diagonal to have high CCF values, close to 1 and marked as orange in the tilemap, as the diagonal represents the same source, and the rest of the matrix to have low CCF values, close to 0 and marked as gray. In Figure 5, the behavior is consistent with our expectation overall, except for some rare cases with tool 5 edge D, which is caused by [?????](#). We also put the resulting CCFs in the boxplot, as in Figure 6. We can see that the CCF values for the same sources are close to 1, while the CCF values for different sources are much lower than expected. This difference can be used to establish a threshold for CCF and help us draw conclusions about the similarity between wire cut scans numerically, which can be used in real crime scenes. The density plot in Figure 7 shows the distribution of the CCF values with the same sources and different sources. The overlapping points between the tails of these two distributions can be a rough threshold. Furthermore, the receiver operating characteristic (ROC) curve in Figure 8 shows the sensitivity / true positive rate against the false positive rate (FPR) (1 - specificity). The curve is very close to the upper left corner, which is excellent for classification and drawing conclusion. It gives us a true threshold of 0.589 to control the FPR to be less than 0.05 with false negative rate (FNR) to be 0, ([false positive rate \(FPR\) / false discovery](#)

200 rate (FDR) -> define the H0 or call it false identification rate (FIR)????, and 0.658 to control the FPR to be less than 0.01, with
201 FNR to be 0.02.

202 (unlimited length) The Usage Notes should contain brief instructions to assist other researchers with reuse of the data.
203 This may include discussion of software packages that are suitable for analysing the assay data files, suggested downstream
204 processing steps (e.g. normalization, etc.), or tips for integrating or comparing the data records with other datasets. Authors
205 are encouraged to provide code, programs or data-processing workflows if they may help others understand or use the data.
206 Please see our code availability policy for advice on supplying custom code alongside Data Descriptor manuscripts.

207 For studies involving privacy or safety controls on public access to the data, this section should describe in detail these
208 controls, including how authors can apply to access the data, what criteria will be used to determine who may access the data,
209 and any limitations on data use.

210 **Code availability**

211 **table of code-manual?**

212 The data set can be easily accessed with the CRAN R package `x3ptools`. Further analysis can be conducted with the
213 GitHub R package `wire` and the GitHub R shiny app `wireShiny` ([citation](#)) ([again????](#)).

214 For all studies using custom code in the generation or processing of datasets, a statement must be included under the heading
215 "Code availability", indicating whether and how the code can be accessed, including any restrictions to access. This section
216 should also include information on the versions of any software used, if relevant, and any specific variables or parameters used
217 to generate, test, or process the current dataset.

218 **1 End of Body**

219 **(Note that the bibliography style and the name of the bib-file are hard coded in the template file right now.)**

220 LaTeX formats citations and references automatically using the bibliography records in your .bib file, which you can edit via
221 the project menu. Use the cite command for an inline citation, e.g. ?????. For data citations of datasets uploaded to e.g. `figshare`,
222 please use the `howpublished` option in the bib entry to specify the platform and the link, as in the `Hao:gidmaps:2014`
223 example in the sample bibliography file. For journal articles, DOIs should be included for works in press that do not yet
224 have volume or page numbers. For other journal articles, DOIs should be included uniformly for all articles or not at all. We
225 recommend that you encode all DOIs in your bibtex database as full URLs, e.g. <https://doi.org/10.1007/s12110-009-9068-2>.

226 **Acknowledgements**

227 Acknowledgements should be brief, and should not include thanks to anonymous referees and editors, or effusive comments.
228 Grant or contribution numbers may be acknowledged.

229 **Author contributions statement**

230 Y.L. did all of the work, H.H. made him do the work. But seriously, this paper is the one where we need to cite everybody:
231 Eden Amin, Curtis Mosher, Jeff Salyards. Alicia? Must include all authors, identified by initials, for example: A.A. conceived
232 the experiment(s), A.A. and B.A. conducted the experiment(s), C.A. and D.A. analysed the results. All authors reviewed the
233 manuscript.

234 **Competing interests**

235 (mandatory statement)

236 The corresponding author is responsible for providing a [competing interests statement](#) on behalf of all authors of the paper.
237 This statement must be included in the submitted article file. H.H. is a technical advisor to AFTE (Association of Firearms and
238 Toolmarks Examiners), fellow of the ASA (American Statistical Association), and committee member of the ASA Forensic
239 Science Committee. H.H. has testified as court witness on behalf of judge April Neubauer, NY State Supreme Court Criminal
240 Term in New York City.

241 **Figures & Tables**

242 Figures, tables, and their legends, should be included at the end of the document. Figures and tables can be referenced in
243 [LATEX](#) using the `ref` command, e.g. Figure 9 and Table 1.

244 Authors are encouraged to provide one or more tables that provide basic information on the main inputs to the study
245 (e.g. samples, participants, or information sources) and the main data outputs of the study. Tables in the manuscript should

246 generally not be used to present primary data (i.e. measurements). Tables containing primary data should be submitted to an
247 appropriate data repository.

248 Tables may be provided within the L^AT_EX document or as separate files (tab-delimited text or Excel files). Legends, where
249 needed, should be included here. Generally, a Data Descriptor should have fewer than ten Tables, but more may be allowed
250 when needed. Tables may be of any size, but only Tables which fit onto a single printed page will be included in the PDF
251 version of the article (up to a maximum of three).

252 Due to typesetting constraints, tables that do not fit onto a single A4 page cannot be included in the PDF version of the
253 article and will be made available in the online version only. Any such tables must be labelled in the text as Online-only tables
254 and numbered separately from the main table list e.g. Table 1, Table 2, Online-only Table 1 etc.


Condition	n	p
A	5	0.1
B	10	0.01

Table 1. Legend (350 words max). Example legend text.

Edge A



Edge C



Edge B



Edge D



Figure 2. Scans from different sides of tool 1 at the inner location.




Figure 3. (a) A profile line in dark blue was drawn across the striations of the scan. (b) The profile function extracted along the profile line in (a). (c) The raw signal in light blue is obtained by using the low-pass filter on the profile function in (b) and the filtered signal is obtained by using the high-pass filter on the raw signal.




Figure 4. The first and second columns show the signals extracted from Figure 2, and the third column shows the alignments and CCF values between pairs of signals.



Figure 5. The tilemap shows signals from the same source have CCFs close to 1.




Figure 6. The boxplot shows that signals from the same sources have higher CCFs than those from different sources.




Figure 7. The density plot shows tails of distributions overlap, which can be used as a rough threshold for drawing conclusions.




Figure 8. The ROC curve is bending very close to the upper left corner, which means excellent in classification and drawing conclusions.




Figure 9. Legend (350 words max). Example legend text.