

1 **Three-dimensional data of wirecut surface scans
2 under the confocal microscope (110 character
3 maximum, inc. spaces)**

4 **Yuhang Lin^{1,2} and Heike Hofmann^{2,3}**

5 ¹Iowa State University, Department of Statistics, Ames,

6 Center for Statistics and Applications in Forensic Evidence (CSAFE), Iowa State University, Ames,

7 ³University of Nebraska-Lincoln, Department of Statistics, Lincoln,

8 *corresponding author(s): Yuhang Lin (yuhanglin@iastate.edu) **it.corresponding returns nothing**

9 *corresponding author(s): Heike Hofmann (hhofmann4@unl.edu) **it.corresponding returns nothing**

10 **ABSTRACT**

Update later

Wire cut data is important in forensic investigations but lacks a systematic way of analyzing the data. We created a data set of 120 scans of aluminum wire cut in x3p format, using 5 wire cutters and 3 locations along the 4 blades, with 2 replicates for each combination. A systematic pipeline with multiple analysis plots was developed to analyze the data and draw conclusions based on numerical measures.

(maximum 170 words) This is a manuscript template for Data Descriptor submissions to *Scientific Data* (<http://www.nature.com/scientificdata>). The abstract must be no longer than 170 words, and should succinctly describe the study, the assay(s) performed, the resulting data, and the reuse potential, but should not make any claims regarding new scientific findings. No references are allowed in this section.

12 Please note: Abbreviations should be introduced at the first mention in the main text no abbreviations lists or tables should be
13 included. Structure of the main text is provided below.

14 **Background & Summary**

15 **XXX This section needs a lot more detail - as per instructions, we need:**

16 **overview of the study design: create dataset, manual alignment**

17 **overview of files created (table?):**

- 18 • x3p files from scans: format, explanations, link to sections
- 19 • derivatives from manual processing: profiles, signals
- 20 • aligned signals
- 21 • meta csv

22 **context of previous work and literature**

23 **motivation for the creation of the dataset**

24 Wire cut data is a type of forensic tool mark data used to identify the source of a wire cutter based on the striations left on
25 the surface. There have been cases where the evidence and testimony on wire cut evidence played a crucial role in the criminal
26 investigation and conviction of a defendant. However, there is a lack of a standardized method to analyze it except for visual
27 comparison. **...literature review and motivation...** Here, we provide a data set with multiple files in our study, see Table 1.

Table 1. Overview of the whole data set.

Description	Section
-------------	---------

Raw data

x3p files metadata	120 scans of aluminum wire cut in x3p format metadata of the scans in 1 CSV	Cutting wires Cutting wires
Manually processed derivatives		
profiles	profiles extracted from scans in 120 CSVs	Extract profiles
Computational processed derivatives		
signals	signals filtered from profiles in 1 CSV	Filtered signals
aligned signals	pictures of pairwise aligned signals from same sources in PNGs	Align signals
CCF values	CCF values of all pairwise aligned signals in 1 CSV	Align signals

28 breakable table, cannot cross-reference inside table

29 For the reproducibility of all our data and alignment results, we introduce in details in (cross-reference not working)
30 how we cut the wire and collect the 120 scans with 5 tools on 3 locations, in how we extract profiles from the scans, in
31 how we filter signals from the profiles, in how we align signals from different scans, and optimize the alignment with the
32 cross-correlation function (CCF) values. Then, a technical validation was conducted to further compare signals from different
33 sources also match our assumption. We hope this pipeline developed using this data set can be further generalized and applied
34 to real crime scenes to help investigators draw conclusions based on real wire cut data.

35 (unlimited length) An overview of the study design, the assay(s) performed, and the created data, including any background
36 information needed to put this study in the context of previous work and the literature. The section should also briefly outline
37 the broader goals that motivated the creation of this dataset and the potential reuse value. We also encourage authors to include
38 a figure that provides a schematic overview of the study and assay(s) design. The Background & Summary should not include
39 subheadings. This section and the other main body sections of the manuscript should include citations to the literature as
40 needed.

41 Methods

42 full descriptions of the experimental design, data acquisition assays, and any computational processing

43 In this study, aluminum wire was used to create an optimal scenario where the most amount of information could be
44 transferred from the tool to the substrate, despite the wire in some real cases being made of lead. The physical property of
45 aluminium wire make it an excellent candidate for keeping marks while being relatively easy to bend and non-toxic.

46 Cutting wires

47 The aluminum wire used was 16 Gauge/1.5 mm, anodized. In order to cut the wire, 4-inch pieces were unspooled and cut using
48 Kaiweets wire cutters, model KWS-105, as shown in Figure 1(a), for 1 blade location, either inner, middle, or outer, which
49 gives us 1 replicate. Each piece was then cut into half to create 2-inch pieces for each side, AB and CD, with a sharpie line
50 marking the cut ends, giving us 4 samples. Here, we are showing AB sides only in Figure 1(b) (need a different tent figure),
51 and the CD sides are similar from the other side of the cut, with the back of A being C and the back of B being D. Both AB and
52 CD sides form tent structures on the tips of the wire, and we can separate each side of the tent into 2 pieces along the bending
53 position, resulting in 8 scans. We repeated this process for all 3 locations along the blade and 5 wire cutters, with 2 replicates
54 for each tool-edge-location combination, resulting in 120 scans. Each piece was labeled with the naming conventions, T(tool)
55 1/2/3/4/5 (Edge) A/B/C/D W(ire) - L(ocation) I(nner)/M(iddle)/O(uter) - R(epetition) 1/2, with T1AW-LI-R1 being the piece
56 cut by tool 1 on the A edge at the inner location for the first repetition. Then, we can use the standard scanning protocols for
57 the confocal microscope, shown in Figure 1(c) (need an extra pic of the very tip), to scan the wire tip surfaces. The scanned
58 surfaces are saved in a resolution of $0.645\mu m \times 0.645\mu m$ per square pixel in an x3p file format.

59 XXX figure 1 - generally, zoom into these images - we do not want to have a hand in the image, nor a view of the
60 crafting aluminum :) - what are the exact rules on visuals in Scientific Data ? XXX hard to put the full requirements here, see
61 <https://www.nature.com/sdata/publish/submission-guidelines#figures>

62 put into quarto layout with (a) (b) (c) on the top left, no tent, add blade C & D

63 Extract profiles

64 Numerical comparisons between 2 replicates cannot be done directly on the x3p files. We need to extract representative
65 functions from the scans first. A representative function with the most information is considered as a signal for one scan,






Figure 1. (a) A Kaiweets wire cutter of model KWS-105 was used to cut the wire. (b) A tent structure created by blade AB. After separating 2 tent structures by the connecting position, we obtained 2 samples - 1 sample from blade A and B. (c) A confocal microscope was used to scan the wire surfaces.

which can be used for comparison later. To obtain this function, we first need a profile of the scan, which is a sequence of values along a user-drawn line on the surface. The profile should capture most features of the scan, and be orthogonal to the striation marks of the scan, which are formed by ups and downs of grooves. So, we draw the line across the wide region of the scan to maximize the feature captured, as shown in dark blue in Figure 2(a). We can then investigate the values under this profile line. The profile function is along the line is plotted in Figure 2(b).

71 **Filtered signals**

With the profile extracted, we can then obtain the signal. Two Gaussian filters are applied to these resulting profiles. In particular, we first used a large low-pass filter with bandwidths of 400 microns to remove large trend, as it can overwhelm the signals, and then used a small high-pass filter of 40 microns to average across noise and remove spikes, as shown in Figure 2(c). [@clevelandLocalRegressionModels1992 ?](#) (add reference: W. S. Cleveland, E. Grosse and W. M. Shyu (1992) Local regression models. Chapter 8 of Statistical Models in S eds J.M. Chambers and T.J. Hastie, Wadsworth & Brooks/Cole.). Finally, the extreme tail values are removed.

78 **Align signals**

Signals extracted from different scans can be put together for comparison, and we maximize the cross-correlation function (CCF) values between the signals to numerically find the best alignment. For example, we compare T1AW-LI-R1 to T1AW-LI-R2, T1CW-LI-R1 to T1CW-LI-R2, and so on. That is comparing each row in Figure 3. We know that signals from two replicates with the same tool-edge-location combination should yield similar signals as in the first and second column of Figure 4, which will give alignments of massive overlapping and high CCF values close to 1. The alignments and values we got in the rightmost column of Figure 4 fulfill our expectations.

(unlimited length) The Methods should include detailed text describing any steps or procedures used in producing the data,

86 including full descriptions of the experimental design, data acquisition assays, and any computational processing (e.g. normalization,
87 image feature extraction). See the detailed section in our submission guidelines for advice on writing a transparent
88 and reproducible methods section. Related methods should be grouped under corresponding subheadings where possible, and
89 methods should be described in enough detail to allow other researchers to interpret and repeat, if required, the full study.
90 Specific data outputs should be explicitly referenced via data citation (see Data Records and Citing Data, below).

91 Authors should cite previous descriptions of the methods under use, but ideally the method descriptions should be complete
92 enough for others to understand and reproduce the methods and processing steps without referring to associated publications.
93 There is no limit to the length of the Methods section. Subheadings should not be numbered.

94 Authors should review the transparent methods checklist below, and ensure that their manuscript complies with any relevant
95 points. Authors are also encouraged to search FAIRsharing.org for community reporting standards that may be relevant
96 to their specific data-type.

97 Transparent Methods Checklist

- 98 • Materials & reagents: Identify commercial suppliers of reagents, instrumentation or kits, when the source is critical to
99 the outcome of the experiments. Declare any restrictions on the availability of unique materials (more information here).
100 Provide catalogue or clone numbers for all antibodies (if available). For primary antibodies, provide proof of validation
101 for the relevant species and applications.
- 102 • Exclusion criteria: If any data or samples were excluded, explain the exclusion criteria and state in the methods whether
103 the criteria were established before the study was conducted.
- 104 • Randomization & blinding: For any studies that involve assigning samples, animals or participants into different groups:
105 State clearly whether randomization methods were used. If randomization was not employed, this should be clearly
106 stated. State clearly whether blinding was employed during data collection. If blinding was not employed, this should
107 be clearly stated.
- 108 • Animal & human studies (full journal policies here): Experiments involving human participants must identify the
109 committee approving the experiments, and include a statement confirming that informed consent was obtained from all
110 participants. Studies employing nonhuman animals should ensure that methods descriptions comply with the ARRIVE
111 checklist.
- 112 • Cell lines: For each eukaryotic cell line used, state the source and whether the cell line has been authenticated or
113 otherwise tested for integrity. If any commonly misidentified cell lines were used (see ICLAC or NCBI Biosample),
114 justify their use. Report whether the cell lines were tested for mycoplasma contamination.
- 115 • Chemistry & materials science: Manuscripts describing chemical syntheses, or characterizing new chemicals or materi-
116 als should refer to the guidance at Nature Chemistry.

117 Data Records

118 The complete data set is available on the ISU DataShare repository at <https://iastate.figshare.com/>, which is public and open
119 access for every interested researcher. The data set consists of 120 scans in the x3p file format with the naming convention
120 as described before. (Explain the x3p header info?)

121 (unlimited length) The Data Records section should be used to explain each data record associated with this work, in-
122 cluding the repository where this information is stored, and to provide an overview of the data files and their formats. Each
123 external data record should be cited numerically in the text of this section, for example ?, and included in the main reference
124 list as described below. A data citation should also be placed in the subsection of the Methods containing the data-collection
125 or analytical procedure(s) used to derive the corresponding record. Providing a direct link to the dataset may also be helpful
126 to readers (<https://doi.org/10.6084/m9.figshare.853801>).

127 Tables should be used to support the data records, and should clearly indicate the samples and subjects (study inputs), their
128 provenance, and the experimental manipulations performed on each (please see 'Tables' below). They should also specify the
129 data output resulting from each data-collection or analytical step, should these form part of the archived record.

130 Technical Validation

131 a picture of alignment with ccf from different sources to show if different source, our evaluation returns small ccf, which
132 matches what we thought.

133 For the data collection process, two team members did the cutting and labeling together, then one person did the scanning
134 and named according to the naming convention above. The scanning was done in a specific order to ensure consistency across
135 all scans. The data was saved in a consistent format to ensure they could be easily accessed and analyzed. A third person then
136 checked the data to ensure that the data was consistent in naming and accurate.

137 again - the website is not the right place for the validation - instead, move parts from the website here.

138 For the validation of the scans and their processing we investigate the correlation scores of pair-wise aligned signals. For
139 signals from scans of wires cut with a different tool, we would expect a low correlation score. Large scores between signals
140 are indicative of being made by the same tool. Show boxplots and roc curve.

141 For validation of all other tools and locations of scan replicates, see the detailed [report](#).




Figure 2. (a) A profile line in dark blue was drawn across the striations of the scan. (b) The profile function extracted along the profile line in (a). (c) The raw signal in light blue is obtained by using the low-pass filter on the profile function in (b) and the filtered signal is obtained by using the high-pass filter on the raw signal.

142 (unlimited length) This section presents any experiments or analyses that are needed to support the technical quality of
143 the dataset. This section may be supported by figures and tables, as needed. This is a required section; authors must present
144 information justifying the reliability of their data.

145 • Measurement of data quality?

- 146 – Numeric measurements / tests: ?
147 – Visualizations: ?
148 – Check with existing data: ?
149 – Questionable / slur procedures:

150 * [AidDatas Geospatial Global Chinese Development Finance Dataset](#): Second, all data collected is reviewed
151 by at least two individuals. Although this is not a double-blind review procedure, the use of satellite imagery
152 to verify project locations results in far less uncertainty when compared to previous approaches to geocoding
153 where locations were selected entirely based on text descriptions.

154 * [A large open access dataset of brain metastasis 3D segmentations on MRI with clinical and imaging information](#): A medical student (D.R.) double checked and adjusted the revised NIfTI segmentation masks and
155 manually counted the number of lesions with contrast-enhancement, necrosis, and peritumoral edema for
156 each patient.

158 * [Time series of freshwater macroinvertebrate abundances and site characteristics of European streams and rivers](#): Technical validation of the TREAM dataset was achieved through exclusion of time series data that
159 did not match our inclusion criteria and data standardisation steps (outlined in Methods above). Any noted
160 issues that did not adhere to the outlined standardisation within the datasets from the 41 independent projects

162 included in this dataset were checked with data providers and corrected or removed when standardisation
163 was not achievable (e.g., when collection methods changed over the course of the time series).

- 164 * **3D surgical instrument collection for computer vision and extended reality:** The main issue...Since we
165 store our models in a standard format (STL), they are compatible with a large variety of visualisation and
166 processing software.
- 167 * **Three-dimensional reconstruction of high latitude bamboo coral via X-ray microfocus Computed Tomogra-
168 phy :** Regular quality assurance inspections are carried out on the μ -CT scanner to verify its metrological and
169 geometrical (alignments) accuracy for conducting the scans. The geometry of source to object and source
170 to detector distances are verified whenever there is any significant physical interaction with the source such
171 as re-alignment, change of filament, or source anode change. This calibration process involves scanning
172 a specially designed phantom known as an hourglass36, which consists of three pairs of high-sphericity
173 spheres. The sphere sizes are as follows: two spheres with a diameter of 3.000 mm, two spheres with a di-
174 ameter of 6.000 mm, and two spheres with a diameter of 9.525 mm, and each sphere is kept in contact with
175 its size-counterpart. By using this phantom, it becomes possible to accurately determine a known distance,
176 specifically the centre-to-centre distance of the spheres, in a threshold-independent manner. If the measured
177 distance deviates beyond the acceptable limits of metrological accuracy, the systems calibration parameters
178 are adjusted to ensure agreement between the measured distance and the actual distance.

179 Usage Notes

180 The R package `x3ptools` (available from CRAN) supports working with files in `x3p` format.

181 Sample scripts in R for processing scans from `x3p` format to their signal are available from ... [github](#).

182 Further analysis can be conducted with the GitHub R package `wire` and the GitHub R shiny app `wireShiny` ([ci-
183 tation?](#)). We already conduct between-replicate comparisons in the technical validation section, and we can also conduct
184 across-replicate comparisons to establish error rates threshold and produce other analysis plots.

185 Suppose we put the CCF values in a tilemap with different tool, location and edge combinations. In that case, we expect
186 only the diagonal to have high CCF values, close to 1 and marked as orange in the tilemap, as the diagonal represents the same
187 source, and the rest of the matrix to have low CCF values, close to 0 and marked as gray. In Figure 5, the behavior is consistent
188 with our expectation overall, except for some rare cases with tool 5 edge D, which is caused by [?????](#). We also put the resulting
189 CCFs in the boxplot, as in Figure 6. We can see that the CCF values for the same sources are close to 1, while the CCF values
190 for different sources are much lower than expected. This difference can be used to establish a threshold for CCF and help us
191 draw conclusions about the similarity between wire cut scans numerically, which can be used in real crime scenes. The density
192 plot in Figure 7 shows the distribution of the CCF values with the same sources and different sources. The overlapping points
193 between the tails of these two distributions can be a rough threshold. Furthermore, the receiver operating characteristic (ROC)
194 curve in Figure 8 shows the sensitivity / true positive rate against the false positive rate (FPR) (1 - specificity). The curve is
195 very close to the upper left corner, which is excellent for classification and drawing conclusion. It gives us a true threshold of
196 0.589 to control the FPR to be less than 0.05 with false negative rate (FNR) to be 0, ([false positive rate \(FPR\) / false discovery
197 rate \(FDR\) -> define the H0 or call it false identification rate \(FIR\)???](#)), and 0.658 to control the FPR to be less than 0.01, with
198 FNR to be 0.02.

199 ([unlimited length](#)) The Usage Notes should contain brief instructions to assist other researchers with reuse of the data.
200 This may include discussion of software packages that are suitable for analysing the assay data files, suggested downstream
201 processing steps (e.g. normalization, etc.), or tips for integrating or comparing the data records with other datasets. Authors
202 are encouraged to provide code, programs or data-processing workflows if they may help others understand or use the data.
203 Please see our code availability policy for advice on supplying custom code alongside Data Descriptor manuscripts.

204 For studies involving privacy or safety controls on public access to the data, this section should describe in detail these
205 controls, including how authors can apply to access the data, what criteria will be used to determine who may access the data,
206 and any limitations on data use.

207 Code availability

208 [table of code-manual?](#)

209 [no, we can't use the website as a place for more detailed procedures. This paper is the detailed procedure.no more
210 README, scanning procedures in another HTML](#)

211 We put together the cutting and the standard scanning procedures mentioned in Section [cross-ref not working](#) with more
212 pictures for each step into a [README of the GitHub repository heike/Wirecuts \(High-res pics needed in the README\)](#).

213 The data set can be easily accessed with the CRAN R package `x3ptools`. Further analysis can be conducted with the
214 GitHub R package `wire` and the GitHub R shiny app `wireShiny` ([citation](#)) ([again????](#)).

215 For all studies using custom code in the generation or processing of datasets, a statement must be included under the heading
216 "Code availability", indicating whether and how the code can be accessed, including any restrictions to access. This section
217 should also include information on the versions of any software used, if relevant, and any specific variables or parameters used
218 to generate, test, or process the current dataset.

219 **1 End of Body**

220 **(Note that the bibliography style and the name of the bib-file are hard coded in the template file right now.)**

221 LaTeX formats citations and references automatically using the bibliography records in your .bib file, which you can edit via
222 the project menu. Use the `cite` command for an inline citation, e.g. [????](#). For data citations of datasets uploaded to e.g. `figshare`,
223 please use the `howpublished` option in the bib entry to specify the platform and the link, as in the `Hao:gidmaps:2014`
224 example in the sample bibliography file. For journal articles, DOIs should be included for works in press that do not yet
225 have volume or page numbers. For other journal articles, DOIs should be included uniformly for all articles or not at all. We
226 recommend that you encode all DOIs in your bibtex database as full URLs, e.g. <https://doi.org/10.1007/s12110-009-9068-2>.

227 **Acknowledgements**

228 Acknowledgements should be brief, and should not include thanks to anonymous referees and editors, or effusive comments.
229 Grant or contribution numbers may be acknowledged.

230 **Author contributions statement**

231 Y.L. did all of the work, H.H. made him do the work. But seriously, this paper is the one where we need to cite everybody:
232 Eden Amin, Curtis Mosher, Jeff Salyards. Alicia? Must include all authors, identified by initials, for example: A.A. conceived
233 the experiment(s), A.A. and B.A. conducted the experiment(s), C.A. and D.A. analysed the results. All authors reviewed the
234 manuscript.

235 **Competing interests**

236 (mandatory statement)

237 H.H. is a technical advisor to AFTE (Association of Firearms and Toolmarks Examiners), fellow of the ASA (American
238 Statistical Association), and committee member of the ASA Forensic Science Committee. H.H. has testified as court witness
239 on behalf of judge April Neubauer, NY State Supreme Court Criminal Term in New York City. The corresponding author
240 is responsible for providing a [competing interests statement](#) on behalf of all authors of the paper. This statement must be
241 included in the submitted article file.

242 **Figures & Tables**

243 Figures, tables, and their legends, should be included at the end of the document. Figures and tables can be referenced in
244 `LATEX` using the `ref` command, e.g. Figure 9 and Table 2.

245 Authors are encouraged to provide one or more tables that provide basic information on the main inputs to the study
246 (e.g. samples, participants, or information sources) and the main data outputs of the study. Tables in the manuscript should
247 generally not be used to present primary data (i.e. measurements). Tables containing primary data should be submitted to an
248 appropriate data repository.


249 Tables may be provided within the `LATEX` document or as separate files (tab-delimited text or Excel files). Legends, where
250 needed, should be included here. Generally, a Data Descriptor should have fewer than ten Tables, but more may be allowed
251 when needed. Tables may be of any size, but only Tables which fit onto a single printed page will be included in the PDF
252 version of the article (up to a maximum of three).

253 Due to typesetting constraints, tables that do not fit onto a single A4 page cannot be included in the PDF version of the
254 article and will be made available in the online version only. Any such tables must be labelled in the text as Online-only tables
255 and numbered separately from the main table list e.g. Table 1, Table 2, Online-only Table 1 etc.

Condition	n	p
A	5	0.1
B	10	0.01

Table 2. Legend (350 words max). Example legend text.

Edge A



Edge C



Edge B



Edge D



Figure 3. Scans from different sides of tool 1 at the inner location.




Figure 4. The first and second columns show the signals extracted from Figure 3, and the third column shows the alignments and CCF values between pairs of signals.




Figure 5. The tilemap shows signals from the same source have CCFs close to 1.




Figure 6. The boxplot shows that signals from the same sources have higher CCFs than those from different sources.




Figure 7. The density plot shows tails of distributions overlap, which can be used as a rough threshold for drawing conclusions.




Figure 8. The ROC curve is bending very close to the upper left corner, which means excellent in classification and drawing conclusions.




Figure 9. Legend (350 words max). Example legend text.