4-more ddply

Rearranging Data

Iowa State University

Outline

- working with `ddply`: an example
- plyr variations

French Fries

- 10 week experiment
- 12 participants
- 3 types of oil
- 2 replicates for each individudal, each week
- Participants asked to evaluate how potato-y, buttery, grassy, rancid, and paint-y the french fries taste

What would be interesting to investigate?

What would be interesting to investigate?

- How have average ratings changed over time?
- Do certain participants give higher ratings than others?
- How similar are different replicates for each subject?
- Do different oils have different rating trajectories over time?

All of these questions can be answered using ddply.

Your Turn

Answer one or more of the questions you came up with using ddply

Sample Questions:

- How do average ratings change over time for each variable?
- How similar are different replicates for each subject?
- Do different oils have different average rating trajectories over time?

stringr package

The str_command philosophy for more consistency with string operators

- Basics
  - str_c
    Join multiple strings into a single string.
  - str_join
    Join multiple strings into a single string.
  - str_length
    The length of a string (in characters).
  - str_dup
    Duplicate and concatenate strings within a character vector.
  - str_trim
    Trim whitespace from start and end of string.
  - word
    Extract words from a sentence.
  - str_split
    Split up a string into a variable number of pieces.
- Pattern Detection
  - str_detect
    Detect the presence or absence of a pattern in a string.
  - str_locate, str_locate_all
    Locate the position of the first, all occurrence of a pattern in a string.
  - str_count
    Count the number of matches in a string.
  - str_match, str_match_all
    Extract first, all matched group from a string.
- Pattern Extraction & Replacement
  - str_extract, str_extract_all
    Extract first, all piece of a string that matches a pattern.
  - str_sub
    Extract substrings from a character vector.
  - str_sub_replace
    Replace substrings in a character vector.
    'str_sub<-' will recycle all arguments to be the same length as the longest argument.
  - str_replace, str_replace_all
    Replace first occurrence of a matched pattern in a string.

transform

Transform allows multiple statements with the same dataset (shortcut)

```
data$newvar1 = ...
data$newvar2 = ...
data$newvar3 = ...
```

With transform, this becomes...

```
data <- transform(data,
  newvar1 = ...,
  newvar2 = ...,
  newvar3 = ...
)
```

ddply and transform together allow us to perform group-wise operations

OkCupid Data

OkCupid is an online dating site. This dataset contains demographic information (age, gender, location, relationship status, religious affiliation) from a subset of OkCupid users, along with their response to one essay prompt.

http://www.stat.iastate.edu/centers/CCGS/R%20workshops/03-r-format/data/OkCupid.csv

Download the data to your working directory, and read it into R:

```
## Error:  cannot change working directory
```

```
profile <- read.csv("OkCupid.csv", stringsAsFactors=FALSE)
```

```
## Warning:  cannot open file 'OkCupid.csv':  No such file or
directory
## Error:  cannot open the connection
## Error:  cannot change working directory
```

Your Turn

Use Stringr and transform to create separate variables for the state, city, and height in inches of each user.

Hints:

- `word()` will give you single items in a string, so if you define `sep=", "`, you can extract the city and state separately by changing `start` and `end`
- Use `word()` with a different `sep=""`, twice. The second time, specify `start`.
  Alternately, use `str_sub()` to get feet and/or inches, with `str_locate()` to get the relevant start/end locations.

ddply + separate function

Instead of using an existing function, we can have more flexibility and write our own function:

```
data <- ddply(data, .(id),
              function(x){
                ...
              })
```

This function should return a data frame (for now).

Notice that you no longer have to use one of "summarize", "transform", etc. after your .(id) statement.

Your Turn

Use ddply to create a dataset that examines the proportion of users of each gender and one other variable in each state that are on OkCupid.

Hint: Variables with a small number of choices, such as orientation, status, Education, Drinks, Smokes are good options.

Hint 2: Use table() and as.data.frame to convert the table into something we can deal with.

Variations on ddply

- plyr commands have the format `xyply`
- `x` and `y` are letters representing different object types
- `x` is "going in" and `y` is "coming out"

letter	object
l	list
d	data frame
m	data frame or matrix
a	array (vector or matrix)
_	no output
r	input only

Example: `ldply` takes a list and returns a data frame

Your Turn

Use one of the plyr commands to do each of the following:

1. For each state, return the longest essay (`essay_0`) for each gender
2. From the previous output, extract the most common word (use table() and order()) and count the number of sentences (or at least the number of "."'s.).