

ICT & Infra S3 S/NO week 4: AWS VPC

Sample web application

Date: Sep 2020
Version 1.0

Class: I3 CB01

Student numbers: 4642295, 4216709, 4961854

Student names: Ryan Smith, Edris Rahimi, Heiko Morales

Introduction

S/NO: In this exercises you will learn:

- how to create initial secure VPC web application design in AWS
- make a connection to S3 bucket from a public EC2 Instance
- study sample AWS Powershell scripts for this design and create similar Ansible/Teffaform scripts.

How to deliver your assignments?

Fill in this document with required information. Answer questions and upload the document to Canvas at most one week after the assignment is given.

Assignment 1: Create initial VPC web application setup

- Follow the demo from the class and create web-vpc and shared-vpc with corresponding EC2 instances.
- Demonstrate successful ssh-access to web-pub instance.
- Demonstrate successful “ping 8.8.8.8” from web-pub instance.
- Explain routing rules via “route” command at web-pub instance

We created a VPC and assigning tags to it. We then created a subnet for our VPC and configured the subnet settings. After that we created an internet gateway and attached it to our VPC. After that we used ssh to connect to an ec2 instance and pinged 8.8.8.8. The response was successful

Create VPC [Info](#)

A VPC is an isolated portion of the AWS Cloud populated by AWS objects, such as Amazon EC2 instances.

VPC settings

Resources to create [Info](#)

Create only the VPC resource or the VPC and other networking resources.

☒ VPC only

☐ VPC and more

Name tag - *optional*

Creates a tag with a key of 'Name' and a value that you specify.

web-group14

IPv4 CIDR block [Info](#)

☒ IPv4 CIDR manual input

☐ IPAM-allocated IPv4 CIDR block

IPv4 CIDR

10.0.0.0/16

IPv6 CIDR block [Info](#)

☒ No IPv6 CIDR block

☐ IPAM-allocated IPv6 CIDR block

☐ Amazon-provided IPv6 CIDR block

☐ IPv6 CIDR owned by me

Tenancy [Info](#)

Default

Tags

A tag is a label that you assign to an AWS resource. Each tag consists of a key and an optional value. You can use tags to search and filter your resources or track your AWS costs.

Key

Q Name



Value - *optional*

Q web-group14



Remove

Add new tag

You can add 49 more tags.

Cancel

Create VPC

Create subnet [Info](#)

VPC

VPC ID

Create subnets in this VPC.

vpc-00e0230a2642bf855 (web-group14) ▼

Associated VPC CIDRs

IPv4 CIDRs

10.0.0.0/16

Subnet settings

Specify the CIDR blocks and Availability Zone for the subnet.

Subnet 1 of 1

Subnet name

Create a tag with a key of 'Name' and a value that you specify.

web-subnet

The name can be up to 256 characters long.

Availability Zone [Info](#)

Choose the zone in which your subnet will reside, or let Amazon choose one for you.

Europe (Frankfurt) / eu-central-1a ▼

IPv4 CIDR block [Info](#)

0.0.0.0/24

▼ Tags - optional

Key

Name



Value - optional

web-subnet



Remove

Add new tag

You can add 49 more tags.

Remove

Add new subnet

Cancel

Create subnet

Create internet gateway [Info](#)

An internet gateway is a virtual router that connects a VPC to the internet. To create a new internet gateway specify the name for the gateway below.

Internet gateway settings

Name tag

Creates a tag with a key of 'Name' and a value that you specify.

Tags - *optional*

A tag is a label that you assign to an AWS resource. Each tag consists of a key and an optional value. You can use tags to search and filter your resources or track your AWS costs.

Key



Value - *optional*



You can add 49 more tags.

Attach to VPC (igw-0348c337fb05abfe6) [Info](#)

VPC

Attach an internet gateway to a VPC to enable the VPC to communicate with the internet. Specify the VPC to attach below.

Available VPCs

Attach the internet gateway to this VPC.



► AWS Command Line Interface command

Edit routes

Destination	Target	Status	Propagated
10.0.0.0/16	<input type="text" value="local"/>	Active	No
<input type="text" value="0.0.0.0/0"/>	<input type="text" value="igw-0348c337fb05abfe6"/>	Active	No <input type="button" value="Remove"/>
<input type="button" value="Add route"/>			

Edit subnet associations

Change which subnets are associated with this route table.

Available subnets (1/1)

Filter subnet associations

< 1 > ⌵

<input checked="" type="checkbox"/>	Name	Subnet ID	IPv4 CIDR	IPv6 CIDR	Route table ID
<input checked="" type="checkbox"/>	web-subnet	subnet-0220d95d77b441cd0	10.0.0/24	-	Main (rtb-0c93169716ec7dae0)

Selected subnets

subnet-0220d95d77b441cd0 / web-subnet ✕

Cancel Save associations

```
heiko@DESKTOP-IDN3683:~$ ssh -i .ssh/heiko_ubuntu_key.pem ubuntu@ec2-18-184-82-172.eu-central-1.compute.amazonaws.com
The authenticity of host 'ec2-18-184-82-172.eu-central-1.compute.amazonaws.com (18.184.82.172)' can't be established.
ECDSA key fingerprint is SHA256:2d4br+0sRv4XzomqfZKfV9nqPXpv+vNp1gZKiGI4C64.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'ec2-18-184-82-172.eu-central-1.compute.amazonaws.com,18.184.82.172' (ECDSA) to the list of k
nown hosts.
Welcome to Ubuntu 20.04.5 LTS (GNU/Linux 5.15.0-1019-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Sun Oct  9 17:30:40 UTC 2022

System load:  0.19           Processes:           101
Usage of /:   19.6% of 7.57GB Users logged in:      0
Memory usage: 21%           IPv4 address for eth0: 10.0.8.11
Swap usage:   0%

0 updates can be applied immediately.

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

ubuntu@ip-10-0-8-11:~$
```

```
ubuntu@ip-10-0-8-11:~$ ping 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=113 time=1.25 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=113 time=2.17 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=113 time=1.40 ms
64 bytes from 8.8.8.8: icmp_seq=4 ttl=113 time=1.31 ms
^C^C
--- 8.8.8.8 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3004ms
rtt min/avg/max/mdev = 1.251/1.533/2.171/0.371 ms
```

first row is the ip for the DHCP

second row is the subnet ip

```
ubuntu@ip-10-0-8-11:~$ ip route
default via 10.0.0.1 dev eth0 proto dhcp src 10.0.8.11 metric 100
10.0.0.0/20 dev eth0 proto kernel scope link src 10.0.8.11
10.0.0.1 dev eth0 proto dhcp scope link src 10.0.8.11 metric 100
```

Assignment 2: Make a connection from web-pub instance to s3 bucket

- Follow the guidelines:

<https://aws.amazon.com/premiumsupport/knowledge-center/ec2-instance-access-s3-bucket/>

We created an s3 bucket and an ec2 instance. We connected to the instance by SSH and installed aws tools on the instance. We then went back to the bucket and applied the policies that would allow the ec2 instance to connect to the bucket. When that was done we went back to the instance and ran the command “aws s3 ls s3://heikoweb”

```
{
  "Effect": "Allow",
  "Principal": "*",
  "Action": "s3:GetObject",
  "Resource": "arn:aws:s3:::heikoweb/*"
},
{
  "Effect": "Allow",
  "Principal": "*",
  "Action": "s3:ListBucket",
  "Resource": "arn:aws:s3:::heikoweb"
}
]

ubuntu@ip-10-0-8-11:~$ aws s3 ls s3://heikoweb
PRE css/
PRE img/
2022-09-16 10:50:08 994 main.html
```

Assignment 3: Create Ansible/Terraform scripts for initial VPC web application setup

- Install latest Windows 7 Powershell Tool
- Unpack “PS_scripts.zip” archive
- Study and experiment with “PS_scripts.zip/Test” scripts. You don’t need to run these scripts, but you may use for inspiration.

The main task is to compose the Ansible/Terraform scripts with all necessary configuration as in the Assignment 1 for public web-pub and private database

To run these sample scripts you may need to:

- Run “Install-awspowershell.ps1” to install AWS Powershell tools.
- Update “credentials.ps1”.
- Run “TEST/vpc-creation.ps1” to create sample web-pub instance with all necessary configurations in AWS.

On this task we ran into errors every time we tried to run the script. After an hour of troubleshooting we could not find the cause.

```
PS C:\Users\heiko\Desktop\PS_scripts_> .\install-awspowershell.ps1
You are using PowerShell Desktop!
Importing module...
Import-Module : No se cargó el módulo 'AWSPowerShell' especificado porque no se encontró ningún archivo de módulo
válido en ningún directorio de módulo.
En C:\Users\heiko\Desktop\PS_scripts_\install-awspowershell.ps1: 22 Carácter: 9
+ Import-Module AWSPowerShell -Force
+ ~~~~~
+ CategoryInfo          : ResourceUnavailable: (AWSPowerShell:String) [Import-Module], FileNotFoundException
+ FullyQualifiedErrorId : Modules_ModuleNotFound,Microsoft.PowerShell.Commands.ImportModuleCommand

Get-AWSPowerShellVersion : El término 'Get-AWSPowerShellVersion' no se reconoce como nombre de un cmdlet, función,
archivo de script o programa ejecutable. Compruebe si escribió correctamente el nombre o, si incluyó una ruta de
acceso, compruebe que dicha ruta es correcta e inténtelo de nuevo.
En C:\Users\heiko\Desktop\PS_scripts_\install-awspowershell.ps1: 27 Carácter: 5
+ Get-AWSPowerShellVersion
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (Get-AWSPowerShellVersion:String) [], CommandNotFoundException
+ FullyQualifiedErrorId : CommandNotFoundException
```