



Search

This document is about: **QUANTUM 2**

SWITCH TO



# Input & Connection Flags

## Introduction

The **DeterministicInputFlags** are used by Quantum to:

- detect whether a player is *present*, i.e. connected, to the simulation;
- decide how to *predict* the next tick's input for a given player; and,
- know whether the input on a verified frame was provided by a client or was *replaced* by the server.

It is possible to automate the checks by implementing **PlayerConnectedSystem**, for more information [please refer to its entry on the Player page](#).

## Types

**C#**

```
public enum DeterministicInputFlags : byte {  
    Repeatable = 1 << 0,  
    PlayerNotPresent = 1 << 1,  
    ReplacedByServer = 1 << 2  
}
```

- **PlayerNotPresent** = means there is no client connected for this player index.
- **ReplacedByServer** = means the player index is controlled by a client, but the client did not send the input in time which resulted in the server repeating or replacing/zeroing out the input.



This can be set by the developer from Unity when injecting player input and should be used on direct-control-like input such as movement; it is not meant for command-like input (e.g. buy item).

# Implementation example



**IMPORTANT:** `DeterministicInputFlags` can only be trusted on *verified* frames.

The code snippet below is an extra from the LittleGuys sample found on the BotSDK page.

C#

```
private void UpdateIsBot(Frame f, EntityRef littleGuyEntity)
{
    // Return if players shouldn't be replaced by bots
    if (!f.RuntimeConfig.ReplaceOnDisconnect)
        return;

    // Only update this information if this frame is Verified.
    if (!f.IsVerified) return;

    var littleGuyComponent = f.Unsafe.GetPointer<LittleGuyComponent>

    // Get the input flags for that player
    var inputFlags = f.GetPlayerInputFlags(littleGuyComponent->Play

    // Bitwise operations to see if the PlayerNotPresent flag is ac
    var playerDisconnected = (inputFlags & DeterministicInputFlags.

    // Store it in the IsBot field so this can be evaluated in othe
    littleGuyComponent->IsBot = playerDisconnected;

    // Only initialize the entity as a bot if it doesn't have the H
    if (playerDisconnected && f.TryGet<HFSMAgent>(littleGuyEntity,
    {
        // We're replacing players only by the HFSM, but this could e

        HFSMHelper.SetupHFSM(f, littleGuyEntity, f.RuntimeConfig.Repl
```



[Back to top](#)



We Make Multiplayer Simple

## Products

Fusion  
Quantum  
Realtime  
Chat  
Voice  
PUN

## Memberships

Gaming Circle  
Industries Circle

## Support

Gaming Circle  
Industries Circle  
Circle Discord  
Circle Stack Overflow

## Connect

Public Discord  
YouTube  
Facebook  
Twitter

## Documentation

Fusion  
Quantum  
Realtime  
Chat  
Voice  
PUN  
Bolt  
Server  
VR | AR | MR

## Resources

Dashboard  
Samples  
SDK Downloads  
Cloud Status

## Languages

English  
日本語  
한국어  
简体中文



[Terms](#) [Regulatory](#) [Privacy Policy](#) [Privacy](#) [Code of Conduct](#) [Cookie Settings](#)

