



Search



FUSION



QUANTUM

API Reference

Getting Started



Quantum 100



Game Samples



Technical Samples



AddOns



Manual



Quantum Ecs



- DSL (game state)
- Systems (game logic)
- Components
- Events & Callbacks

Fixed Point

- Animation
- Assets
- Cheat Protection
- Commands
- Configuration Files
- Custom Server Plugin
- Entity Prototypes
- Entity View
- Frames





Input	
Materialization	
Map Baking	
Multi-Client Runner	
Navigation	▼
Physics	▼
Player	▼
Prediction Culling	
Profiling	
Quantum Project	
Replays	
RNG Session	
WebGL	
Concepts And Patterns	▼
Consoles	▼
Gaming Circle	▼
Reference	▼
REALTIME	▼
CHAT	▼
VOICE	▼
SERVER	▼
PUN	▼
BOLT	▼



Languages [English](#) , [日本語](#) , [한국어](#) , [繁体中文](#)

[FIND HELP ON DISCORD](#)

QUANTUM | v2 [switch to V1 ▶](#) [switch to V3 ▶](#)

Fixed Point

- [Introduction](#)
- [Parsing FPs](#)
 - [TLDR](#)
 - [FP.FromFloat_UNSAFE\(\)](#)
 - [FP.FromString_UNSAFE\(\)](#)
 - [FP.FromString\(\)](#)
 - [FP.FromRaw\(\)](#)
- [Const Variables](#)
- [Casting](#)
- [Inlining](#)
- [Overflow](#)
- [Precision](#)
- [FPAnimationCurves](#)
 - [Polling Data From An FPAnimationCurve](#)
 - [Creating FPAnimationCurves Directly On The Simulation](#)
 - [Baking Unity's AnimationCurve Into A FPAnimationCurve](#)

Introduction

In Quantum the **FP** struct (Fixed Point) completely replaces all usages of **floats** and **doubles** to ensure cross-platform determinism. It offers versions of common math data structures like **FPVector2**, **FPVector3**, **FPMatrix**, **FPQuaternion**, **RNGSession**, **FPBounds2**, etc. All systems in Quantum, including physics and navigation, exclusively use **FP** values in their computations.

The fixed-point type implemented in Quantum is **Q48.16** . It has proved to a good balance between precision and performance with a bias towards the latter.

Internally **FP** uses one long to represent the combined fixed-point number (whole number + decimal part); the long value can be accessed and set via **FP.RawValue** .

Quantum's FP Math uses carefully tuned look up tables for fast trigonometric and square root functions (see [QuantumSDK\quantum_unity\Assets\Photon\Quantum\Resources\LUT](#)).

[Back To Top](#)

Parsing FPs

The representable **FP** fraction is limited and never as accurate as a **double** . Parsing is an approximation and will round to the nearest possible **FP** precision. This is reflected in:



- different parsing methods yielding different results on the same machine.

```
FP.FromFloat(1.1f).RawValue != FP.FromString("1.1").RawValue
```

[Back To Top](#)

TLDR

- Use from float only during edit time, never inside the simulation or at runtime.
- It is best to convert from raw whenever possible.

[Back To Top](#)

FP.FromFloat_UNSAFE()

Converting from `float` is not deterministic due to rounding errors and should **never** be done inside the simulation. Doing such a conversion in the simulation will cause desyncs 100% of the time.

However, it can be used during **edit** or **build time**, when the converted (FP) data is first created and then shared with everyone. **IMPORTANT:** Data generated this way on **different** machines may not be compatible.

```
var v = FP.FromFloat_UNSAFE(1.1f);
```

[Back To Top](#)

FP.FromString_UNSAFE()

This will internally parse the `string` as a float and then convert to `FP`. All caveats from `FromFloat_UNSAFE()` apply here as well.

```
var v = FP.FromFloat_UNSAFE("1.1");
```

[Back To Top](#)

FP.FromString()

This is deterministic and therefore safe to use anywhere but may not be the most performant option. A typical use case is balancing information (patch) that clients load from a server and then use to update data in Quantum assets.

Be aware of the string locale! It only parses English number formatting for decimals and requires a dot (e.g. 1000.01f).

```
var v = FP.FromFloat("1.1");
```

[Back To Top](#)



```
var v = FP.FromRaw(72089);
```

This snippet can be used to create a FP converter window in Unity for convenient conversion.

```
using System;
using UnityEditor;
using Photon.Deterministic;

public class FPConverter : EditorWindow {
    private float _f;
    private FP _fp;

    [MenuItem("Quantum/FP Converter")]
    public static void ShowWindow() {
        GetWindow(typeof(FPConverter), false, "FP Converter");
    }

    public virtual void OnGUI() {
        _f = EditorGUILayout.FloatField("Input", _f);
        try {
            _fp = FP.FromFloat_UNSAFE(_f);
            var f = FPPROPERTYDRAWER.GetRawAsFloat(_fp.RawValue);
            var rect = EditorGUILayout.GetControlRect(true);
            EditorGUI.FloatField(rect, "Output FP", f);
            QuantumEditorGUI.Overlay(rect, "(FP)");
            EditorGUILayout.LongField("Output Raw", _fp.RawValue);
        }
        catch (OverflowException e) {
            EditorGUILayout.LabelField("Out of range");
        }
    }
}
```

[Back To Top](#)

Const Variables

The `FP._1_10` syntax can not be extended or generated.

FP is a struct and can therefore not be used as a constant. It is, however, possible to hard-code and use " FP " values in const variables:

1. Combine pre-defined FP._1 static getters or FP.Raw._1 const variables.

```
FP foo = FP._1 + FP._0_10;
// or
```



```
const long MagicNumber = FP.Raw._1 + FP.Raw._0_10;
```

```
FP foo = default;
foo.RawValue = MagicNumber;
// or
foo = FP.FromRaw(MagicNumber);
```

2. Convert the specific float once to FP and save the raw value as a constant

```
const long MagicNumber = 72089; // 1.1
```

```
var foo = FP.FromRaw(MagicNumber);
// or
foo.RawValue = MagicNumber;
```

3. Create the constant inside the Quantum DSL

```
#define FPConst 1.1
```

Then use like this:

```
var foo = default(FP);
foo += Constants.FPConst;
// or
foo.RawValue += Constants.Raw.FPConst;
```

It will generate code to represent the constant in the following way:

```
public static unsafe partial class Constants {
    public const Int32 PLAYER_COUNT = 8;
    /// <summary>1.100006</summary>

    public static FP FPConst {
        [MethodImpl(MethodImplOptions.AggressiveInlining)] get {
            FP result;
            result.RawValue = 72090;
            return result;
        }
    }
    public static unsafe partial class Raw {
        /// <summary>1.100006</summary>
        public const Int64 FPConst = 72090;
    }
}
```

4. Define `readonly static` variables in the class.



There is a performance penalty compared to `const` variables and don't forget to mark `readonly` because randomly changing the value during runtime could lead to desyncs.

[Back To Top](#)

Casting

Implicit casting to `FP` from `int`, `uint`, `short`, `ushort`, `byte`, `sbyte` is allowed and safe.

```
FP v = (FP)1;
FP v = 1;
```

Explicit casting from `FP` to `float` or `double` is possible, but obviously should not be used inside the simulation.

```
var v = (double)FP._1;
var v = (float)FP._1;
```

Casting to integer and back is safe though.

```
FP v = (FP)(int)FP._1;
```

Unsafe casts are marked as `[obsolete]` and will cause a `InvalidOperationException`.

```
FP v = 1.1f; // ERROR
FP v = 1.1d; // ERROR
```

[Back To Top](#)

Inlining

All low-level Quantum systems use manual inlined `FP` arithmetic to extract every ounce of performance possible. Fixed point math uses integer division and multiplication. To achieve this, the result or dividend are bit-shifted by the FP-Precision (16) before or after the calculation.

```
var v = parameter * FP._0_01;

// inlined integer math
FP v = default;
v.RawValue = (parameter.RawValue * FP._0_01.RawValue) >> FPLut.PRECISION;

var v = parameter / FP._0_01;

// inlined integer math
```



`FP.UseableMax` represents the highest `FP` number that can be multiplied with itself and not cause an overflow (exceeding `long` range).

```
FP.UseableMin
  Decimal: -32768
  Raw: -2147483648
  Binary: 10000000000000000000000000000000 = 32 bit
```

The general **FP** precision is decent when the numbers are kept within a certain range (**0.01..1000**) . FP-math related precision problems usually produce inaccurate results and tend to make systems (based on math) unstable. A very common case is to multiply very high or small numbers and then returning to the original range by division for example. The resulting numbers lose precision.

Another example is this method excerpt from `ClosestDistanceToTriangle` . Where `t0` is calculated from multiplying two dot products with each other, where a dot-product is already also a result of multiplications. This is a problem when very accurate results are expected. A way to mitigate this issue is shifting the values artificially before the calculation then shift the result back. This will work when the ranges of the input are somewhat known.

<https://doc.photonengine.com/quantum/current/manual/quantum-ecs/fixed-point>



FPAnimationCurves

Unity comes with a set of tools which are useful to express some values in the form of curves. It comes with a custom editor for such curves, which are then serialised and can be used in runtime in order to evaluate the value of the curve in some specific point.

There are many situations where curves can be used, such as expressing steering information when implementing vehicles, the utility value during the decision making for an AI agent (as done in Bot SDK's Utility Theory), getting the multiplier value for some attack's damage, and so on.

The Quantum SDK already comes with its own implementation of an animation curve, named **FPAnimationCurve**, evaluated as FPs. This custom type, when inspected directly on Data Assets and Components in Unity, are drawn with Unity's default Animation Curve editors, whose data are then internally baked into the deterministic type.

[Back To Top](#)

Polling Data From An FPAnimationCurve

The code needed to poll some data from a curve, with Quantum code, is very similar to the Unity's version:

```
// This returns the pre-baked value, interpolated accordingly to the curve's configura
FP myValue = myCurve.Evaluate(FP._0_50);
```

[Back To Top](#)

Creating FPAnimationCurves Directly On The Simulation

Here are the snippets to create a deterministic animation curve from scratch, directly on the simulation:

```
// Creating a simple, linear curve with five key points
// Change the parameter as preferred
public static class FPAnimationCurveUtils
{
    public static FPAnimationCurve CreateLinearCurve(FPAnimationCurve.WrapMode preWrapMode,
    {
        return new FPAnimationCurve
        {
            Samples = new FP[5] { FP._0, FP._0_25, FP._0_50, FP._0_75, FP._1 },
            PostWrapMode = (int)postWrapMode,
            PreWrapMode = (int)preWrapMode,
            StartTime = 0,
            EndTime = 1,
            Resolution = 32
        };
    }
}
```



```
// It can also be used directly to pre-initialise a curve in an asset
public unsafe partial class CollectibleData
{
    public FPAAnimationCurve myCurve = FPAAnimationCurveUtils.CreateLinearCurve(FPAnimat
```

[Back To Top](#)

Baking Unity's AnimationCurve Into A FPAAnimationCurve

The snippets needed for converting a regular Unity `AnimationCurve` into an `FPAAnimationCurve` can be found [HERE](#).

[To Document Top](#)

We Make Multiplayer Simple

Products

Fusion
Quantum
Realtime
Chat
Voice
PUN

Memberships

Gaming Circle
Industries Circle

Support

Gaming Circle
Industries Circle

Documentation

Fusion
Quantum
Realtime
Chat
Voice
PUN
Bolt
Server
VR | AR | MR

Resources

Dashboard
Samples



Connect

[Public Discord](#)

[YouTube](#)

[Facebook](#)

[Twitter](#)

[Blog](#)

[Contact Us](#)

Languages

[English](#)

[日本語](#)

[한국어](#)

[简体中文](#)

[繁体中文](#)

[Terms](#) [Regulatory](#) [Privacy Policy](#) [Privacy](#) [Code of Conduct](#) [Cookie Settings](#)