Quantitative comparisons: bar-charts

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Ariel Rokem
Data Scientist

Olympic medals

```
,Gold, Silver, Bronze
United States, 137, 52, 67
Germany, 47, 43, 67
Great Britain, 64, 55, 26
Russia, 50, 28, 35
China, 44, 30, 35
France, 20, 55, 21
Australia, 23, 34, 25
Italy, 8, 38, 24
Canada, 4, 4, 61
Japan, 17, 13, 34
```

Olympic medals: visualizing the data

```
medals = pd.read_csv('medals_by_country_2016.csv', index_col=0)
fig, ax = plt.subplots()
ax.bar(medals.index, medals["Gold"])
plt.show()
```



Interlude: rotate the tick labels

```
fig, ax = plt.subplots()
ax.bar(medals.index, medals["Gold"])
ax.set_xticklabels(medals.index, rotation=90)
ax.set_ylabel("Number of medals")
plt.show()
```



Olympic medals: visualizing the other medals

```
fig, ax = plt.subplots
ax.bar(medals.index, medals["Gold"])
ax.bar(medals.index, medals["Silver"], bottom=medals["Gold"])
ax.set_xticklabels(medals.index, rotation=90)
ax.set_ylabel("Number of medals")
plt.show()
```

create a stacked bar chart



Olympic medals: visualizing all three

```
fig, ax = plt.subplots
ax.bar(medals.index, medals["Gold"])

ax.bar(medals.index, medals["Silver"], bottom=medals["Gold"])
ax.bar(medals.index, medals["Bronze"],
       bottom=medals["Gold"] + medals["Silver"])
ax.set_xticklabels(medals.index, rotation=90)
ax.set_ylabel("Number of medals")
plt.show()
```

Stacked bar chart



Adding a legend

```
fig, ax = plt.subplots
ax.bar(medals.index, medals["Gold"])
ax.bar(medals.index, medals["Silver"], bottom=medals["Gold"])
ax.bar(medals.index, medals["Bronze"],
       bottom=medals["Gold"] + medals["Silver"])

ax.set_xticklabels(medals.index, rotation=90)
ax.set_ylabel("Number of medals")
```

Adding a legend

```
fig, ax = plt.subplots
ax.bar(medals.index, medals["Gold"], label="Gold")
ax.bar(medals.index, medals["Silver"], bottom=medals["Gold"],
       label="Silver")
ax.bar(medals.index, medals["Bronze"],
       bottom=medals["Gold"] + medals["Silver"],
       label="Bronze")

ax.set_xticklabels(medals.index, rotation=90)
ax.set_ylabel("Number of medals")
ax.legend()
plt.show()
```

Stacked bar chart with legend



Create a bar chart!

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Quantitative comparisons: histograms

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Ariel Rokem
Data Scientist

Histograms



	ID	Name	Sex	Age	Height	Weight	Team	NOC	Games	Year	Season	City	Sport	Event	Medal
158	62	Giovanni Abagnale	M	21.0	198.0	90.0	Italy	ITA	2016 Summer	2016	Summer	Rio de Janeiro	Rowing	Rowing Men's Coxless Pairs	Bronze
11648	6346	Jrmie Azou	M	27.0	178.0	71.0	France	FRA	2016 Summer	2016	Summer	Rio de Janeiro	Rowing	Rowing Men's Lightweight Double Sculls	Gold
14871	8025	Thomas Gabriel Jrmie Baroukh	M	28.0	183.0	70.0	France	FRA	2016 Summer	2016	Summer	Rio de Janeiro	Rowing	Rowing Men's Lightweight Coxless Fours	Bronze
15215	8214	Jacob Jepsen Barse	M	27.0	188.0	73.0	Denmark	DEN	2016 Summer	2016	Summer	Rio de Janeiro	Rowing	Rowing Men's Lightweight Coxless Fours	Silver
18441	9764	Alexander Belonogoff	M	26.0	187.0	90.0	Australia	AUS	2016 Summer	2016	Summer	Rio de Janeiro	Rowing	Rowing Men's Quadruple Sculls	Silver

A bar chart again

```
fig, ax = plt.subplots()
ax.bar("Rowing", mens_rowing["Height"].mean())
ax.bar("Gymnastics", mens_gymnastics["Height"].mean())
ax.set_ylabel("Height (cm)")
plt.show()
```



Introducing histograms

```
fig, ax = plt.subplots()
ax.hist(mens_rowing["Height"])
ax.hist(mens_gymnastic["Height"])
ax.set_xlabel("Height (cm)")
ax.set_ylabel("# of observations")
plt.show()
```



Labels are needed

```
ax.hist(mens_rowing["Height"], label="Rowing")
ax.hist(mens_gymnastic["Height"], label="Gymnastics")
ax.set_xlabel("Height (cm)")
ax.set_ylabel("# of observations")

ax.legend()
plt.show()
```



Customizing histograms: setting the number of bins

```
ax.hist(mens_rowing["Height"], label="Rowing", bins=5)
ax.hist(mens_gymnastic["Height"], label="Gymnastics", bins=5)
ax.set_xlabel("Height (cm)")
ax.set_ylabel("# of observations")
ax.legend()
plt.show()
```



Customizing histograms: setting bin boundaries

```
ax.hist(mens_rowing["Height"], label="Rowing",
        bins=[150, 160, 170, 180, 190, 200, 210])

ax.hist(mens_gymnastic["Height"], label="Gymnastics",
        bins=[150, 160, 170, 180, 190, 200, 210])

ax.set_xlabel("Height (cm)")
ax.set_ylabel("# of observations")
ax.legend()
plt.show()
```



Customizing histograms: transparency

```
ax.hist(mens_rowing["Height"], label="Rowing",
        bins=[150, 160, 170, 180, 190, 200, 210],
        histtype="step")

ax.hist(mens_gymnastic["Height"], label="Gymnastics",
        bins=[150, 160, 170, 180, 190, 200, 210],
        histtype="step")

ax.set_xlabel("Height (cm)")
ax.set_ylabel("# of observations")
ax.legend()
plt.show()
```

Histogram with a histtype of step



Create your own histogram!

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Statistical plotting

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Ariel Rokem
Data Scientist

Adding error bars to bar charts

```
fig, ax = plt.subplots()

ax.bar("Rowing",
       mens_rowing["Height"].mean(),
       yerr=mens_rowing["Height"].std())

ax.bar("Gymnastics",
       mens_gymnastics["Height"].mean(),
       yerr=mens_gymnastics["Height"].std())

ax.set_ylabel("Height (cm)")

plt.show()
```

How can we make these comparisons more formal?
Statistical plotting is a set of methods for using visualization to make comparisons.
Error bars: summarize the distribution of the data in one number, such as the standard deviation of the values.
1. add the error bar as an argument to a bar chart, the standard deviation of the “Height” column displays as an additional vertical marker

Error bars in a bar chart



Adding error bars to plots

```
fig, ax = plt.subplots()

ax.errorbar(seattle_weather["MONTH"],
            seattle_weather["MLY-TAVG-NORMAL"],
            yerr=seattle_weather["MLY-TAVG-STDDEV"])

ax.errorbar(austin_weather["MONTH"],
            austin_weather["MLY-TAVG-NORMAL"],
            yerr=austin_weather["MLY-TAVG-STDDEV"])

ax.set_ylabel("Temperature (Fahrenheit)")

plt.show()
```

Error bars in plots



2. add error bars to a line plot

Adding boxplots

```
fig, ax = plt.subplots()

ax.boxplot([mens_rowing["Height"],
            mens_gymnastics["Height"]])

ax.set_xticklabels(["Rowing", "Gymnastics"])
ax.set_ylabel("Height (cm)")


plt.show()
```

Interpreting boxplots



The whiskers at the ends of the thin bars indicate one and a half times. This should encompass roughly 99 percent of the distribution if the data is normal.

Try it yourself!

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Quantitative comparisons: scatter plots

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB

Ariel Rokem
Data Scientist

Introducing scatter plots

```
fig, ax = plt.subplots()
ax.scatter(climate_change["co2"], climate_change["relative_temp"])
ax.set_xlabel("CO2 (ppm)")
ax.set_ylabel("Relative temperature (Celsius)")
plt.show()
```



Customizing scatter plots

```python
eighties = climate_change["1980-01-01":"1989-12-31"]
nineties = climate_change["1990-01-01":"1999-12-31"]
fig, ax = plt.subplots()
ax.scatter(eighties["co2"], eighties["relative_temp"],
           color="red", label="eighties")
ax.scatter(nineties["co2"], nineties["relative_temp"],
           color="blue", label="nineties")
ax.legend()

ax.set_xlabel("CO2 (ppm)")
ax.set_ylabel("Relative temperature (Celsius)")

plt.show()
```

Encoding a comparison by color



Encoding a third variable by color

```
fig, ax = plt.subplots()
ax.scatter(climate_change["co2"], climate_change["relative_temp"],
           c=climate_change.index)
ax.set_xlabel("CO2 (ppm)")
ax.set_ylabel("Relative temperature (Celsius)")
plt.show()
```

Encoding time in color



Practice making your own scatter plots!

INTRODUCTION TO DATA VISUALIZATION WITH MATPLOTLIB