



INTRODUCTION TO RELATIONAL DATABASES IN SQL

Your first database


Timo Grossenbacher
Data Journalist

Investigating universities in Switzerland


Eidgenössische Technische Hochschule Zürich

Zu dieser Hochschule gehören rund **18'600 Studierende** und **Professor/innen**. Es besteht ein jährlicher Aufwand von rund **1.6 Mrd. Fr.**, wovon **8.8 % aus privaten Drittmitteln** stammen (BFS, 2014).

Jeder Punkt in der Grafik zeigt eine von insgesamt **516 Interessenbindungen**.



Stand der Daten: Juni 2015
Quelle: Pressestelle
Interessenbindungen beinhalten auch Mandate in Verwaltungs- und Stiftungsräten sowie Vereinsvorstände, die im Auftrag der ETH Zürich von Professor/innen wahrgenommen werden. ETHZ und EPFL teilen sich den Universitätsrat («ETH-Rab»).





A relational database:

- real-life *entities* become *tables*
- reduced redundancy
- data integrity by *relationships*
- e.g. professors, universities, companies
- e.g. only one entry in companies for the bank "Credit Suisse"
- e.g. a professor can work at multiple universities and companies, a company can employ multiple professors



Throughout this course you will:

- work with the data I used for my investigation
- create a relational database from scratch
- learn three concepts:
 - *constraints*
 - *keys*
 - *referential integrity*

You'll need: Basic understanding of SQL, as taught in [Intro to SQL for Data Science](#).

Your first duty: Have a look at the PostgreSQL database

```
SELECT table_schema, table_name
FROM information_schema.tables;
```

tables: information about all tables in your current database

columns: information about all columns in all of the tables in your current database

table_schema	table_name
pg_catalog	pg_statistic
pg_catalog	pg_type
pg_catalog	pg_policy
pg_catalog	pg_authid
pg_catalog	pg_shadow
public	university_professors
pg_catalog	pg_settings
pg_catalog	pg_hba_file_rules
pg_catalog	pg_file_settings
pg_catalog	pg_config
...	

information_schema database is available in PostgreSQL by default.

information_schema is a meta-database that holds information about your current database. information_schema has multiple tables you can query with the known SELECT * FROM syntax:

tables: information about all tables in your current database

columns: information about all columns in all of the tables in your current database

...



Have a look at the columns of a certain table

```
SELECT table_name, column_name, data_type
FROM information_schema.columns
WHERE table_name = 'pg_config';
```

table_name	column_name	data_type
pg_config	name	text
pg_config	setting	text



INTRODUCTION TO RELATIONAL DATABASES IN SQL

Let's do this.



INTRODUCTION TO RELATIONAL DATABASES IN SQL

Tables: At the core of every database

Timo Grossenbacher
Data Journalist



Redundancy in the university_professors table

```
SELECT * FROM  
university_professors  
LIMIT 3;
```




Redundancy in the university_professors table



```
-[ RECORD 1 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortname | EPF  
university_city | Lausanne  
function       | Chairman of L3S Advisory Board  
organisation   | L3S Advisory Board  
organisation_sector | Education & research  
-[ RECORD 2 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university     | ETH Lausanne  
university_shortname | EPF  
university_city | Lausanne  
function       | Member Conseil of Zeno-Karl Schindler Foundation  
organisation   | Zeno-Karl Schindler Foundation  
organisation_sector | Education & research  
-[ RECORD 3 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
(truncated)  
function       | Member of Conseil Fondation IDIAP  
organisation   | Fondation IDIAP  
(truncated)
```




Currently: One "entity type" in the database






A better database model with three entity types

Old:




New:





A better database model with four entity types





Create new tables with CREATE TABLE

```
CREATE TABLE table_name (  
  column_a data_type,  
  column_b data_type,  
  column_c data_type  
);
```




Create new tables with CREATE TABLE

```
CREATE TABLE weather (  
  clouds text,  
  temperature numeric,  
  weather_station char(5)  
);
```

To add columns you can use the following SQL query:

```
ALTER TABLE table_name  
ADD COLUMN column_name data_type;
```





INTRODUCTION TO RELATIONAL DATABASES IN SQL

Let's practice!




INTRODUCTION TO RELATIONAL DATABASES IN SQL

Update your database as the structure changes


Timo Grossenbacher
Data Journalist



The current database model



The current database model





Only store DISTINCT data in the new tables

```
SELECT COUNT(*)  
FROM university_professors;
```

```
count  
-----  
1377
```

```
SELECT COUNT(DISTINCT organization)  
FROM university_professors;
```

```
count  
-----  
1287
```



INSERT DISTINCT records INTO the new tables

```
INSERT INTO organizations
SELECT DISTINCT organization,
       organization_sector
FROM university_professors;
```

Output: INSERT 0 1287

```
INSERT INTO organizations
SELECT organization,
       organization_sector
FROM university_professors;
```

Output: INSERT 0 1377



The INSERT INTO statement

```
INSERT INTO table_name (column_a, column_b)
VALUES ("value_a", "value_b");
```



RENAME a COLUMN in affiliations

```
CREATE TABLE affiliations (  
  firstname text,  
  lastname text,  
  university_shortcode text,  
  function text,  
  organisation text  
);
```

```
ALTER TABLE table_name  
RENAME COLUMN old_name TO new_name;
```




DROP a COLUMN in affiliations

```
CREATE TABLE affiliations (  
  firstname text,  
  lastname text,  
  university_shortname text,  
  function text,  
  organization text  
);
```

```
ALTER TABLE table_name  
DROP COLUMN column_name;
```

A professor is uniquely identified by firstname, lastname only

```
SELECT DISTINCT firstname, lastname,  
                university_shortcode  
FROM university_professors  
ORDER BY lastname;
```

```
-[ RECORD 1 ]-----+-----  
firstname      | Karl  
lastname       | Aberer  
university_shortcode | EPF  
-[ RECORD 2 ]-----+-----  
firstname      | Reza Shokrollah  
lastname       | Abhari  
university_shortcode | ETH  
-[ RECORD 3 ]-----+-----  
firstname      | Georges  
lastname       | Abou Jaoudé  
university_shortcode | EPF
```

(truncated)

(551 records)

```
SELECT DISTINCT firstname, lastname  
FROM university_professors  
ORDER BY lastname;
```


```
-[ RECORD 1 ]-----  
firstname | Karl  
lastname  | Aberer  
-[ RECORD 2 ]-----  
firstname | Reza Shokrollah  
lastname  | Abhari  
-[ RECORD 3 ]-----  
firstname | Georges  
lastname  | Abou Jaoudé
```

(truncated)

(551 records)



A professor is uniquely identified by firstname, lastname only





INTRODUCTION TO RELATIONAL DATABASES IN SQL

Let's get to work!