US010143069B2

(12) **United States Patent**
Cheung et al.

(10) **Patent No.: US 10,143,069 B2**
(45) **Date of Patent: Nov. 27, 2018**

(54) **INTELLIGENT LIGHTING CONTROL SYSTEM AUTOMATED ADJUSTMENT APPARATUSES, SYSTEMS, AND METHODS**

(71) Applicant: **Locoroll, Inc.**, Cupertino, CA (US)

(72) Inventors: **Ann Claire Lim Chi Cheung**, San Francisco, CA (US); **William Lark, Jr.**, Glendale, CA (US)

(73) Assignee: **Noon Home, Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/644,470**

(22) Filed: **Jul. 7, 2017**

(65) **Prior Publication Data**

US 2018/0014393 A1 Jan. 11, 2018

Related U.S. Application Data

(60) Provisional application No. 62/360,292, filed on Jul. 8, 2016.

(51) **Int. Cl.**
H05B 37/02 (2006.01)
H03K 17/96 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H05B 37/0272*** (2013.01); ***H03K 17/96*** (2013.01); ***H05B 37/0218*** (2013.01); ***H05B 37/0227*** (2013.01); *G06F 3/04847* (2013.01); *G06F 3/04883* (2013.01); *G06F 2203/04808* (2013.01)

(58) **Field of Classification Search**
CPC H05B 37/0245; H05B 37/0263; H05B 37/0272; H05B 37/0281; H05B 37/0227; H05B 37/0218; H01H 3/22; H01H 2215/00; H01H 2205/00; H03K 17/962; H03K 17/969; H03K 17/97; G06F 3/04883; G06F 3/04847; G06F 2203/04808
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,425,628 A * 1/1984 Bedard H05B 37/0254 710/8
5,990,635 A 11/1999 Ference et al.
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for App. Ser. No. PCT/US17/41070, dated Nov. 21, 2017, 10 pages.

Primary Examiner — Haissa Philogene
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

The present disclosure provides an intelligent lighting control system for automated lighting adjustments. The system includes a first light control module configured to cause a transmission of a first quantity of electrical energy to a first lighting circuit of a first light fixture electrically connected to the first lighting control module. The system transmits a control message from the first light control module to at least one second light control module configured to cause a transmission of a second quantity of electrical energy to at least one second lighting circuit of at least one second light fixture electrically connected to the at least one second lighting control module. The system changes a flow of electricity from the at least one second light control module to the at least one second lighting circuit based on the input received via the first light control module.

31 Claims, 17 Drawing Sheets