



EP 3 399 806 A1 (11)

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

07.11.2018 Bulletin 2018/45

(51) Int Cl.: H04W 52/14 (2009.01)

H04W 52/24 (2009.01)

(21) Application number: 18180438.6

(22) Date of filing: 19.07.2016

(84) Designated Contracting States: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: 25.07.2015 US 201514809201 24.08.2015 US 201514833519

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 16180195.6 / 3 125 618

(71) Applicant: Cisco Technology, Inc. San Jose, CA 95134 (US)

(72) Inventors:

· MADAN, Ritesh K. Berkeley, CA 94709 (US)

- · NABAR. Rohit Umesh Sunnyvale, CA 94087 (US)
- · CHANDRASEKHAR, Vikram Mountain View, CA 94041 (US)
- · SHIRALI, Kedar Durgadas Sunnyvale, CA 94087 (US)
- · ZHAO, Qing Fremont, CA 94539 (US)
- (74) Representative: Coates, Robert James Patterson Kilburn & Strode LLP Lacon London 84 Theobalds Road London WC1X 8NL (GB)

Remarks:

This application was filed on 28-06-2018 as a divisional application to the application mentioned under INID code 62.

SYSTEM AND METHOD TO FACILITATE SMALL CELL UPLINK POWER CONTROL IN A (54)**NETWORK ENVIRONMENT**

(57)A method is provided in one example embodiment and may include calculating, by one or more of a plurality of small cell radios, one or more sets of candidate power control parameters using a first interference constraint for uplink user equipment (UE) transmissions for UE served by the one or more of the plurality of small cell radios; determining, at a central management entity, whether an average of a sum of an expected interference for UE associated with the plurality of small cell radios violates a second interference constraint for any of the one or more sets of candidate power control parameters; and generating one or more messages for each of the plurality of small cell radios identifying one or more particular sets of power control parameters that provide for meeting the second interference constraint.

