(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) EP 3 402 108 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
14.11.2018 Bulletin 2018/46

(51) Int Cl.:
H04L 1/16 *(2006.01)*

(21) Application number: **18181360.1**

(22) Date of filing: **18.06.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

(30) Priority: **19.06.2009 JP 2009146592**
02.11.2009 JP 2009252051

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
10789258.0 / 2 445 249

(71) Applicant: **Godo Kaisha IP Bridge 1**
Tokyo 101-0051 (JP)

(72) Inventors:
- **NAKAO, Seigo**
Chiyoda-ku, Tokyo 101-0051 (JP)
- **IMAMURA, Daichi**
Chiyoda-ku, Tokyo 101-0051 (JP)

(74) Representative: **Grünecker Patent- und Rechtsanwälte**
PartG mbB
Leopoldstraße 4
80802 München (DE)

Remarks:
This application was filed on 03-07-2018 as a divisional application to the application mentioned under INID code 62.

(54) TERMINAL DEVICE AND RETRANSMISSION CONTROL METHOD

(57) Provided are a terminal device and a retransmission control method which enable the avoidance of the degradation of transmission characteristics of a response signal and the minimization of the increase of the overhead of an uplink control channel when ARQ is applied in communication using an uplink unit band and a plurality of downlink unit bands associated with the uplink unit band. In a terminal (200), a control unit (209) transmits a bundle response signal using a resource in a basic region of an uplink control channel in an uplink unit band of a unit band group when no error is detected in each of a plurality of pieces of downlink data of the unit band group, the uplink control channel in the uplink unit band being associated with a downlink control channel in a basic unit band that is a downlink unit band in which a broadcast channel signal including information relating to the uplink unit band is transmitted, and the control unit transmits the bundle response signal using a resource in an additional region of the uplink control channel when an error is detected in each of the plurality of pieces of downlink data.



FIG.6A

EP 3 402 108 A1

(Cont. next page)