

US010142596B2

(12) United States Patent Lam et al.

(54) METHOD AND APPARATUS OF SECURED INTERACTIVE REMOTE MAINTENANCE ASSIST

(71) Applicant: The United States of America as represented by the Secretary of the Navy, Washington, DC (US)

(72) Inventors: Jack Lam, Rancho Cucamonga, CA

(US); Philippe Navarro, Pasadena, CA (US); Bryan Stewart, Oxnard, CA (US); Michael Virbia, Oxnard, CA (US); Jacky Wong, Chino Hills, CA

(US)

(73) Assignee: The United States of America, as represented by the Secretary of the

Navy, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 408 days.

(21) Appl. No.: 15/057,000

(22) Filed: Feb. 29, 2016

(65) Prior Publication Data

US 2016/0253563 A1 Sep. 1, 2016

Related U.S. Application Data

(60) Provisional application No. 62/126,024, filed on Feb. 27, 2015.

(51) **Int. Cl. G06K 9/00** (2006.01) **H04N 7/18** (2006.01)
(Continued)

(10) Patent No.: US 10,142,596 B2

(45) **Date of Patent:** Nov. 27, 2018

(58) Field of Classification Search

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

6,763,148 B1 7/2004 Sternberg et al. 7,641,342 B2 1/2010 Eberl et al. (Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2009/036782 3/2009

OTHER PUBLICATIONS

Lipson, et al., Online Product Maintenance by Web-Based Augmented Reality; retrieved on 2001; 12 pages.

(Continued)

Primary Examiner — Obafemi O Sosanya (74) Attorney, Agent, or Firm — Christopher A. Monsey

(57) ABSTRACT

A system and method for using the system comprising a head mounted device (HMD), a remote maintenance server (RMS), and a control section operable to identify the system under test (SUT) using an image recognition function, to identify a plurality of subsystems (PLoS) within the SUT in a data library, to create three dimensional models of the PLoS and displaying the same on a visual interface of the HMD using an augmented reality function, to connect to the RMS using an encryption algorithm via streaming video or images sent to the RMS, to collect SUT data and external (to the SUT) sensor data, to conduct a prognostics and/or health, maintenance, and/or management (HMM) service on the collected data to determine system health and projected health of the SUT and/or PLoS, to authenticate remote user (Continued)

